

Package ‘heuristicsmineR’

March 29, 2020

Type Package

Title Discovery of Process Models with the Heuristics Miner

Version 0.2.4

Description Provides the heuristics miner algorithm for process discovery as proposed by Weijters et al. (2011) <doi:10.1109/CIDM.2011.5949453>. The algorithm builds a causal net from an event log created with the 'bupaR' package. Event logs are a set of ordered sequences of events for which 'bupaR' provides the S3 class eventlog(). The discovered causal nets can be visualised as 'htmlwidgets' and it is possible to annotate them with the occurrence frequency or processing and waiting time of process activities.

License MIT + file LICENSE

Encoding UTF-8

LazyData true

LinkingTo Rcpp, BH

SystemRequirements C++11

Depends R (>= 2.10)

Imports bupaR, processmapR (>= 0.3.1), rlang, magrittr, dplyr, tidyr, DiagrammeR (>= 1.0.0), petrinetR, purrr, scales, Rcpp, ggplot2, ggthemes, data.table, stringr

Suggests eventdataR, svgPanZoom, DiagrammeRsvg

RoxygenNote 7.1.0

URL <https://github.com/bupaverse/heuristicsmineR>

BugReports <https://github.com/bupaverse/heuristicsmineR/issues>

NeedsCompilation yes

Author Felix Mannhardt [aut, cre]

Maintainer Felix Mannhardt <felix.mannhardt@sintef.no>

Repository CRAN

Date/Publication 2020-03-29 19:50:03 UTC

R topics documented:

as.petrinet	2
causal_bindings	3
causal_custom	3
causal_frequency	4
causal_net	5
causal_performance	7
dependency_matrix	7
dependency_type_fhm	8
dependency_type_lifecycle	10
hospital_multi_perspective	11
L_heur_1	11
L_heur_2	12
parallel_matrix_lifecycle	12
plot.dependency_matrix	13
precedence_matrix	13
precedence_matrix_absolute	14
precedence_matrix_length_two_loops	15
precedence_matrix_lifecycle	15
print.causal_net	16
print.dependency_matrix	16
render_causal_net	17
render_dependency_matrix	18
Index	19

as.petrinet	<i>Converts the object to a Petrinet</i>
-------------	--

Description

Converts the object to a Petrinet

Usage

```
as.petrinet(obj)
```

Arguments

obj The event log to be used. An object of class

Examples

```
data(L_heur_1)
cn <- causal_net(L_heur_1, threshold = .8)
pn <- as.petrinet(cn)
petrinetR::render_PN(pn)
```

causal_bindings	<i>Compute input and output bindings</i>
-----------------	--

Description

Computes the input- and output bindings for use in a causal map. Several heuristics may be used to determine the activities that are activated or consumed by an event. The Flexible Heuristic Miner (FHM) paper describes a heuristic that looks ahead (or looks back) until the end of the trace and determines those activities as activated for which no other cause (activity in a causal dependency) is found. This approach is implemented as type nearest.

Usage

```
causal_bindings(eventlog, dependencies, type = c("nearest"))
```

Arguments

eventlog	The bupaR event log.
dependencies	A dependency matrix obtained, for example, through dependency_matrix .
type	The heuristic used to determine the bindings. Currently only nearest is available.

Value

A data frame

Examples

```
causal_bindings(L_heur_1,  
                dependencies = dependency_matrix(L_heur_1))
```

causal_custom	<i>Custom map profile</i>
---------------	---------------------------

Description

Function to create a custom map profile based on some event log attribute.

Usage

```
causal_custom(
  FUN = mean,
  attribute,
  units = "",
  color_scale = "RdPu",
  color_edges = "red4",
  ...
)
```

Arguments

<code>FUN</code>	A summary function to be called on the process time of a specific activity, e.g. mean, median, min, max
<code>attribute</code>	The name of the case attribute to visualize (should be numeric)
<code>units</code>	Character to be placed after values (e.g. EUR for monetary euro values)
<code>color_scale</code>	Name of color scale to be used for nodes. Defaults to RdPu See <code>Rcolorbrewer::brewer.pal.info()</code> for all options.
<code>color_edges</code>	The color used for edges. Defaults to red4.
<code>...</code>	Additional arguments forwarded to FUN

Details

If used for edges, it will show the attribute values which related to the out-going node of the edge.

Examples

```
causal_net(L_heur_1,
  type_nodes = causal_custom(attribute = "timestamp"),
  type_edges = causal_custom(attribute = "timestamp"))
```

`causal_frequency` *Frequency map profile*

Description

Function to create a frequency profile for a process map.

Usage

```
causal_frequency(
  value = c("absolute", "relative"),
  color_scale = "PuBu",
  color_edges = "dodgerblue4"
)
```

Arguments

value	The type of frequency value to be used: absolute, relative (percentage of activity instances).
color_scale	Name of color scale to be used for nodes. Defaults to PuBu. See <code>Rcolorbrewer::brewer.pal.info()</code> for all options.
color_edges	The color used for edges. Defaults to dodgerblue4.

Examples

```
causal_net(L_heur_1,
           type = causal_frequency("relative"))
```

causal_net	<i>Create a Causal net (also Heuristics net)</i>
------------	--

Description

Creates a Causal net, also known as Heuristics net. This is similar to a `processmapR` process map. However, the causal map deals with parallelism by trying to identifying causal dependencies between activities by using different heuristics as documented in [dependency_matrix](#).

Usage

```
causal_net(
  eventlog = NULL,
  dependencies = dependency_matrix(eventlog = eventlog, threshold = threshold,
  threshold_frequency = threshold_frequency, ...),
  bindings = causal_bindings(eventlog, dependencies),
  threshold = 0.9,
  threshold_frequency = 0,
  type = causal_frequency("absolute"),
  sec = NULL,
  type_nodes = type,
  type_edges = type,
  sec_nodes = sec,
  sec_edges = sec,
  ...
)
```

Arguments

eventlog	The event log for which a causal map should be computed. Can be left NULL for more control if parameters dependencies and bindings are provided directly.
dependencies	A dependency matrix created for the event log, for example, by dependency_matrix .
bindings	Causal bindings created by causal_bindings .

threshold	The dependency threshold to be used when using the default dependency matrix computation.
threshold_frequency	The frequency threshold to be used when using the default dependency matrix computation.
type	A causal map type. For example, causal_frequency or causal_performance .
sec	A causal process map type. Values are shown between brackets.
type_nodes	A causal map type to be used for nodes only.
type_edges	A causal map type to be used for edges only.
sec_nodes	A secondary causal map type for nodes only.
sec_edges	A secondary causal map type for edges only.
...	Further parameters forwarded to the default dependency_matrix function.

Details

Warning: Projected frequencies are heuristically determined and counts may not add up.

Value

A DiagrammeR graph of the causal map.

Examples

```
# Causal map with default parameters
causal_net(L_heur_1)

# Causal map with lower dependency threshold
causal_net(L_heur_1, threshold = .8)

# For even more control omit the `eventlog` parameter
# and provide `dependencies` and `bindings` directly.
d <- dependency_matrix(L_heur_1, threshold = .8)
causal_net(dependencies = d,
           bindings = causal_bindings(L_heur_1, d, "nearest"))

# The returned DiagrammeR object can be further augmented with
# panning and zooming before rendering:

library(magrittr)
causal_net(L_heur_1) %>%
  render_causal_net(render = TRUE) %>%
  DiagrammeRsvg::export_svg() %>%
  svgPanZoom::svgPanZoom()
```

causal_performance *Performance map profile*

Description

Function to create a performance profile for a causal map.

Usage

```
causal_performance(  
  FUN = mean,  
  units = c("mins", "secs", "hours", "days", "weeks", "months", "quarters",  
            "semesters", "years"),  
  color_scale = "Reds",  
  color_edges = "red4",  
  ...  
)
```

Arguments

FUN	A summary function to be called on the process time of a specific activity, e.g. mean, median, min, max
units	The time unit in which processing time should be presented (mins, hours, days, weeks, months, quarters, semesters, years. A month is defined as 30 days. A quarter is 13 weeks. A semester is 26 weeks and a year is 365 days
color_scale	Name of color scale to be used for nodes. Defaults to Reds. See <code>Rcolorbrewer::brewer.pal.info()</code> for all options.
color_edges	The color used for edges. Defaults to red4.
...	Additional arguments forwarded to FUN

Examples

```
causal_net(L_heur_1,  
           type = causal_performance())
```

dependency_matrix *Create a dependency matrix*

Description

Creates a dependency matrix from a precedence matrix ([precedence_matrix](#)) based on different approaches.

Usage

```
dependency_matrix(
  eventlog = NULL,
  dependency_type = dependency_type_fhm(threshold_dependency = threshold,
    threshold_frequency = threshold_frequency, ...),
  threshold = 0.9,
  threshold_frequency = 0,
  ...
)
```

Arguments

eventlog	A bupaR event log, may be NULL when a precedence matrix is provided.
dependency_type	Which approach to use for calculation of the dependency matrix. Currently only (dependency_type_fhm) is available.
threshold	A dependency threshold, usually in the interval [0,1], filtering out dependencies below the threshold.
threshold_frequency	An absolute frequency threshold filtering dependencies which are observed infrequently.
...	Parameters forwarded to (dependency_type_fhm).

Value

A square matrix with class `dependency_matrix` containing the computed dependency values between all activities.

See Also

[precedence_matrix](#)

Examples

```
d <- dependency_matrix(L_heur_1)
print(d)
as.matrix(d)
```

dependency_type_fhm *Dependency type based on Flexible Heuristics Miner (FHM)*

Description

Computes the dependencies based on the approach known as Flexible Heuristics Miner.

Usage

```
dependency_type_fhm(  
  threshold_dependency = 0.9,  
  threshold_l1 = threshold_dependency,  
  threshold_l2 = threshold_dependency,  
  threshold_frequency = 0,  
  all_connected = FALSE,  
  endpoints_connected = FALSE  
)
```

Arguments

threshold_dependency A dependency threshold, usually in the interval [0,1], filtering out dependencies below the threshold.

threshold_l1 A dependency threshold, usually in the interval [0,1], filtering out self-loop dependencies below the threshold.

threshold_l2 A dependency threshold, usually in the interval [0,1], filtering out length-two loop dependencies below the threshold.

threshold_frequency An absolute frequency threshold filtering dependencies which are observed infrequently.

all_connected If TRUE the best antecedent and consequent (as determined by the dependency measure) are going to be added regardless of the threshold value.

endpoints_connected If TRUE the start/end activity is added as antecedent/consequent when an activity would not be connected according to the threshold value.

Value

A dependency type.

References

A. J. M. M. Weijters and J. T. S. Ribeiro, "Flexible Heuristics Miner (FHM)," 2011 IEEE Symposium on Computational Intelligence and Data Mining (CIDM), Paris, 2011, pp. 310-317. doi: 10.1109/CIDM.2011.5949453

Examples

```
dependency_matrix(L_heur_1,  
  dependency_type = dependency_type_fhm(all_connected = TRUE))
```

dependency_type_lifecycle

Dependency type based on time intervals

Description

Computes the dependencies based on the approach taking into account activity durations based on life-cycle transitions.

Usage

```
dependency_type_lifecycle(  
  threshold_dependency = 0.9,  
  threshold_l1 = threshold_dependency,  
  threshold_frequency = 0,  
  all_connected = FALSE,  
  endpoints_connected = FALSE  
)
```

Arguments

threshold_dependency	A dependency threshold, usually in the interval [0,1], filtering out dependencies below the threshold.
threshold_l1	A dependency threshold, usually in the interval [0,1], filtering out self-loop dependencies below the threshold.
threshold_frequency	An absolute frequency threshold filtering dependencies which are observed infrequently.
all_connected	If TRUE the best antecedent and consequent (as determined by the dependency measure) are going to be added regardless of the threshold value.
endpoints_connected	If TRUE the start/end activity is added as antecedent/consequent when an activity would not be connected according to the threshold value.

Value

A dependency type.

References

A. Burattin and A. Sperduti, "Heuristics Miner for Time Intervals," in ESANN 2010, 18th European Symposium on Artificial Neural Networks, Bruges, Belgium, April 28-30, 2010, Proceedings, 2010.

Examples

```
dependency_matrix(L_heur_1,  
                  dependency_type = dependency_type_fhm(all_connected = TRUE))
```

hospital_multi_perspective

Hospital example event log capturing multi-perspectives

Description

Sample of 10 000 traces from an artificial eventlog from the PhD thesis 'Multi-perspective Process Mining' used to illustrate the Data-aware Heuristic Miner algorithm.

Usage

```
hospital_multi_perspective
```

Format

Eventlog containing a sample of 10 000 cases

Source

<https://data.4tu.nl/repository/uuid:32cad43f-8bb9-46af-8333-48aae2bea037>

References

Mannhardt, F. (Felix) (2016) Data-driven Process Discovery - Artificial Event Log. Eindhoven University of Technology. Dataset. <https://doi.org/10.4121/uuid:32cad43f-8bb9-46af-8333-48aae2bea037>

L_heur_1

Heuristics miner example log #1

Description

Artificial eventlog for illustrating Heuristics Miner published as supplementary material to the book Process Mining: Discovery, Conformance and Enhancement of Business Processes.

Usage

```
L_heur_1
```

Format

Eventlog containing 40 cases

Source

http://www.processmining.org/event_logs_and_models_used_in_book

References

Process Mining: Discovery, Conformance and Enhancement of Business Processes by W.M.P. van der Aalst, Springer Verlag, 2011 (ISBN 978-3-642-19344-6).

L_heur_2

Heuristics miner example log #2

Description

Artificial eventlog for illustrating Heuristics Miner published as supplementary material to the book Process Mining: Discovery, Conformance and Enhancement of Business Processes.

Usage

L_heur_2

Format

Eventlog containing 85 cases

Source

http://www.processmining.org/event_logs_and_models_used_in_book

References

Process Mining: Discovery, Conformance and Enhancement of Business Processes by W.M.P. van der Aalst, Springer Verlag, 2011 (ISBN 978-3-642-19344-6).

parallel_matrix_lifecycle

Parallel Matrix with Lifecycle

Description

Parallel Matrix with Lifecycle

Usage

parallel_matrix_lifecycle(eventlog)

Arguments

eventlog The event log object to be used.

Examples

```
parallel_matrix_lifecycle(L_heur_1)
```

```
plot.dependency_matrix
```

Dependency matrix plot

Description

Visualize a dependency matrix. A generic plot function for dependency matrices.

Usage

```
## S3 method for class 'dependency_matrix'
plot(x, ...)
```

Arguments

x Dependency matrix
 ... Additional parameters

Value

A ggplot object, which can be customized further, if deemed necessary.

```
precedence_matrix        Precedence Matrix
```

Description

Construct a precedence matrix, showing how activities are followed by each other. This is a performance improved variant of [precedence_matrix](#) in the processmapR package.

Usage

```
precedence_matrix(  
  eventlog,  
  type = c("absolute", "relative", "relative-antecedent", "relative-consequent",  
           "relative-case")  
)
```

Arguments

eventlog	The event log object to be used
type	The type of precedence matrix, which can be absolute, relative, relative-antecedent or relative-consequent. Absolute will return a matrix with absolute frequencies, relative will return global relative frequencies for all antecedent-consequent pairs. Relative-antecedent will return relative frequencies within each antecedent, i.e. showing the relative proportion of consequents within each antecedent. Relative-consequent will do the reverse.

Examples

```
m <- precedence_matrix(hospital_multi_perspective, type = "absolute")
print(m)
as.matrix(m)
```

precedence_matrix_absolute

Precedence Matrix

Description

Construct a precedence matrix, showing how activities are followed by each other. This function computes the precedence matrix directly in C++ for efficiency. Only the type absolute of ([precedence_matrix](#)) is supported.

Usage

```
precedence_matrix_absolute(eventlog, lead = 1)
```

Arguments

eventlog	The event log object to be used.
lead	The distance between activities following/preceding each other.

Examples

```
library(eventdataR)
data(traffic_fines)
m <- precedence_matrix_absolute(traffic_fines)
print(m)
as.matrix(m)
```

precedence_matrix_length_two_loops

Length Two Loop Precedence Matrix

Description

Construct a precedence matrix counting how often pattern aba occurs.

Usage

```
precedence_matrix_length_two_loops(eventlog)
```

Arguments

eventlog The event log object to be used.

Examples

```
m <- precedence_matrix_length_two_loops(hospital_multi_perspective)
print(m)
as.matrix(m)
```

precedence_matrix_lifecycle

Precedence Matrix with Lifecycle

Description

Precedence Matrix with Lifecycle

Usage

```
precedence_matrix_lifecycle(eventlog)
```

Arguments

eventlog The event log object to be used.

Examples

```
precedence_matrix_lifecycle(L_heur_1)
```

print.causal_net *Generic print function for a Causal net*

Description

Generic print function for a Causal net

Usage

```
## S3 method for class 'causal_net'  
print(x, ...)
```

Arguments

x	Causal net object
...	Additional Arguments

print.dependency_matrix
Generic print function for a dependency matrix

Description

Generic print function for a dependency matrix

Usage

```
## S3 method for class 'dependency_matrix'  
print(x, ...)
```

Arguments

x	dependency matrix object
...	Additional Arguments

render_causal_net *Renders a Causal net as graph*

Description

Renders a Causal net as graph

Usage

```
render_causal_net(  
  causal_net,  
  rankdir = "LR",  
  layout = "dot",  
  render = T,  
  fixed_edge_width = F,  
  fixed_node_pos = NULL,  
  ...  
)
```

Arguments

causal_net	A causal net created by causal_net
rankdir	Rankdir to be used for DiagrammeR.
layout	Layout to be used for DiagrammeR.
render	Whether to directly render the DiagrammeR graph or simply return it.
fixed_edge_width	If TRUE, don't vary the width of edges.
fixed_node_pos	When specified as a data.frame with three columns 'act', 'x', and 'y' the position of nodes is fixed. Note that this can only be used with the 'neato' layout engine.
...	Further parameters forwarded to the DiagrammeR render function.

Value

A DiagrammeR graph of the Causal net.

Examples

```
render_causal_net(causal_net(L_heur_1))
```

`render_dependency_matrix`*Renders a dependency matrix as dependency graph*

Description

Creates a dependency graph visualizing the contents of a dependency matrix.

Usage

```
render_dependency_matrix(  
  dependencies,  
  rankdir = "LR",  
  layout = "dot",  
  render = T  
)
```

Arguments

<code>dependencies</code>	A dependency matrix created by dependency_matrix
<code>rankdir</code>	Rankdir to be used for DiagrammeR.
<code>layout</code>	Layout to be used for DiagrammeR.
<code>render</code>	Whether to directly render the DiagrammeR graph or simply return it.

Value

A DiagrammeR graph of the (filtered) dependency matrix.

Examples

```
render_dependency_matrix(dependency_matrix(L_heur_1))
```

Index

*Topic **datasets**

- hospital_multi_perspective, [11](#)
 - L_heur_1, [11](#)
 - L_heur_2, [12](#)

as.petrinet, [2](#)

causal_bindings, [3](#), [5](#)

causal_custom, [3](#)

causal_frequency, [4](#), [6](#)

causal_net, [5](#), [17](#)

causal_performance, [6](#), [7](#)

dependency_matrix, [3](#), [5](#), [6](#), [7](#), [18](#)

dependency_type_fhm, [8](#), [8](#)

dependency_type_lifecycle, [10](#)

hospital_multi_perspective, [11](#)

L_heur_1, [11](#)

L_heur_2, [12](#)

parallel_matrix_lifecycle, [12](#)

plot.dependency_matrix, [13](#)

precedence_matrix, [7](#), [8](#), [13](#), [13](#), [14](#)

precedence_matrix_absolute, [14](#)

precedence_matrix_length_two_loops, [15](#)

precedence_matrix_lifecycle, [15](#)

print.causal_net, [16](#)

print.dependency_matrix, [16](#)

render_causal_net, [17](#)

render_dependency_matrix, [18](#)