

Package ‘rasciidoc’

February 18, 2021

Title Create Reports Using R and 'asciidoc'

Version 3.1.1

Description Inspired by Karl Broman`s reader on using 'knitr' with 'asciidoc' (http://kbroman.org/knitr_knutshell/pages/asciidoc.html), this is merely a wrapper to 'knitr' and 'asciidoc'.

License BSD_2_clause + file LICENSE

URL <https://gitlab.com/fvafrcu/rasciidoc>

Depends R (>= 3.3.0)

Imports checkmate, document (>= 3.3.0), fritools (>= 1.3.0), gert, highr, knitr, reticulate, tools

Suggests devtools, pkgload, rasciidoc, rmarkdown, rprojroot, RUnit, testthat, withr

Encoding UTF-8

LazyData true

RoxygenNote 7.1.1

SystemRequirements python >= 2.6, by default rasciidoc uses a system installation of asciidoc. If a system installation of asciidoc is not available, it downloads the sources from (<http://gitlab.com/asciidoc>). GNU source-highlight is recommended.

VignetteBuilder rasciidoc

NeedsCompilation no

Author Andreas Dominik Cullmann [aut, cre]

Maintainer Andreas Dominik Cullmann <fvafrcu@mailbox.org>

Repository CRAN

Date/Publication 2021-02-18 17:20:02 UTC

R topics documented:

rasciidoc-package	2
adjust_asciidoc_hooks	2
rasciidoc	3
render	4

Index	7
--------------	----------

rasciidoc-package	<i>Create Reports Using R and asciidoc</i>
-------------------	--

Description

Inspired by Karl Broman's reader on using **knitr** with asciidoc (http://kbroman.org/knitr_knutshell/pages/asciidoc.html), this is merely a wrapper to **knitr** and asciidoc.

Arguments

`write_to_disk` Write to disk? See **Warning**.

Details

You will find the details in `vignette("An_Introduction_to_rasciidoc", package = "rasciidoc")`.

Warning

Due to the CRAN policy of not writing "anywhere else on the file system apart from the R session's temporary directory", we work on a temporary copy of `file_name`. Thus all internal sourcing and internal links will be broken and any output is written to `tempdir()`. Set the option "write_to_disk" to TRUE (using `options(write_to_disk = TRUE)`) to bypass this. You may want to include the above line into your `~/.Rprofile`.

adjust_asciidoc_hooks	<i>Adjust knitr's Hooks for asciidoc</i>
-----------------------	---

Description

By default, **knitr** renders messages, warnings and errors to [NOTE|WARNING|ERROR]-blocks in asciidoc, which is ... not my choice. To restore **knitr**'s behaviour, set `hooks` or `replacement` to `NULL`.

Usage

```
adjust_asciidoc_hooks(
  hooks = c("message", "error", "warning"),
  replacement = "source"
)
```

Arguments

`hooks` Character vector naming the output hooks to be replaced by the replacement's hooks.

`replacement` The hook with which to replace the hooks given by `hooks`.

Details

This is a modified version of `render_asciidoc` of **knitr** version 1.18.7.

Value

The return value of `knit_hooks$set`, invisibly `NULL`, currently.

rasciidoc

Render an asciidoc File

Description

This is the basic interface to asciidoc. Not more than a call to `system2` and checks on asciidoc and source-highlight. You should usually not call it directly, see `render` for a wrapper.

Usage

```
rasciidoc(
  file_name,
  ...,
  write_to_disk = getOption("write_to_disk"),
  enforce_requirements = getOption("enforce_requirements")
)
```

Arguments

`file_name` The file to run asciidoc on.

`...` arguments passed to asciidoc via `system2`.

`write_to_disk` Write to disk? See **Warning**.

`enforce_requirements` Should system requirements be enforced (CRAN requires packages to pass checks if system requirements (external commands) are not met)? Set to `TRUE` to enforce.

Value

Invisibly `TRUE` or `FALSE`, depending on success.

Warning

Due to the CRAN policy of not writing "anywhere else on the file system apart from the R session's temporary directory", we work on a temporary copy of `file_name`. Thus all internal sourcing and internal links will be broken and any output is written to `tempdir()`. Set the option "write_to_disk" to `TRUE` (using `options(write_to_disk = TRUE)`) to bypass this. You may want to include the above line into your `~/.Rprofile`.

See Also

[render](#)

Examples

```
# CRAN complains about elapsed times
if (fritools::is_running_on_fvafrcu_machines()) {
  wd <- file.path(tempdir(), "rasciidoc")
  dir.create(wd)
  file <- system.file("files", "minimal", "knit.asciidoc",
                     package = "rasciidoc")
  file.copy(file, wd)
  rasciidoc::rasciidoc(file_name = file.path(wd, basename(file)),
                      write_to_disk = getOption("write_to_disk"),
                      "-b html")
  if (isTRUE(getOption("write_to_disk"))) {
    dir(wd, full.names = TRUE)
  } else {
    dir(tempdir(), full.names = TRUE)
  }
  unlink(wd, recursive = TRUE)
}
```

render

Spin or Knit and Render a ‘Rasciidoc’ File

Description

Spin or Knit (if required) and render an ‘Rasciidoc’ file.

Usage

```
render(
  file_name,
  knit = NA,
```

```

write_to_disk = getOption("write_to_disk"),
envir = parent.frame(),
hooks = c("message", "error", "warning"),
replacement = "source",
asciidoc_args = "-b html",
what = c("auto", "all", "no_slides", "slides"),
clean = FALSE,
...
)

```

Arguments

<code>file_name</code>	The file to render.
<code>knit</code>	Knit the file first using <code>knitr::knit</code> ? If set to <code>NA</code> , knitting is based on the file's contents or name. Set to <code>TRUE</code> to force knitting or to <code>FALSE</code> , to disable knitting.
<code>write_to_disk</code>	Write to disk? See Warning .
<code>envir</code>	The frame in which to render.
<code>hooks</code>	Character vector naming the output hooks to be replaced by the replacement's hooks.
<code>replacement</code>	The hook with which to replace the hooks given by hooks.
<code>asciidoc_args</code>	arguments passed to asciidoc via <code>system2</code> .
<code>what</code>	What is to be rendered? "all" renders everything, "no_slides" renders parts that are not meant for slides, "slides" renders parts that are meant for slides. The defaults looks for any in- or exclusion tagging and renders parts that are not meant for slides if found any, else it renders everything.
<code>clean</code>	Remove temporary file(s)?
<code>...</code>	Only there to register as vignette engine. Do not use!

Value

The return value of `rasciidoc`.

Warning

Due to the CRAN policy of not writing "anywhere else on the file system apart from the R session's temporary directory", we work on a temporary copy of `file_name`. Thus all internal sourcing and internal links will be broken and any output is written to `tempdir()`. Set the option "write_to_disk" to `TRUE` (using

```
options(write_to_disk = TRUE)
```

to bypass this. You may want to include the above line into your `~/.Rprofile`.

See Also

[rasciidoc](#)

Examples

```
# CRAN complains about elapsed times
if (fritools::is_running_on_fvafrcu_machines()) {
  wd <- file.path(tempdir(), "rasciidoc")
  dir.create(wd)
  file <- system.file("files", "minimal", "knit.Rasciidoc",
                     package = "rasciidoc")
  file.copy(file, wd)
  rasciidoc::render(file.path(wd, basename(file)),
                   write_to_disk = getOption("write_to_disk"),
                   asciidoc_args = "-b slidy")
  if (isTRUE(getOption("write_to_disk"))) {
    dir(wd, full.names = TRUE)
  } else {
    dir(tempdir(), full.names = TRUE)
  }
  unlink(wd, recursive = TRUE)
}
```

Index

* package

rasciidoc-package, 2

adjust_asciidoc_hooks, 2

FALSE, 4, 5

Invisibly, 4

invisibly, 3

knit_hooks, 3

knitr::knit, 5

NA, 5

NULL, 2, 3

rasciidoc, 3, 5

rasciidoc-package, 2

render, 3, 4, 4

system2, 3, 5

TRUE, 3–5