

Package ‘MDFS’

February 9, 2021

Title MultiDimensional Feature Selection

Version 1.2.0

Date 2021-02-09

URL <https://featureselector.uco.uwb.edu.pl/software/mdfs/>

Description Functions for MultiDimensional Feature Selection (MDFS):
calculating multidimensional information gains, scoring variables,
finding important variables, plotting selection results.

This package includes an optional CUDA implementation that speeds up
information gain calculation using NVIDIA GPGPUs.

R. Piliszek et al. (2019) <doi:10.32614/RJ-2019-019>.

Depends R (>= 3.4.0)

License GPL-3

SystemRequirements C++11

NeedsCompilation yes

Encoding UTF-8

LazyData true

RoxygenNote 7.1.1

Author Radosław Piliszek [aut, cre],

Krzysztof Mnich [aut],

Paweł Tabaszewski [aut],

Szymon Migacz [aut],

Andrzej Sulecki [aut],

Witold Remigiusz Rudnicki [aut]

Maintainer Radosław Piliszek <r.piliszek@uwb.edu.pl>

Repository CRAN

Date/Publication 2021-02-09 18:00:02 UTC

R topics documented:

AddContrastVariables 2

as.data.frame.MDFS	3
ComputeInterestingTuples	3
ComputeMaxInfoGains	5
ComputePValue	6
Discretize	8
madelon	9
MDFS	9
plot.MDFS	11
RelevantVariables	11
RelevantVariables.MDFS	12

Index	13
--------------	-----------

AddContrastVariables *Add contrast variables to data*

Description

Add contrast variables to data

Usage

```
AddContrastVariables(data, n.contrast = max(ncol(data)/10, 30))
```

Arguments

data	data organized in matrix with separate variables in columns
n.contrast	number of contrast variables (defaults to max of 1/10 of variables number and 30)

Value

A list with the following key names:

- indices – vector of indices of input variables used to construct contrast variables
- x – data with contrast variables appended to it
- mask – vector of booleans making it easy to select just contrast variables

Examples

```
AddContrastVariables(madelon$data)
```

as.data.frame.MDFS *as.data.frame S3 method implementation for MDFS*

Description

as.data.frame S3 method implementation for MDFS

Usage

```
## S3 method for class 'MDFS'
as.data.frame(x, ...)
```

Arguments

x	an MDFS object
...	ignored

Value

data.frame

ComputeInterestingTuples
Interesting tuples

Description

Interesting tuples

Usage

```
ComputeInterestingTuples(
  data,
  decision,
  dimensions = 2,
  divisions = NULL,
  discretizations = 1,
  seed = NULL,
  range = NULL,
  pc.xi = 0.25,
  ig.thr = 0,
  I.lower,
  interesting.vars = vector(mode = "integer"),
  require.all.vars = FALSE,
  return.matrix = FALSE
)
```

Arguments

<code>data</code>	input data where columns are variables and rows are observations (all numeric)
<code>decision</code>	decision variable as a binary sequence of length equal to number of observations
<code>dimensions</code>	number of dimensions (a positive integer; 5 max) - FIXME: only 2D supported for now!
<code>divisions</code>	number of divisions (from 1 to 15; NULL selects probable optimal number)
<code>discretizations</code>	number of discretizations
<code>seed</code>	seed for PRNG used during discretizations (NULL for random)
<code>range</code>	discretization range (from 0.0 to 1.0; NULL selects probable optimal number)
<code>pc.xi</code>	parameter xi used to compute pseudocounts (the default is recommended not to be changed)
<code>ig.thr</code>	IG threshold above which the tuple is interesting (0 and negative mean no filtering)
<code>I.lower</code>	IG values computed for lower dimension (1D for 2D, etc.)
<code>interesting.vars</code>	variables for which to check the IGs (none = all)
<code>require.all.vars</code>	boolean whether to require tuple to consist of only interesting.vars
<code>return.matrix</code>	boolean whether to return a matrix instead of a list (ignored if not using the optimised method variant)

Details

If no filtering is applied, this function is able to run in an optimised fashion. It is recommended to avoid filtering if only it is feasible.

Value

A `data.frame` or `NULL` (following a warning) if no tuples are found.

The following columns are present in the `data.frame`:

- `Var` – interesting variable index
- `Tuple.1, Tuple.2, ...` – corresponding tuple (up to dimensions columns)
- `IG` – information gain achieved by `var` in `Tuple.*`

Additionally attribute named `run.params` with run parameters is set on the result.

Examples

```
ig.1d <- ComputeMaxInfoGains(madelon$data, madelon$decision, dimensions = 1, divisions = 1,
                             range = 0, seed = 0)
ComputeInterestingTuples(madelon$data, madelon$decision, dimensions = 2, divisions = 1,
                        range = 0, seed = 0, ig.thr = 100, I.lower = ig.1d$IG)
```

ComputeMaxInfoGains *Max information gains*

Description

Max information gains

Usage

```

ComputeMaxInfoGains(
  data,
  decision,
  dimensions = 1,
  divisions = NULL,
  discretizations = 1,
  seed = NULL,
  range = NULL,
  pc.xi = 0.25,
  return.tuples = FALSE,
  return.min = FALSE,
  interesting.vars = vector(mode = "integer"),
  require.all.vars = FALSE,
  use.CUDA = FALSE
)

```

Arguments

<code>data</code>	input data where columns are variables and rows are observations (all numeric)
<code>decision</code>	decision variable as a binary sequence of length equal to number of observations
<code>dimensions</code>	number of dimensions (a positive integer; 5 max)
<code>divisions</code>	number of divisions (from 1 to 15; additionally limited by dimensions if using CUDA; NULL selects probable optimal number)
<code>discretizations</code>	number of discretizations
<code>seed</code>	seed for PRNG used during discretizations (NULL for random)
<code>range</code>	discretization range (from 0.0 to 1.0; NULL selects probable optimal number)
<code>pc.xi</code>	parameter xi used to compute pseudocounts (the default is recommended not to be changed)
<code>return.tuples</code>	whether to return tuples (and relevant discretization number) where max IG was observed (one tuple and relevant discretization number per variable) - not supported with CUDA nor in 1D
<code>return.min</code>	whether to return min instead of max (per tuple, always max per discretization) - not supported with CUDA

interesting.vars variables for which to check the IGs (none = all) - not supported with CUDA
 require.all.vars boolean whether to require tuple to consist of only interesting.vars
 use.CUDA whether to use CUDA acceleration (must be compiled with CUDA)

Value

A `data.frame` with the following columns:

- IG – max information gain (of each variable)
- Tuple.1, Tuple.2, ... – corresponding tuple (up to dimensions columns, available only when `return.tuples == T`)
- Discretization.nr – corresponding discretization number (available only when `return.tuples == T`)

Additionally attribute named `run.params` with run parameters is set on the result.

Examples

```
ComputeMaxInfoGains(madelon$data, madelon$decision, dimensions = 2, divisions = 1,
                    range = 0, seed = 0)
```

ComputePValue

Compute p-values from information gains and return MDFS

Description

Compute p-values from information gains and return MDFS

Usage

```
ComputePValue(
  IG,
  dimensions,
  divisions,
  response.divisions = 1,
  df = NULL,
  contrast.mask = NULL,
  ig.in.bits = TRUE,
  ig.doubled = FALSE,
  one.dim.mode = "exp",
  irr.vars.num = NULL,
  ign.low.ig.vars.num = NULL,
  min.irr.vars.num = NULL,
```

```

    max.ign.low.ig.vars.num = NULL,
    search.points = 8,
    level = 0.05
)

```

Arguments

IG	max conditional information gains
dimensions	number of dimensions
divisions	number of divisions
response.divisions	number of response divisions (i.e. categories-1)
df	vector of degrees of freedom for each variable (optional)
contrast.mask	boolean mask on IG specifying which variables are contrast variables (or NULL if none, otherwise at least 3 variables must be marked)
ig.in.bits	TRUE if input is in binary log (as opposed to natural log)
ig.doubled	TRUE if input is doubled (to follow the chi-squared distribution)
one.dim.mode	'exp' for exponential distribution, 'lin' for linear function of chi-squared or 'raw' for raw chi-squared
irr.vars.num	if not NULL, number of irrelevant variables, specified by the user
ign.low.ig.vars.num	if not NULL, number of ignored low IG variables, specified by the user
min.irr.vars.num	minimum number of irrelevant variables (NULL selects probable optimal number)
max.ign.low.ig.vars.num	maximum number of ignored low IG variables (NULL selects probable optimal number)
search.points	number of points in search procedure for the optimal number of ignored variables
level	acceptable error level of goodness-of-fit one-sample Kolmogorov-Smirnov test (used only for warning)

Value

A [data.frame](#) with class set to MDFS. Can be coerced back to [data.frame](#) using [as.data.frame](#).

The following columns are present:

- IG – information gains (input copy)
- chi.squared.p.value – chi-squared p-values
- p.value – theoretical p-values

Additionally the following [attributes](#) are set:

- run.params – run parameters

- `sq.dev` – vector of square deviations used to estimate the number of irrelevant variables
- `dist.param` – distribution parameter
- `err.param` – squared error of the distribution parameter
- `fit.p.value` – p-value of fit

Examples

```
ComputePValue(madelon$IG.2D, dimensions = 2, divisions = 1)
```

Discretize

Discretize variable on demand

Description

Discretize variable on demand

Usage

```
Discretize(data, variable.idx, divisions, discretization.nr, seed, range)
```

Arguments

<code>data</code>	input data where columns are variables and rows are observations (all numeric)
<code>variable.idx</code>	variable index (as it appears in data)
<code>divisions</code>	number of divisions
<code>discretization.nr</code>	discretization number (positive integer)
<code>seed</code>	seed for PRNG
<code>range</code>	discretization range

Value

Discretized variable.

Examples

```
Discretize(madelon$data, 3, 1, 1, 0, 0.5)
```

madelon	<i>An artificial dataset called MADELON</i>
---------	---------------------------------------------

Description

An artificial dataset containing data points grouped in 32 clusters placed on the vertices of a five dimensional hypercube and randomly labeled 0/1.

Usage

madelon

Format

A list of two elements:

data 2000 by 500 matrix of 2000 objects with 500 features

decision vector of 2000 decisions (labels 0/1)

IG.2D example 2D IG computed using ComputeMaxInfoGains

Details

The five dimensions constitute 5 informative features. 15 linear combinations of those features are added to form a set of 20 (redundant) informative features. There are 480 distractor features called 'probes' having no predictive power.

Included is the original training set with label -1 changed to 0.

Source

<https://archive.ics.uci.edu/ml/datasets/Madelon>

MDFS	<i>Run end-to-end MDFS</i>
------	----------------------------

Description

Run end-to-end MDFS

Usage

```
MDFS(
  data,
  decision,
  n.contrast = max(ncol(data)/10, 30),
  dimensions = 1,
  divisions = NULL,
  discretizations = 1,
  range = NULL,
  pc.xi = 0.25,
  p.adjust.method = "holm",
  level = 0.05,
  seed = NULL,
  use.CUDA = FALSE
)
```

Arguments

<code>data</code>	input data where columns are variables and rows are observations (all numeric)
<code>decision</code>	decision variable as a boolean vector of length equal to number of observations
<code>n.contrast</code>	number of contrast variables (defaults to max of 1/10 of variables number and 30)
<code>dimensions</code>	number of dimensions (a positive integer; on CUDA limited to 2–5 range)
<code>divisions</code>	number of divisions (from 1 to 15; NULL selects probable optimal number)
<code>discretizations</code>	number of discretizations
<code>range</code>	discretization range (from 0.0 to 1.0; NULL selects probable optimal number)
<code>pc.xi</code>	parameter xi used to compute pseudocounts (the default is recommended not to be changed)
<code>p.adjust.method</code>	method as accepted by <code>p.adjust</code> ("BY" is recommended for FDR, see Details)
<code>level</code>	statistical significance level
<code>seed</code>	seed for PRNG used during discretizations (NULL for random)
<code>use.CUDA</code>	whether to use CUDA acceleration (must be compiled with CUDA)

Details

In case of FDR control it is recommended to use Benjamini-Hochberg-Yekutieli p-value adjustment method ("BY" in `p.adjust`) due to unknown dependencies between tests.

Value

A `list` with the following fields:

- `contrast.indices` – indices of variables chosen to build contrast variables
- `contrast.variables` – built contrast variables

- MIG.Result – result of ComputeMaxInfoGains
- MDFS – result of ComputePValue (the MDFS object)
- statistic – vector of statistic's values (IGs) for corresponding variables
- p.value – vector of p-values for corresponding variables
- adjusted.p.value – vector of adjusted p-values for corresponding variables
- relevant.variables – vector of relevant variables indices

Examples

```
MDFS(madelon$data, madelon$decision, dimensions = 2, divisions = 1,
     range = 0, seed = 0)
```

plot.MDFS

Plot MDFS details

Description

Plot MDFS details

Usage

```
## S3 method for class 'MDFS'
plot(x, plots = c("ig", "c", "p"), ...)
```

Arguments

x	an MDFS object
plots	plots to plot (ig for max IG, c for chi-squared p-values, p for p-values)
...	passed on to plot

RelevantVariables

Find indices of relevant variables

Description

Find indices of relevant variables

Usage

```
RelevantVariables(fs, ...)
```

Arguments

fs feature selector
... arguments passed to methods

Value

indices of important variables

RelevantVariables.MDFS

Find indices of relevant variables from MDFS

Description

Find indices of relevant variables from MDFS

Usage

```
## S3 method for class 'MDFS'  
RelevantVariables(fs, level = 0.05, p.adjust.method = "holm", ...)
```

Arguments

fs an MDFS object
level statistical significance level
p.adjust.method method as accepted by `p.adjust` ("BY" is recommended for FDR, see Details)
... ignored

Details

In case of FDR control it is recommended to use Benjamini-Hochberg-Yekutieli p-value adjustment method ("BY" in `p.adjust`) due to unknown dependencies between tests.

Value

indices of relevant variables

Index

* datasets

madelon, [9](#)

AddContrastVariables, [2](#)

as.data.frame, [7](#)

as.data.frame.MDFS, [3](#)

attributes, [7](#)

ComputeInterestingTuples, [3](#)

ComputeMaxInfoGains, [5](#)

ComputePValue, [6](#)

data.frame, [4](#), [6](#), [7](#)

Discretize, [8](#)

list, [10](#)

madelon, [9](#)

MDFS, [9](#)

NULL, [4](#)

p.adjust, [10](#), [12](#)

plot, [11](#)

plot.MDFS, [11](#)

RelevantVariables, [11](#)

RelevantVariables.MDFS, [12](#)