

Package ‘WorldFlora’

September 23, 2021

Type Package

Title Standardize Plant Names According to World Flora Online
Taxonomic Backbone

Version 1.9

Date 2021-9-21

Author Roeland Kindt [cre, aut] (<<https://orcid.org/0000-0002-7672-0712>>)

Maintainer Roeland Kindt <R.KINDT@CGIAR.ORG>

Description World Flora Online is an online flora of all known plants, available from <<http://www.worldfloraonline.org/>>. Methods are provided of matching a list of plant names (scientific names, taxonomic names, botanical names) against a static copy of the World Flora Online Taxonomic Backbone data that can be downloaded from the World Flora Online website. The World Flora Online Taxonomic Backbone is an updated version of The Plant List (<<http://www.theplantlist.org/>>), a working list of plant names that has become static since 2013.

License GPL-3

Depends R (>= 3.5.0)

Suggests data.table, utils, stringr

NeedsCompilation no

Repository CRAN

Date/Publication 2021-09-23 07:20:02 UTC

R topics documented:

new.backbone	2
vascular.families	4
WFO.example	5
WFO.match	5
WFO.prepare	12
WFO.remember	14

Index	16
--------------	-----------

 new.backbone

Develop a User-created Taxonomic Backbone data set

Description

Instead of using the taxonomic backbone data set from World Flora Online, it is possible to use matching functions of WorldFlora with alternative taxonomic backbone. The function creates new variables that correspond to key variables in the World Flora Online backbone so that matching functions WFO.match and WFO.one can be applied.

Usage

```
new.backbone(x,
  taxonID = "taxonID", scientificName = "scientificName",
  scientificNameAuthorship = "scientificNameAuthorship",
  acceptedNameUsageID = NULL, taxonomicStatus = NULL
)
```

Arguments

x	data.frame with the variables.
taxonID	name of the variable with the identification
scientificName	name of the variable with the full taxon name
scientificNameAuthorship	name of the variable with the naming authors
acceptedNameUsageID	ID of the record with the current (accepted) name. Should respond to an ID in the 'taxonID' column. In case the taxonomic name is current, then this field should be left blank. This field is used by function WFO.match to find the accepted name of a species.
taxonomicStatus	Variable that indicates whether the record is for a current name or a synonym. This variable is used by function WFO.one to discriminate situations where best matches include matches with current names and synonyms.

Details

This function allows a user to create a new taxonomic backbone data set that is understood by WFO.match and WFO.one.

Alternative examples with the Mammal Diversity Database (<https://www.mammaldiversity.org/>) and the World Checklist of Vascular Plants (<https://wcvp.science.kew.org/>) are provided in the Kindt 2021a,b R Pubs.

Value

The function returns a `data.table` that can be understood by `WFO.match` and `WFO.one` for standardizing taxonomic names.

Author(s)

Roeland Kindt (World Agroforestry)

References

- Kindt, R. 2021a. Standardizing mammal species names with the Mammal Species Database via exact and fuzzy matching functions from the WorldFlora package. <https://rpubs.com/Roeland-KINDT>
- Kindt, R. 2021b. Standardizing GlobalTreeSearch tree species names with World Flora Online and the World Checklist of Vascular Plants <https://rpubs.com/Roeland-KINDT>

See Also

[WFO.match](#), [WFO.one](#)

Examples

```
## Not run:

# load the World Flora Online taxonomic backbone
WFO.remember()

# get a list of Sapotaceae species
Sapotaceae <- WFO.data[WFO.data$family == "Sapotaceae",]
Sapotaceae <- Sapotaceae[Sapotaceae$taxonRank == "SPECIES", ]
Sapotaceae <- Sapotaceae[Sapotaceae$taxonomicStatus == "Accepted", ]
Sapotaceae <- Sapotaceae[, c("scientificName", "scientificNameAuthorship")]
Sapotaceae <- data.frame(ID = c(1:nrow(Sapotaceae)), Sapotaceae)
names(Sapotaceae)[2:3] <- c("species.name", "author")
head(Sapotaceae)

# create a new backbone from the GlobalTreeSearch database,
# after copying locally from https://tools.bgci.org/global_tree_search.php
GTS.dir <- "E://Roeland//R//World Flora Online//2021"
GTS <- read.csv(paste0(GTS.dir, "//global_tree_search.csv"))
GTS <- GTS[, 1:2]
GTS <- data.frame(GTS.ID = paste0("GTS-", c(1:nrow(GTS))), GTS)
nrow(GTS)

# create the new backbone
GTS.data <- new.backbone(GTS,
                        taxonID="GTS.ID",
                        scientificName="TaxonName",
                        scientificNameAuthorship="Author")

head(GTS.data)
```

```
# Check and standardize Sapotaceae
Sapotaceae.match <- WFO.one(WFO.match(Sapotaceae,
                                     WFO.data = GTS.data,
                                     spec.name = "species.name",
                                     Authorship = "author"))

nrow(Sapotaceae.match[Sapotaceae.match$Fuzzy == FALSE, ] )
nrow(Sapotaceae.match[Sapotaceae.match$Fuzzy == TRUE &
                      Sapotaceae.match$Fuzzy.dist < 4, ] )
Sapotaceae.match[Sapotaceae.match$Fuzzy == TRUE &
                  Sapotaceae.match$Fuzzy.dist < 4,
                  c("ID", "species.name", "Fuzzy.dist", "scientificName")]

## End(Not run)
```

 vascular.families

Orders and Higher Level Classifications of Vascular Plants

Description

This data set lists orders for families of vascular plants (angiosperms, gymnosperms and pteridophytes). For angiosperms, information from orders and higher levels of classification correspond to the fourth update of the Angiosperm Phylogeny Group (APG IV, doi: [10.1111/boj.12385](https://doi.org/10.1111/boj.12385)). Higher levels of classification correspond to names of nodes of the consensus tree (Figure 1 in doi: [10.1111/boj.12385](https://doi.org/10.1111/boj.12385)). Orders for gymnosperms and pteridophytes were obtained from <http://www.mobot.org/MOBOT/research/APweb/>.

Usage

```
data(vascular.families)
```

Format

A data frame with 476 observations on the following 10 variables.

Group Group.

Family.ID Unique ID for each family. For angiosperms, these correspond to APG IV.

Family Name of the plant family.

Family.taxonID taxonID retrieved from World Flora Online.

Order Name of the plant order.

Order.taxonID taxonID retrieved from World Flora Online.

Node.1 Name of the node in the consensus tree.

Node.2 Name of the node in the consensus tree, with Node.2 nested within Node.1.

Node.3 Name of the node in the consensus tree, with Node.3 nested within Node.2.

Node.4 Name of the node in the consensus tree, with Node.4 nested within Node.3.

References

The Angiosperm Phylogeny Group, M. W. Chase, M. J. M. Christenhusz, M. F. Fay, J. W. Byng, W. S. Judd, D. E. Soltis, D. J. Mabberley, A. N. Sennikov, P. S. Soltis, P. F. Stevens, An update of the Angiosperm Phylogeny Group classification for the orders and families of flowering plants: APG IV, Botanical Journal of the Linnean Society 181: 1-20. doi: [10.1111/boj.12385](https://doi.org/10.1111/boj.12385)

Examples

```
data(vascular.families)
```

WFO.example

World Flora Online (WFO) taxonomic backbone example data set

Description

This data set is a subset of the World Flora Online taxonomic backbone that allows running the first set of examples. In practical applications, users should first download a static copy of the Taxonomic Backbone data from <http://www.worldfloraonline.org/downloadData>.

Usage

```
data(WFO.example)
```

Source

World Flora Online. An Online Flora of All Known Plants. <http://www.worldfloraonline.org>

Examples

```
data(WFO.example)
```

WFO.match

Standardize plant names according to World Flora Online taxonomic backbone

Description

This package checks a list of species against the World Flora Online (WFO) taxonomic backbone. The user needs to first download a static copy of the Taxonomic Backbone data from <http://www.worldfloraonline.org/downloadData>.

Usage

```

WFO.match(spec.data = NULL, WFO.file = NULL, WFO.data = NULL,
  no.dates = TRUE,
  spec.name = "spec.name", Genus = "Genus", Species = "Species",
  Infrspecific.rank = "Infrspecific.rank", Infrspecific = "Infrspecific",
  Authorship = "Authorship", First.dist = FALSE,
  acceptedNameUsageID.match = TRUE,
  Fuzzy = 0.1, Fuzzy.force = FALSE, Fuzzy.max = 250, Fuzzy.min = TRUE,
  Fuzzy.shortest = FALSE, Fuzzy.within = FALSE,
  Fuzzy.two = TRUE, Fuzzy.one = TRUE,
  squish = TRUE,
  spec.name.tolower = FALSE, spec.name.nonnumber = TRUE, spec.name.nobrackets = TRUE,
  exclude.infrspecific = FALSE,
  infrspecific.excluded = c("cultivar.", "f.", "sect.", "subf.", "subg.",
    "subsp.", "subvar.", "var", "var."),
  spec.name.sub = TRUE,
  sub.pattern=c(" sp[.] A", " sp[.] B", " sp[.] C", " sp[.]", " spp[.]", " pl[.]",
    " indet[.]", " ind[.]", " gen[.]", " g[.]", " fam[.]", " nov[.]", " prox[.]",
    " cf[.]", " aff[.]", " s[.]s[.]", " s[.]l[.]",
    " p[.]p[.]", " p[.] p[.]", "[?]", " inc[.]", " stet[.]", "Ca[.]",
    "nom[.] cons[.]", "nom[.] dub[.]", " nom[.] err[.]", " nom[.] illeg[.]",
    " nom[.] inval[.]", " nom[.] nov[.]", " nom[.] nud[.]", " nom[.] obl[.]",
    " nom[.] prot[.]", " nom[.] rej[.]", " nom[.] supp[.]", " sensu auct[.]"),
  verbose = TRUE, counter = 1000)

WFO.url(WFO.result = NULL, browse = FALSE, browse.rows = c(1:1), ...)

WFO.one(WFO.result = NULL, priority = "Accepted",
  spec.name = NULL, Auth.dist = NULL, First.dist = NULL,
  verbose = TRUE, counter = 1000)

WFO.browse(taxon, WFO.file = NULL, WFO.data = NULL,
  accepted.only = FALSE, acceptedNameUsageID.match = TRUE, ...)

WFO.synonyms(taxon, WFO.file = NULL, WFO.data = NULL, ...)

WFO.family(taxon, WFO.file = NULL, WFO.data = NULL, ...)

```

Arguments

spec.data	A data.frame containing variables with species names. In case that a character vector is provided, then this vector will be converted to a data.frame
WFO.file	File name of the static copy of the Taxonomic Backbone. If not NULL, then data will be reloaded from this file.
WFO.data	Data set with the static copy of the Taxonomic Backbone. Ignored if WFO.file is not NULL.
no.dates	Speeding up the loading of the WFO.data by not loading fields of 'created' and 'modified'.

<code>spec.name</code>	Name of the column with taxonomic names. In case that a <code>spec.name</code> is provided, then separate genus and species names will be ignored. For function <code>WFO.one</code> , giving the name for this columns results in copying a submitted but unmatched plant name into the <code>scientificName</code> of the results.
<code>Genus</code>	Name of the column with the genus names.
<code>Species</code>	Name of the column with the species names.
<code>Infraspecific.rank</code>	Name of the column with the infraspecific rank (such as "subsp.", "var." or "cultivar.").
<code>Infraspecific</code>	Name of the column with the infraspecific names.
<code>Authorship</code>	Name of the column with the naming authorities.
<code>First.dist</code>	If TRUE, then calculate the fuzzy distance between the first words of the submitted and matched names (these are typically the genus names) .
<code>acceptedNameUsageID.match</code>	If TRUE, obtain the accepted name and others details from the earlier <code>acceptedNameUsageID</code> .
<code>Fuzzy</code>	If larger than 0, then attempt fuzzy matching in case an identical taxonomic name is not found in the World Flora Online. This argument will be used as argument <code>max.distance</code> in the internally called <code>agrep</code> . Note that fuzzy matching is only possible for the <code>spec.name</code> .
<code>Fuzzy.force</code>	If TRUE, always use the fuzzy matching algorithm, even when the <code>spec.name</code> was matched exactly.
<code>Fuzzy.max</code>	Maximum number of fuzzy matches.
<code>Fuzzy.min</code>	If TRUE, limit the matching of names to those with the smallest Levenshtein distance, calculated via <code>adist</code> .
<code>Fuzzy.shortest</code>	If TRUE, limit the matching of names to those with the most similar length of characters (this feature is expected to eliminate matches at infraspecific levels, see examples).
<code>Fuzzy.within</code>	If TRUE, limit the matching of names to those that contain exactly the submitted plant name (this feature is expected to be useful when submitting plant names that only contain a subset of the first characters of the species name, in order to check for best matches manually afterwards).
<code>Fuzzy.two</code>	If TRUE, in case that there were no fuzzy matches, limit the terms to be matched to the first two (these are expected to be genus and species names).
<code>Fuzzy.one</code>	If TRUE, in case that there were no fuzzy matches, limit the terms to be matched to the first one (expected to be the genus name).
<code>squish</code>	If TRUE, remove repeated whitespace and white space from the start and end of the submitted full name via <code>str_squish</code> .
<code>spec.name.tolower</code>	If TRUE, then convert all characters of the <code>spec.name</code> to lower case via <code>tolower</code> .
<code>spec.name.nonumber</code>	If TRUE, then submitted <code>spec.name</code> that contain numbers will be interpreted as genera, only matching the first word.

<code>spec.name.nobrackets</code>	If TRUE, then submitted <code>spec.name</code> then sections of the submitted name after '(' will be removed. Note that this will also remove sections after ')', such as authorities for plant names that are in a separate column of WFO.
<code>exclude.infraspecific</code>	If TRUE, then exclude records that contain the infraspecific levels defined by <code>infraspecific.excluded</code> .
<code>infraspecific.excluded</code>	Infraspecific levels (available from column 'verbatimTaxonRank') excluded in the results. Note that levels are excluded both in direct matches and matches with the accepted name.
<code>spec.name.sub</code>	If TRUE, then delete sections of the <code>spec.name</code> that match the <code>sub.pattern</code> .
<code>sub.pattern</code>	Sections of the <code>spec.name</code> to be deleted
<code>verbose</code>	Give details on the fuzzy matching process.
<code>counter</code>	Progress on the matching process is reported by multiples of this counter.
<code>WFO.result</code>	Result obtained via WFO.match .
<code>browse</code>	If TRUE, then browse urls specified by <code>browse.rows</code> .
<code>browse.rows</code>	Indices of row with the urls to be browsed.
<code>priority</code>	Method of selecting the 1-to-1 matches. Option Accepted first limits candidates to accepted names, with a possible second step of eliminating accepted names that are synonyms. Option Synonym first limits candidates to those that are not synonyms, with a possible second step of eliminating names that are not accepted. When the number of matches is larger than one after these steps, a third algorithm picks the candidate with the smallest taxonID.
<code>Auth.dist</code>	In case that the name of the variable with the Levenshtein distance between the authorship names is provided, then the algorithm first prioritizes records with the best match between the submitted and matched author names.
<code>taxon</code>	Character string with the name of the taxon for which information will be given (for families, different genera; for genera, different species; for species, infraspecific levels).
<code>accepted.only</code>	If TRUE, then only provide taxa with accepted names.
<code>...</code>	Other arguments for browseURL (<code>WFO.url</code>) or WFO.match (<code>WFO.browse</code>).

Details

The principal function (`WFO.match`) matches plant names. Columns retrieved from the World Flora Online are added to the provided input `data.frame`. In case that there are multiple matches, then rows from the input `data.frame` are repeated.

Column 'Unique' shows whether there was a unique match (or not match) in the WFO.

Column 'Matched' shows whether there was a match in the WFO.

Column 'Fuzzy' shows whether matching was done by the fuzzy method.

Column 'Fuzzy.dist' gives the Levenshtein distance calculated between submitted and matched plant names [adist](#).

Column 'Auth.dist' gives the Levenshtein distance calculated between submitted and matched authorship names, if the former were provided [adist](#).

Column 'Subseq' gives different numbers for different matches for the same plant name.

Column 'Hybrid' shows whether there was a hybrid character in the scientificName.

Column 'New.accepted' shows whether the species details correspond to the current accepted name.

Column 'Old.status' gives the taxonomic status of the first match with the non-blank acceptedNameUsageID.

Column 'Old.ID' gives the ID of the first match with the non-blank acceptedNameUsageID.

Column 'Old.name' gives the name of the first match with the non-blank acceptedNameUsageID.

The function was inspired on the Taxonstand package that matches plant names against The Plant List. Note that The Plant List has been static since 2013, but was used as the starting point for the Taxonomic Backbone of the World Flora Online.

Function WFO.one finds one unique matching name for each submitted name. Via `priority = "Accepted"`, it first limits candidates to accepted names, with a possible second step of eliminating accepted names that are synonyms. Via `priority = "Synonym"`, it first limits candidates to those that are not synonyms, with a possible second step of eliminating names that are not accepted. When the number of matches is larger than one after these steps, a third algorithm picks the candidate with the smallest taxonID. When a `spec.name` is given to WFO.one, the original submitted name is inserted for the `codescientificName`.

When the user specifies the column with the `Auth.dist`, documenting the Levenshtein distance between the submitted and matched authorities, then WFO.one first prioritizes records with best match between Authorities.

Function WFO.browse lists all the genera for a family, all species for a genus or all infraspecific levels for a species.

Function WFO.synonyms gives all records with the `acceptedNameUsageID` equal to the matched accepted species shown in the first row.

Function WFO.family provides information on the order of vascular plants, based on information available from [vascular.families](#). Based on an internal list of bryophyte families, when the submitted plant name is a bryophyte, the function returns 'bryophyte' instead.

Value

The main function returns a `data.set` with the matched species details from the WFO.

Author(s)

Roeland Kindt (World Agroforestry)

References

- World Flora Online. An Online Flora of All Known Plants. <http://www.worldfloraonline.org>
- Sigovini M, Keppel E, Tagliapietra. 2016. Open Nomenclature in the biodiversity era. *Methods in Ecology and Evolution* 7: 1217-1225.
- Kindt, R. 2020. WorldFlora: An R package for exact and fuzzy matching of plant names against the World Flora Online taxonomic backbone data. *Applications in Plant Sciences* 8(9): e11388

Examples

```

data(WFO.example)

spec.test <- data.frame(spec.name=c("Faidherbia albida", "Acacia albida",
  "Omalanthus populneus", "Pygeum afric"))

WFO.match(spec.data=spec.test, WFO.data=WFO.example, counter=1, verbose=TRUE)

# Also calculate the Levenshtein distance for the genus
WFO.match(spec.data=spec.test, WFO.data=WFO.example, First.dist=TRUE,
  counter=1, verbose=TRUE)

# Show all the fuzzy matches, which included those at infraspecific level
e1 <- WFO.match(spec.data=spec.test, WFO.data=WFO.example, counter=1,
  Fuzzy.min=FALSE, Fuzzy.shortest=FALSE, verbose=TRUE)
e1

# Use function WFO.one for a 1-to-1 match between submitted and matched names
WFO.one(e1)

# Hybrid species
WFO.match("Arabis divaricarpa", WFO.data=WFO.example)
WFO.match("Arabis x divaricarpa", WFO.data=WFO.example)

# Convert capitals to lower case
WFO.match("FAIDHERBIA ALBIDA", WFO.data=WFO.example, spec.name.to.lower=TRUE)

# Remove sections of plant names that are equal to ' sp.' or ' indet. '
WFO.match("Prunus sp.", WFO.data=WFO.example, spec.name.sub=TRUE)

# Get urls, but do not open any
e2 <- WFO.match(spec.data=spec.test, WFO.data=WFO.example, counter=1, verbose=TRUE)
WFO.url(e2, browse=FALSE, browse.rows=c(1:nrow(e1)))

# Include input species names where now matches were found
# This happens when the name with original species names is provided to WFO.one
x1 <- WFO.match("World agroforestry", WFO.data=WFO.example)
WFO.one(x1, spec.name="spec.name")

## Not run:

# Cross-check with Taxonstand results
library(Taxonstand)
data(bryophytes)

# Give the file with the static copy of the Taxonomic Backbone data ('classification.txt')
# that was downloaded from \url{http://www.worldfloraonline.org/downloadData}.
# Possibly first use unzip(file.choose()) for the downloaded WFO_Backbone.zip
WFO.file.RK <- file.choose()

# check species name

```

```

w1 <- WFO.match(bryophytes[1:20], WFO.file=WFO.file.RK, spec.name="Full.name", counter=1)
w1

# check species name from list of names
w1 <- WFO.match(bryophytes$Full.name[1:20], WFO.file=WFO.file.RK, counter=1)

# re-check species names obtained via Taxonstand
# note that Taxonstand did not match some infraspecific names ('Higher.level')
r1 <- Taxonstand:TPL(bryophytes$Full.name[1:20], corr = TRUE)
w2 <- WFO.match(r1, WFO.file=WFO.file.RK, Genus="New.Genus", Species="New.Species",
  Infraspecific.rank="New.Infraspecific.rank", Infraspecific="New.Infraspecific", counter=1)
w2

# only check genus and species
# specify different names for infraspecific columns as default to Taxonstand
w3 <- WFO.match(r1, WFO.file=WFO.file.RK, Genus="New.Genus", Species="New.Species",
  Infraspecific.rank="none", Infraspecific="none", counter=1)

# note that the method above also retrieved infraspecific levels
# to only retrieve at the species level, match infraspecific levels with an empty column
r1$empty <- rep("", nrow(r1))
w4 <- WFO.match(r1, WFO.file=WFO.file.RK, Genus="New.Genus", Species="New.Species",
  Infraspecific.rank="empty", Infraspecific="empty", counter=1)

# as an alternative to the method above, exclude all documented infraspecific levels
# from the results
w5 <- WFO.match(r1, WFO.file=WFO.file.RK, Genus="New.Genus", Species="New.Species",
  exclude.infraspecific=TRUE, counter=1)

# save results to file
# utils::write.table(w4, quote=F, sep="\t", row.names=F, append=FALSE)

# limit the fuzzy matches to those that contain a shortened version of a species name
w6 <- WFO.match("Acacia caes", WFO.file=WFO.file.RK, Fuzzy=0.01, Fuzzy.within=TRUE, verbose=TRUE)

# show all the matches for a genus
spec.test1 <- data.frame(Genus=c("Casimiroa"))
w8 <- WFO.match(spec.test1, WFO.file=WFO.file.RK, exclude.infraspecific=TRUE, verbose=TRUE)

# show all listings at a next hierarchical level
WFO.data1 <- data.table::fread(WFO.file.RK, encoding="UTF-8")

WFO.browse("Pinaceae", WFO.data=WFO.data1)
WFO.browse("Pinaceae", WFO.data=WFO.data1, accepted.only=T)

WFO.browse("Tsuga", WFO.data=WFO.data1)
WFO.browse("Tsuga", WFO.data=WFO.data1, accepted.only=T)

WFO.browse("Olea europaea", WFO.data=WFO.data1)
WFO.browse("Olea europaea", WFO.data=WFO.data1, accepted.only=T)

# browsing only works at family, genus and species levels

```

```
# for orders, however, information is given from vascular.families
WFO.browse("Polypodiales", WFO.data=WFO.data1)

# submitting no name results in a list of all families
WFO.browse(, WFO.data=WFO.data1)

# give synonyms
WFO.synonyms("Olea europaea", WFO.data=WFO.data1)

# give order and other higher levels from family
WFO.family("Olea europaea", WFO.data=WFO.data1)

## End(Not run)
```

WFO.prepare

Prepare a data set for analysis with WFO.match

Description

The function attempts to split a list of species names with naming authorities in different fields of botanical names and authorities.

Usage

```
WFO.prepare(spec.data = NULL, spec.full="spec.full",
squish = TRUE, spec.name.nonnumber = TRUE,
spec.name.sub = TRUE,
sub.pattern = c(" sp[.] A", " sp[.] B", " sp[.] C", " sp[.]", " spp[.]", " pl[.]",
" indet[.]", " ind[.]", " gen[.]", " g[.]", " fam[.]", " nov[.]", " prox[.]",
" cf[.]", " aff[.]", " s[.]s[.]", " s[.]l[.]",
" p[.]p[.]", " p[.] p[.]", "[?]", " inc[.]", " stet[.]", "Ca[.]",
"nom[.] cons[.]", "nom[.] dub[.]", " nom[.] err[.]", " nom[.] illeg[.]",
" nom[.] inval[.]", " nom[.] nov[.]", " nom[.] nud[.]", " nom[.] obl[.]",
" nom[.] prot[.]", " nom[.] rej[.]", " nom[.] supp[.]", " sensu auct[.]"),
genus.2.flag = TRUE, species.2.flag = TRUE,
punctuation.flag = TRUE, pointless.flag = TRUE,
trinomial = c("cultivar.", "f.", "sect.", "subf.", "subg.",
"subsp.", "subvar.", "var.",
"CULTIVAR.", "SECT.", "SUBF.", "SUBG.", "SUBSP.", "SUBVAR.", "VAR."),
verbose = TRUE, counter = 1000)
```

Arguments

spec.data	A data.frame containing variables with species names. In case that a character vector is provided, then this vector will be converted to a data.frame
spec.full	Name of the column with full taxonomic names.
squish	If TRUE, remove repeated whitespace and white space from the start and end of the submitted full name via str_squish .

spec.name.nonumber	If TRUE, then submitted spec.full that contain numbers will be interpreted as genera, only matching the first word.
spec.name.sub	If TRUE, then delete sections of the spec.full that match the sub.pattern.
sub.pattern	Sections of the spec.full to be deleted
genus.2.flag	Flag first part of the names with only 2 characters.
species.2.flag	Flag second part of the names with only 2 characters.
punctuation.flag	Flag if the retained plant name has punctuation characters.
pointless.flag	Flag if the retained plant name has sub.pattern without the point.
trinomial	Descriptors for trinomial names. In case a trinomial name is expected, the species name will be obtained from the first two words and the two words starting with the trinomial descriptor.
verbose	Give details on the process.
counter	Progress on the process is reported by multiples of this counter.

Details

The function splits submitted names into the botanical name ('spec.name') and the naming authority ('Authorship'). When the submitted name contains section between brackets that are not at the beginning of the naming authority, these sections will be removed.

Value

The function splits names in the botanical name and the naming authority.

Author(s)

Roeland Kindt (World Agroforestry)

Examples

```
WFO.prepare("Terminalia superba Engl. & Diels (**) (In review)")
WFO.prepare("Sorbus aucuparia subsp. praemorsa (Guss.) Nyman")
WFO.prepare("Ormosia aff. coarctata Jackson")
WFO.prepare("Ormosia aff coarctata Jackson")
WFO.prepare("Ormosia /coarctata Jackson")
WFO.prepare("Qualea TMG 148 Aubl.")
# Note that the sub.pattern is ' cf.'
WFO.prepare("cf Myrcia M1")
```

WFO.remember

Remember the location of the Taxonomic Backbone data set

Description

The function remembers where the Taxonomic Backbone data was downloaded to. In case that no arguments are specified, then data.frame WFO.data will contain the previously specified Taxonomic Backbone data.

Usage

```
WFO.download(WFO.url =
  "http://104.198.143.165/files/WFO_Backbone/_WFOCompleteBackbone/WFO_Backbone.zip",
  save.dir = getwd(), WFO.remember = TRUE, ...)

WFO.remember(WFO.file = NULL, WFO.data = "WFO.data", WFO.pos = 1)
```

Arguments

WFO.url	Hyperlink to the download from the World Flora Online.
save.dir	Directory where the file will be downloaded and unzipped.
WFO.remember	Remember the location of the file for WFO.remember.
...	Other arguments for download.file .
WFO.file	File path to the Taxonomic Backbone data ('classification.txt').
WFO.data	Name of data set to be used by other WorldFlora functions.
WFO.pos	Argument pos as in assign .

Details

These functions avoid that a user needs to reload and re-specify the location of the Taxonomic Backbone data that was previously downloaded from the World Flora Online website. The location is saved in a text file in the 'etc' directory of the WorldFlora directory.

Value

The function remembers the local location of the Taxonomic Backbone data.

Author(s)

Roeland Kindt (World Agroforestry)

Examples

```
## Not run:  
  
# change the working directory  
setwd(choose.dir())  
  
# download the Taxonomic Backbone data  
WFO.download()  
  
# remember the previous download and avail the data as 'WFO.data'  
WFO.remember()  
  
# check  
WFO.match("Faidherbia albida", WFO.data=WFO.data)  
  
## End(Not run)
```

Index

* datasets

- vascular.families, 4
- WFO.example, 5

adist, 7–9

agrep, 7

assign, 14

browseURL, 8

download.file, 14

new.backbone, 2

str_squish, 7, 12

tolower, 7

vascular.families, 4, 9

WFO.browse (WFO.match), 5

WFO.download (WFO.remember), 14

WFO.example, 5

WFO.family (WFO.match), 5

WFO.match, 3, 5, 8

WFO.one, 3

WFO.one (WFO.match), 5

WFO.prepare, 12

WFO.remember, 14

WFO.synonyms (WFO.match), 5

WFO.url (WFO.match), 5