

Package ‘nonmemica’

October 13, 2022

Type Package

Title Create and Evaluate NONMEM Models in a Project Context

Version 0.9.9

Author Tim Bergsma

Maintainer Tim Bergsma <bergsmat@gmail.com>

Description Systematically creates and modifies NONMEM(R) control streams. Harvests NONMEM output, builds run logs, creates derivative data, generates diagnostics. NONMEM (ICON Development Solutions <<https://www.iconplc.com/>>) is software for nonlinear mixed effects modeling. See 'package?nonmemica'.

License GPL-3

LazyData TRUE

Imports dplyr (>= 0.7.1), tidyr, xml2, encode, csv, spec, lazyeval, metaplot (>= 0.1.4), magrittr, rlang

Suggests pander, knitr, wrangle, rmarkdown

RoxygenNote 7.2.1

VignetteBuilder knitr

Encoding UTF-8

NeedsCompilation no

Repository CRAN

Date/Publication 2022-10-01 07:00:02 UTC

R topics documented:

| | |
|---------------------------------|---|
| absolute | 3 |
| as.halfmatrix.default | 3 |
| as.matrix.halfmatrix | 4 |
| as.xml_document | 4 |
| contains | 5 |
| datafile.character | 6 |
| definitions | 7 |
| depends.default | 8 |

| | |
|-----------------------------------|----|
| errors.character | 9 |
| estimates.character | 10 |
| fixed.model | 11 |
| generalize | 11 |
| initial.model | 12 |
| initial<-.model | 12 |
| likebut | 13 |
| lower.model | 14 |
| lower<-.model | 15 |
| meta.character | 15 |
| metaplot.character | 16 |
| metaplot_character | 17 |
| metasuperset | 18 |
| modeldir | 19 |
| modelfile | 19 |
| modelpath | 20 |
| modelpath.character | 21 |
| ninput | 22 |
| ninput.character | 22 |
| ninput.numeric | 23 |
| nms_canonical.character | 23 |
| nms_canonical.model | 24 |
| nms_nonmem.character | 25 |
| nms_nonmem.model | 25 |
| nms_psn.character | 26 |
| nms_psn.model | 26 |
| nonmemica | 27 |
| offdiag.halfmatrix | 30 |
| parameters.character | 31 |
| partab | 31 |
| partab.character | 32 |
| problem.character | 34 |
| psn_nested | 35 |
| psn_options | 35 |
| relativizePath | 36 |
| resolve | 37 |
| runlog.character | 37 |
| safe_join | 38 |
| safe_join.data.frame | 39 |
| shuffle | 39 |
| specfile.character | 40 |
| superset.character | 41 |
| superspec | 43 |
| superspec.character | 44 |
| superspec.numeric | 45 |
| tad | 45 |
| tad1 | 46 |
| tod | 47 |

| | |
|-----------------------------|----|
| <i>absolute</i> | 3 |
| tweak.default | 48 |
| tweak.model | 49 |
| updated.character | 50 |
| upper.model | 50 |
| upper<-.model | 51 |
| xpath | 51 |

Index **53**

absolute *Check if File Path is Absolute*

Description

Checks if file path is absolute.

Usage

```
absolute(x)
```

Arguments

x character (a file path)

Value

logical; TRUE if x starts with / or .: (e.g. C:)

as.halfmatrix.default *Coerce to Half Matrix by Default*

Description

Coerces to half matrix. Treats x as halfmatrix, coerces to matrix and takes half.

Usage

```
## Default S3 method:
as.halfmatrix(x, ...)
```

Arguments

x object
 ... passed arguments

See Also

Other halfmatrix: [as.data.frame.halfmatrix\(\)](#), [as.halfmatrix.halfmatrix\(\)](#), [as.halfmatrix\(\)](#), [as.matrix.halfmatrix\(\)](#), [half.matrix\(\)](#), [half\(\)](#), [is.square.matrix\(\)](#), [is.square\(\)](#), [offdiag.halfmatrix\(\)](#), [offdiag\(\)](#), [ord.halfmatrix\(\)](#), [ord.matrix\(\)](#), [ord\(\)](#), [print.halfmatrix\(\)](#)

as.matrix.halfmatrix *Coerce Half Matrix to Matrix*

Description

Coerces half matrix to matrix.

Usage

```
## S3 method for class 'halfmatrix'
as.matrix(x, ...)
```

Arguments

| | |
|-----|------------------|
| x | object |
| ... | passed arguments |

See Also

Other halfmatrix: [as.data.frame.halfmatrix\(\)](#), [as.halfmatrix.default\(\)](#), [as.halfmatrix.halfmatrix\(\)](#), [as.halfmatrix\(\)](#), [half.matrix\(\)](#), [half\(\)](#), [is.square.matrix\(\)](#), [is.square\(\)](#), [offdiag.halfmatrix\(\)](#), [offdiag\(\)](#), [ord.halfmatrix\(\)](#), [ord.matrix\(\)](#), [ord\(\)](#), [print.halfmatrix\(\)](#)

as.xml_document *Create an xml_document in a Project Context*

Description

Creates an xml_document in a project context.
 Coerces xml_document to xml_document
 Creates an xml_document from character (modelname or filepath).

Usage

```
as.xml_document(x, ...)

## S3 method for class 'xml_document'
as.xml_document(x, ...)

## S3 method for class 'character'
as.xml_document(x, strip.namespace = TRUE, ...)
```

Arguments

| | |
|-----------------|---------------------------------------------|
| x | object of dispatch |
| ... | arguments to methods |
| strip.namespace | whether to strip e.g. nm: from xml elements |

Value

xml_document
xml_document
xml_document

Methods (by class)

- `as.xml_document(xml_document)`: xml_document method
- `as.xml_document(character)`: filepath method

See Also

[xpath](#)

Other xpath: [as.xml_document.numeric\(\)](#), [xpath\(\)](#)

Other xpath: [as.xml_document.numeric\(\)](#), [xpath\(\)](#)

Other xpath: [as.xml_document.numeric\(\)](#), [xpath\(\)](#)

Examples

```
library(magrittr)
options(project = system.file('project/model', package='nonmemica'))
1001 %>% as.xml_document
```

contains

Check Whether Text Contains Pattern

Description

Checks whether text contains pattern.

Usage

```
contains(pattern, text, ...)
```

Arguments

| | |
|---------|---------------------------|
| pattern | regular expression |
| text | character vector to check |
| ... | arguments to methods |

Value

logical

See Also

[%contains%](#)

datafile.character *Identify the Datafile for a Model*

Description

Identifies the datafile used by a model. Expresses it relative to current working directory.

Usage

```
## S3 method for class 'character'
datafile(x, ...)
```

Arguments

x the model name or path to a control stream
 ... ext can be passed to modelfile, etc.

Value

character

See Also

Other path: [datafile.numeric\(\)](#), [datafile\(\)](#), [modeldir\(\)](#), [modelfile\(\)](#), [modelpath.character\(\)](#), [modelpath.numeric\(\)](#), [modelpath\(\)](#), [psn_options\(\)](#), [specfile.character\(\)](#), [specfile.numeric\(\)](#), [specfile\(\)](#)

Examples

```
library(spec)
source <- system.file(package = 'nonmemica', 'project')
target <- tempdir()
target <- gsub '\\\\', '/', target) # for windows
file.copy(source, target, recursive = TRUE)
project <- file.path(target, 'project', 'model')
options(project = project)
library(magrittr)
1001 %>% datafile
datafile(1001) %matches% specfile(1001)
1001 %>% specfile
1001 %>% specfile %>% read.spec
```

Description

Harvests model item definitions.
 Creates a model item definitions from a definitions object.
 Create Item Definitions from Model Name

Usage

```
definitions(x, ...)

## S3 method for class 'definitions'
definitions(x, ...)

## S3 method for class 'character'
definitions(
  x,
  verbose = FALSE,
  ctlfile = modelfile(x, ...),
  metafile = modelpath(x, "def", ...),
  fields = getOption("fields", default = c("symbol", "label", "unit")),
  read = length(metafile) == 1,
  write = FALSE,
  ...
)
```

Arguments

| | |
|----------|----------------------------------------------------------------|
| x | object of dispatch |
| ... | arguments to methods |
| verbose | set FALSE to suppress messages |
| ctlfile | path to control stream (pass length-zero argument to ignore) |
| metafile | path to definitions file (pass length-zero argument to ignore) |
| fields | metadata fields to read from control stream if no metafile |
| read | whether to read the definitions file |
| write | whether to write the definitions file |

Details

x can be numeric or character model name, assuming project is identified by argument or option.

Just returns the object unmodified.

Creates item definitions from a model name. Scavenges definitions optionally from the control stream and optionally from the definitions file. Optionally writes the result to the definitions file. Always returns a data.frame with at least the column 'item' but possibly no rows.

Value

object of class definitions, or path to metafile if write = TRUE.

Methods (by class)

- definitions(definitions): definitions method
- definitions(character): character method

See Also

[definitions.character](#)

[as.xml_document.character](#)

[as.bootstrap.character](#)

[as.model.character](#)

Other definitions: [definitions.numeric\(\)](#)

Other definitions: [definitions.numeric\(\)](#)

Other definitions: [definitions.numeric\(\)](#)

Examples

```
library(magrittr)
options(project = system.file('project/model',package='nonmemica'))
1001 %>% definitions
```

depends.default

Identify Model Dependencies

Description

Identify those models in the lineage of models in x.

Usage

```
## Default S3 method:
depends(x, ...)
```

Arguments

| | |
|-----|------------------|
| x | object |
| ... | passed arguments |

Value

character

See Also

Other depends: [depends\(\)](#)

errors.character *Get Errors for Character*

Description

Gets model asymptotic standard errors in canonical order, treating character as model names. See [parameters](#) for a less formal interface.

Usage

```
## S3 method for class 'character'
errors(
  x,
  xmlfile = modelpath(x, ext = "xml", ...),
  strip.namespace = TRUE,
  digits = 3,
  ...
)
```

Arguments

| | |
|-----------------|---------------------------------------------------------------------|
| x | character (modelname) |
| xmlfile | path to xml file |
| strip.namespace | whether to strip e.g. nm: from xml elements for easier xpath syntax |
| digits | passed to signif |
| ... | dots |

Value

numeric

See Also

nms_canonical errors
Other errors: [errors.numeric\(\)](#), [errors\(\)](#)

Examples

```
library(magrittr)
options(project = system.file('project/model', package='nonmemica'))
1001 %>% errors
```

estimates.character *Get Estimates for Character*

Description

Gets model parameter estimates in canonical order, treating character as model names. See [parameters](#) for a less formal interface.

Usage

```
## S3 method for class 'character'
estimates(
  x,
  xmlfile = modelpath(x, ext = "xml", ...),
  strip.namespace = TRUE,
  digits = 3,
  ...
)
```

Arguments

| | |
|-----------------|---------------------------------------------------------------------|
| x | character (modelname) |
| xmlfile | path to xml file |
| strip.namespace | whether to strip e.g. nm: from xml elements for easier xpath syntax |
| digits | passed to signif |
| ... | dots |

Value

numeric

See Also

nms_canonical errors
Other estimates: [estimates.numeric\(\)](#), [estimates\(\)](#)

Examples

```
library(magrittr)
options(project = system.file('project/model', package='nonmemica'))
1001 %>% estimates
```

| | |
|-------------|--------------------------------|
| fixed.model | <i>Check If Model is Fixed</i> |
|-------------|--------------------------------|

Description

Checks if model is fixed. Returns a logical vector with element for each init, in canonical order.

Usage

```
## S3 method for class 'model'
fixed(x, ...)
```

Arguments

| | |
|-----|--------|
| x | object |
| ... | dots |

Value

logical

See Also

Other fixed: [fixed<-.inits\(\)](#), [fixed<-.init\(\)](#), [fixed<-.model\(\)](#), [fixed<-\(\)](#), [fixed\(\)](#)

Examples

```
library(magrittr)
options(project = system.file('project/model', package='nonmemica'))
1001 %>% as.model %>% fixed
```

| | |
|------------|--------------------------------------|
| generalize | <i>Generalize a Nonmissing Value</i> |
|------------|--------------------------------------|

Description

#Generalize a nonmissing value. If there is only one such among zero or more NA, impute that value for all NA.

Usage

```
generalize(x, ...)
```

Arguments

| | |
|-----|---------|
| x | vector |
| ... | ignored |

See Also

Other superset: [meta.character\(\)](#), [meta.numeric\(\)](#), [metaplot.character\(\)](#), [metaplot.numeric\(\)](#), [metaplot_character\(\)](#), [metasuperset\(\)](#), [meta\(\)](#), [ninput.character\(\)](#), [ninput.numeric\(\)](#), [ninput\(\)](#), [shuffle\(\)](#), [superset.character\(\)](#), [superset.numeric\(\)](#), [superset\(\)](#), [superspec.character\(\)](#), [superspec.numeric\(\)](#), [superspec\(\)](#)

| | |
|---------------|------------------------------------|
| initial.model | <i>Get Model Initial Estimates</i> |
|---------------|------------------------------------|

Description

Gets model initial estimates.

Usage

```
## S3 method for class 'model'
initial(x, ...)
```

Arguments

| | |
|-----|-------|
| x | model |
| ... | dots |

See Also

Other initial: [initial<-.model\(\)](#), [initial<-\(\)](#), [initial\(\)](#)

Examples

```
library(magrittr)
options(project = system.file('project/model', package='nonmemica'))
1001 %>% as.model %>% initial
```

| | |
|-----------------|-----------------------------------------------------|
| initial<-.model | <i>Set Upper Bounds for Model Initial Estimates</i> |
|-----------------|-----------------------------------------------------|

Description

Sets upper bounds for model initial estimates.

Usage

```
## S3 replacement method for class 'model'
initial(x) <- value
```

Arguments

| | |
|-------|---------|
| x | model |
| value | numeric |

See Also

Other initial: `initial.model()`, `initial<-()`, `initial()`

| | |
|---------|-----------------------|
| likebut | <i>Modify a Model</i> |
|---------|-----------------------|

Description

Makes a copy of a model in a corresponding directory. Problem statement is updated to reflect that the model is LIKE the reference model BUT different in some fundamental way.

Usage

```
likebut(
  x,
  but = "better",
  y = NULL,
  project = getOption("project", getwd()),
  nested = getOption("nested", TRUE),
  overwrite = FALSE,
  ext = getOption("modex", "ctl"),
  include = "\\\\.def$",
  update = FALSE,
  ...
)
```

Arguments

| | |
|-----------|--------------------------------------------------------------------|
| x | a model name, presumably interpretable as numeric |
| but | a short description of the characteristic difference from x |
| y | optional name for model to be created, auto-incremented by default |
| project | project directory |
| nested | model files nested in run-specific directories |
| overwrite | whether to overwrite y if it exists |
| ext | extension for the model file |
| include | regular expressions for files to copy to new directory |
| update | use final estimates of x as initial estimates of y |
| ... | passed arguments, including PsN runrecord elements (experimental) |

Value

the value of y

See Also

[runlog.character](#)

Examples

```
# Create a working project.
source <- system.file(package = 'nonmemica', 'project')
target <- tempdir()
target <- gsub('\\', '/', target) # for windows
source
target
file.copy(source, target, recursive = TRUE)
project <- file.path(target, 'project', 'model')

# Point project option at working project
options(project = project)
library(magrittr)

# Derive models.
1001 %>% likebut('revised', y = 1002, overwrite=TRUE )

# At this point, edit 1002.ct1 to match whatever 'revised' means.
# Then run it with NONMEM.
```

lower.model

Get Lower Bounds for Model Initial Estimates

Description

Gets lower bounds for model initial estimates.

Usage

```
## S3 method for class 'model'
lower(x, ...)
```

Arguments

| | |
|-----|-------|
| x | model |
| ... | dots |

See Also

Other lower: [lower<- .model\(\)](#), [lower<-\(\)](#), [lower\(\)](#)

Examples

```
library(magrittr)
options(project = system.file('project/model',package='nonmemica'))
1001 %>% as.model %>% lower
```

| | |
|---------------|-----------------------------------------------------|
| lower<-.model | <i>Set Lower Bounds for Model Initial Estimates</i> |
|---------------|-----------------------------------------------------|

Description

Sets lower bounds for model initial estimates.

Usage

```
## S3 replacement method for class 'model'
lower(x) <- value
```

Arguments

| | |
|-------|---------|
| x | model |
| value | numeric |

See Also

Other lower: [lower.model\(\)](#), [lower<-\(\)](#), [lower\(\)](#)

| | |
|----------------|-----------------------------------|
| meta.character | <i>Get Metadata for Character</i> |
|----------------|-----------------------------------|

Description

Gets metadata for character, treating it as a model name. Blends metadata from specfile with metadata from control stream, removing both exact duplicates as well as redefined values (with warning).

Usage

```
## S3 method for class 'character'
meta(x, simplify = TRUE, ...)
```

Arguments

| | |
|----------|---------------------------------------------------|
| x | object |
| simplify | logical: remove range information from guide text |
| ... | passed arguments |

Value

data.frame

See Also

Other superset: [generalize\(\)](#), [meta.numeric\(\)](#), [metaplot.character\(\)](#), [metaplot.numeric\(\)](#), [metaplot_character\(\)](#), [metasuperset\(\)](#), [meta\(\)](#), [ninput.character\(\)](#), [ninput.numeric\(\)](#), [ninput\(\)](#), [shuffle\(\)](#), [superset.character\(\)](#), [superset.numeric\(\)](#), [superset\(\)](#), [superspec.character\(\)](#), [superspec.numeric\(\)](#), [superspec\(\)](#)

Examples

```
library(magrittr)
options(project = system.file('project/model', package='nonmemica'))
1001 %>% meta
```

| | |
|--------------------|---------------------------|
| metaplot.character | <i>Metaplot Character</i> |
|--------------------|---------------------------|

Description

Plots character by treating as model name. A dataset is constructed by combining the meta version of the model input with a meta version of the model output and calling metaplot with the result.

Usage

```
## S3 method for class 'character'
metaplot(x, ..., groups, meta = match.fun("meta")(x), subset)
```

Arguments

| | |
|--------|------------------------------------------------------------------------|
| x | object |
| ... | unquoted names of variables to plot, or other named arguments (passed) |
| groups | columns by which to group the dataset |
| meta | metadata; meta(x) by default |
| subset | a condition for filtering data |

See Also

Other superset: [generalize\(\)](#), [meta.character\(\)](#), [meta.numeric\(\)](#), [metaplot.numeric\(\)](#), [metaplot_character\(\)](#), [metasuperset\(\)](#), [meta\(\)](#), [ninput.character\(\)](#), [ninput.numeric\(\)](#), [ninput\(\)](#), [shuffle\(\)](#), [superset.character\(\)](#), [superset.numeric\(\)](#), [superset\(\)](#), [superspec.character\(\)](#), [superspec.numeric\(\)](#), [superspec\(\)](#)

Examples

```

library(magrittr)
library(metaplot)
options(project = system.file('project/model',package='nonmemica'))
## Not run:
1001 %>% metaplot(
  CWRESI, TAD, SEX,
  groups = c('ID', 'TIME'),
  subset = 'MDV == 0',
  yref = 0,
  ysmooth = TRUE
)

## End(Not run)

```

metaplot_character *Metaplot Character, Standard Evaluation*

Description

Plots character by treating as model name. A dataset is constructed by combining the model input with a the model output and calling metaplot with the result.

Usage

```
metaplot_character(x, groups, meta = NULL, subset, var, ...)
```

Arguments

| | |
|--------|---------------------------------------|
| x | object |
| groups | columns by which to group the dataset |
| meta | metadata; meta(x) by default |
| subset | a condition for filtering data |
| var | variables to plot |
| ... | passed arguments |

See Also

Other superset: [generalize\(\)](#), [meta.character\(\)](#), [meta.numeric\(\)](#), [metaplot.character\(\)](#), [metaplot.numeric\(\)](#), [metasuperset\(\)](#), [meta\(\)](#), [ninput.character\(\)](#), [ninput.numeric\(\)](#), [ninput\(\)](#), [shuffle\(\)](#), [superset.character\(\)](#), [superset.numeric\(\)](#), [superset\(\)](#), [superspec.character\(\)](#), [superspec.numeric\(\)](#), [superspec\(\)](#)

metasuperset

*Retrieve Model Outputs with Metadata***Description**

Retrieves model outputs with metadata.

Usage

```
metasuperset(
  x,
  groups,
  meta = match.fun("meta")(x, ...),
  subset = getOption("metasuperset_subset", NULL),
  ...
)
```

Arguments

| | |
|--------|---------------------------------------------------------------------------------|
| x | model name |
| groups | vector of key column names in superset, e.g. USUBJID, TIME |
| meta | metadata with column 'item' and possibly attributes such as 'label' and 'guide' |
| subset | length-one character: a condition for filtering results, e.g. 'EVID == 0' |
| ... | passed arguments |

Value

data.frame

See Also

Other superset: [generalize\(\)](#), [meta.character\(\)](#), [meta.numeric\(\)](#), [metaplot.character\(\)](#), [metaplot.numeric\(\)](#), [metaplot.character\(\)](#), [meta\(\)](#), [ninput.character\(\)](#), [ninput.numeric\(\)](#), [ninput\(\)](#), [shuffle\(\)](#), [superset.character\(\)](#), [superset.numeric\(\)](#), [superset\(\)](#), [superspec.character\(\)](#), [superspec.numeric\(\)](#), [superspec\(\)](#)

Examples

```
library(magrittr)
options(project = system.file('project/model', package='nonmemica'))
1001 %>% metasuperset(c('ID', 'TIME')) %>% head
```

| | |
|----------|-------------------------------------------|
| modeldir | <i>Identify the Directory for a Model</i> |
|----------|-------------------------------------------|

Description

Identifies the directory used by a model.

Usage

```
modeldir(x, ext, ...)
```

Arguments

| | |
|-----|----------------------|
| x | the model name |
| ext | model file extension |
| ... | passed arguments |

Value

character

See Also

Other path: [datafile.character\(\)](#), [datafile.numeric\(\)](#), [datafile\(\)](#), [modelfile\(\)](#), [modelpath.character\(\)](#), [modelpath.numeric\(\)](#), [modelpath\(\)](#), [psn_options\(\)](#), [specfile.character\(\)](#), [specfile.numeric\(\)](#), [specfile\(\)](#)

Examples

```
library(magrittr)
options(project = system.file('project/model', package='nonmemica'))
1001 %>% modeldir
```

| | |
|-----------|-------------------------------------------|
| modelfile | <i>Identify the Modelfile for a Model</i> |
|-----------|-------------------------------------------|

Description

Identifies the modelfile used by a model.

Usage

```
modelfile(x, ext = getOption("modex", "ctl"), ...)
```

Arguments

| | |
|-----|----------------------|
| x | the model name |
| ext | model file extension |
| ... | passed arguments |

Value

character

See Also

Other path: [datafile.character\(\)](#), [datafile.numeric\(\)](#), [datafile\(\)](#), [modeldir\(\)](#), [modelpath.character\(\)](#), [modelpath.numeric\(\)](#), [modelpath\(\)](#), [psn_options\(\)](#), [specfile.character\(\)](#), [specfile.numeric\(\)](#), [specfile\(\)](#)

Examples

```
library(magrittr)
options(project = system.file('project/model', package='nonmemica'))
1001 %>% modelfile('xml')
```

modelpath

Resolve A Path to a Model-related File

Description

Resolves a path to a model-related file.

Usage

```
modelpath(x, ...)
```

Arguments

| | |
|-----|------------------|
| x | object |
| ... | passed arguments |

Value

character

See Also

Other path: [datafile.character\(\)](#), [datafile.numeric\(\)](#), [datafile\(\)](#), [modeldir\(\)](#), [modelfile\(\)](#), [modelpath.character\(\)](#), [modelpath.numeric\(\)](#), [psn_options\(\)](#), [specfile.character\(\)](#), [specfile.numeric\(\)](#), [specfile\(\)](#)

Examples

```
library(magrittr)
options(project = system.file('project/model', package='nonmemica'))
1001 %>% modelpath
```

modelpath.character *Resolve A Path to a Model-related File for Character*

Description

Resolves a path to a model-related file, treating `x` as a model name. By default (`ext` is `NULL`) the run directory is returned. As of version 0.9.2, `nested` can be a function of `ext` and `...` That returns logical.

Usage

```
## S3 method for class 'character'
modelpath(
  x,
  ext = NULL,
  project = getOption("project", getwd()),
  nested = getOption("nested", TRUE),
  ...
)
```

Arguments

| | |
|----------------------|---------------------------------------------------------|
| <code>x</code> | object |
| <code>ext</code> | file extension, no leading dot |
| <code>project</code> | project directory |
| <code>nested</code> | whether model files are nested in eponymous directories |
| <code>...</code> | passed arguments |

Value

character

See Also

Other path: [datafile.character\(\)](#), [datafile.numeric\(\)](#), [datafile\(\)](#), [modeldir\(\)](#), [modelfile\(\)](#), [modelpath.numeric\(\)](#), [modelpath\(\)](#), [psn_options\(\)](#), [specfile.character\(\)](#), [specfile.numeric\(\)](#), [specfile\(\)](#)

| | |
|--------|-----------------------------------|
| ninput | <i>Calculate Number of Inputs</i> |
|--------|-----------------------------------|

Description

Calculates number of inputs.

Usage

```
ninput(x, ...)
```

Arguments

| | |
|-----|------------------|
| x | object |
| ... | passed arguments |

See Also

Other superset: [generalize\(\)](#), [meta.character\(\)](#), [meta.numeric\(\)](#), [metaplot.character\(\)](#), [metaplot.numeric\(\)](#), [metaplot_character\(\)](#), [metasuperset\(\)](#), [meta\(\)](#), [ninput.character\(\)](#), [ninput.numeric\(\)](#), [shuffle\(\)](#), [superset.character\(\)](#), [superset.numeric\(\)](#), [superset\(\)](#), [superspec.character\(\)](#), [superspec.numeric\(\)](#), [superspec\(\)](#)

| | |
|------------------|-------------------------------------------------|
| ninput.character | <i>Calculate Number of Inputs for Character</i> |
|------------------|-------------------------------------------------|

Description

Calculates number of inputs for character by treating as a model name.

Usage

```
## S3 method for class 'character'
ninput(x, ...)
```

Arguments

| | |
|-----|------------------|
| x | character |
| ... | passed arguments |

Value

integer

See Also

Other superset: [generalize\(\)](#), [meta.character\(\)](#), [meta.numeric\(\)](#), [metaplot.character\(\)](#), [metaplot.numeric\(\)](#), [metaplot_character\(\)](#), [metasuperset\(\)](#), [meta\(\)](#), [ninput.numeric\(\)](#), [ninput\(\)](#), [shuffle\(\)](#), [superset.character\(\)](#), [superset.numeric\(\)](#), [superset\(\)](#), [superspec.character\(\)](#), [superspec.numeric\(\)](#), [superspec\(\)](#)

| | |
|----------------|-----------------------------------------------|
| ninput.numeric | <i>Calculate Number of Inputs for Numeric</i> |
|----------------|-----------------------------------------------|

Description

Calculates number of inputs for numeric by coercing to character.

Usage

```
## S3 method for class 'numeric'
ninput(x, ...)
```

Arguments

| | |
|-----|------------------|
| x | numeric |
| ... | passed arguments |

See Also

Other superset: [generalize\(\)](#), [meta.character\(\)](#), [meta.numeric\(\)](#), [metaplot.character\(\)](#), [metaplot.numeric\(\)](#), [metaplot_character\(\)](#), [metasuperset\(\)](#), [meta\(\)](#), [ninput.character\(\)](#), [ninput\(\)](#), [shuffle\(\)](#), [superset.character\(\)](#), [superset.numeric\(\)](#), [superset\(\)](#), [superspec.character\(\)](#), [superspec.numeric\(\)](#), [superspec\(\)](#)

| | |
|-------------------------|-----------------------------------------------|
| nms_canonical.character | <i>Generate Canonical Names for Character</i> |
|-------------------------|-----------------------------------------------|

Description

Generates canonical names for character by converting to parsed model.

Usage

```
## S3 method for class 'character'
nms_canonical(x, ...)
```

Arguments

x object of dispatch
... passed arguments

Examples

```
library(magrittr)
options(project = system.file('project/model', package='nonmemica'))
1001 %>% nms_canonical
```

nms_canonical.model *Generate Canonical Names for Model*

Description

Generates canonical names for a NONMEM control stream object. Canonical names indicate all and only the declared model parameters in lower-case conventional order (theta, omega row-major, sigma) with underscores and two-digit (or more) indices. E.g. theta_01, theta_02, omega_01_01, omega_02_01, omega_02_02, omega_01_01.

Usage

```
## S3 method for class 'model'
nms_canonical(x, ...)
```

Arguments

x a model designator
... passed arguments

Value

canonical (character)

See Also

as.model

nms_nonmem.character *Generate NONMEM-style Names for Character*

Description

Generates NONMEM-style names for numeric by converting to parsed model.

Usage

```
## S3 method for class 'character'
nms_nonmem(x, ...)
```

Arguments

| | |
|-----|--------------------|
| x | object of dispatch |
| ... | passed arguments |

See Also

Other nms_nonmem: [nms_nonmem.model\(\)](#), [nms_nonmem.numeric\(\)](#), [nms_nonmem\(\)](#)

Examples

```
library(magrittr)
options(project = system.file('project/model', package='nonmemica'))
1001 %>% nms_nonmem
```

nms_nonmem.model *Generate NONMEM-style Names for Model*

Description

Generates NONMEM-style names for parameters declared in a NONMEM control stream object. PsN uses NONMEM-style names, substituting a comment, if any: everything after the first semicolon, up to the second semicolon if present, without leading/trailing spaces/tabs.

Usage

```
## S3 method for class 'model'
nms_nonmem(x, ...)
```

Arguments

| | |
|-----|--------------------|
| x | a model designator |
| ... | passed arguments |

Value

nonmem (character)

See Also

as.model

Other nms_nonmem: [nms_nonmem.character\(\)](#), [nms_nonmem.numeric\(\)](#), [nms_nonmem\(\)](#)

nms_psn.character *Generate PsN-style Names for Character*

Description

Generates PsN-style names for numeric by converting to parsed model.

Usage

```
## S3 method for class 'character'
nms_psn(x, ...)
```

Arguments

x object of dispatch
... passed arguments

Examples

```
library(magrittr)
options(project = system.file('project/model', package='nonmemica'))
1001 %>% nms_psn
```

nms_psn.model *Generate PsN-style Names for Model*

Description

Generates PsN-style names for parameters declared in a NONMEM control stream object. PsN uses NONMEM-style names, substituting a comment, if any: everything after the first semicolon, up to the second semicolon if present, without leading/trailing spaces/tabs.

Usage

```
## S3 method for class 'model'
nms_psn(x, ...)
```

Arguments

x a model designator
 . . . passed arguments

Value

psn (character)

See Also

as.model

nonmemica

Create and Evaluate NONMEM Models in a Project Context

Description

Nonmemica (emphasis like 'America') creates and evaluates NONMEM models in a project context.

Details

NONMEM (ICON Development Solutions) is software for nonlinear mixed effects modeling. The fundamental interface is a text file (control stream, typ. *.mod or *.ctl) that specifies model input, structure, and output. There are many add-on interfaces for NONMEM (see references for a few examples). However, much day-to-day modeling, even for R users, involves substantial manual interventions.

Nonmemica streamlines interactions with NONMEM. It adopts some established conventions and techniques (e.g. from PsN and metrumrg), but introduces others that may be useful. Principally, it parses existing control streams for systematic analysis and alteration. Relatively simple, single-problem control streams are supported; see the example.

Of course, NONMEM itself is licensed software that must be installed independently. Nonmemica is largely indifferent to how NONMEM is installed or invoked. However, several features depend on the *.xml output that NONMEM creates; make sure it is available. Also, the best-supported directory structure is that which has numbers for model names, with all model-specific files in eponymous subdirectories of a "project" directory. An example is given below.

Nonmemica adopts three control stream encoding conventions that merit special mention. First, the problem statement is encoded in the form //like/x//but/y// where x is a reference model name and y is a feature difference from the reference model (see likebut()). This allows any given model to be described by chaining together its legacy of features (use runlog(depenencies = TRUE, ...)), which generally works better than trying to describe it exhaustively in the model name. As of version 0.9.2, experimental support is available for natural-language problem statements of the form "like run1001 but fixed additive error".

Second, Nonmemica only needs a single output table (\$TABLE record). Be sure to use ONE-HEADER but avoid FIRSONLY. Nonmemica will integrate model inputs and outputs, regardless of table counts, into one data.frame (see superset()).

Third, Nonmemica supports integrated metadata. With respect to model inputs, use package spec to store column metadata in a companion file (a data specification, e.g. *.spec). Keep the data file and data specification in a central location, not copied to the model directory. For model outputs (tabled items) supply column metadata directly in the control stream (or a *.def file; see example and help).

Nonmemica supports three global options: 'project' (default getwd()) is the parent directory of model-specific files or directories; 'nested' (default TRUE) tells whether model-specific files are nested within eponymous directories; 'modex' (default 'ctl') gives the file extension for control streams. In many cases you can pass these options to the relevant functions; but since they likely won't change for the scope of a given project, it saves effort to set them as global options (if they differ from the defaults) using e.g. options(project=).

Numbers make good names for models because it is never hard for you or the software to think of a new one. That said, model names are typically processed as character in Nonmemica. There are many generic functions with both numeric and character methods that simply assume the (length-one) argument you supply is a model name.

References

[NONMEM](#)

[Icon](#)

[PsN](#)

[Xpose](#)

[Wings for NONMEM](#)

[R speaks NONMEM](#)

[metrumrg](#)

Examples

```
# Create a working project.
source <- system.file(package = 'nonmemica', 'project')
target <- tempdir()
target <- gsub('\\\\', '/', target) # for windows
source
target
file.copy(source, target, recursive = TRUE)
project <- file.path(target, 'project', 'model')

# Point project option at working project
options(project = project)

# Load some packages
library(magrittr)
library(metaplot)
library(wrangle)
library(spec)
library(dplyr, warn.conflicts = FALSE)
```

```
# Identify features of a model.
1001 %>% modelpath
1001 %>% modeldir
1001 %>% modelfile
1001 %>% modelpath('xml')
1001 %>% datafile
datafile(1001) %matches% specfile(1001)
1001 %>% specfile
1001 %>% specfile %>% read.spec
1001 %>% as.model
1001 %>% as.model %>% comments
1001 %>% definitions
1001 %>% runlog(TRUE)
1001 %>% runlog
1001 %>% partab
1001 %>% num_parameters
1001 %>% nms_canonical
1001 %>% nms_psn
1001 %>% nms_nonmem
1001 %>% parameters
1001 %>% errors
1001 %>% as.model %>% initial
1001 %>% as.model %>% lower
1001 %>% as.model %>% upper
1001 %>% as.model %>% fixed
1001 %>% meta %>% class
1001 %>% meta

# Derive datasets.
1001 %>% superset %>% head
1001 %>% superset %>% filter(VISIBLE == 1) %>% group_by(ID,TIME) %>% status
1001 %>% metasuperset(c('ID','TIME')) %>% head
1001 %>% metasuperset(c('ID','TIME')) %>% sapply(attr,'label')

# Make diagnostic plots.
1001 %>% metaplot(
  CWRESI, TAD, SEX,
  groups = c('ID','TIME'),
  subset = 'MDV == 0',
  yref=0,
  ysmooth = TRUE
)
1001 %>% metaplot(
  ETA1, SEX,
  ref = 0,
  groups = c('ID','TIME'),
  subset = 'MDV == 0'
)
1001 %>% metaplot(
  SEX, ETA1,
  ref = 0,
  groups = c('ID','TIME'),
  subset = 'MDV == 0'
```

```
)
1001 %>% metaplot(
  ETA1, ETA2, ETA3,
  groups = c('ID', 'TIME'),
  subset = 'MDV == 0'
)

# Derive models.
1001 %>% likebut('revised', y = 1002, overwrite=TRUE )
# At this point, edit 1002.ct1 to match whatever 'revised' means.
# Then run it with NONMEM and post-process results as above.

# Make ten new models with slightly different initial estimates.
1001 %>% tweak
```

offdiag.halfmatrix *Isolate Off-diagonal of Half Matrix*

Description

Isolates off-diagonal of halfmatrix.

Usage

```
## S3 method for class 'halfmatrix'
offdiag(x, ...)
```

Arguments

| | |
|-----|------------------|
| x | object |
| ... | passed arguments |

See Also

Other halfmatrix: [as.data.frame.halfmatrix\(\)](#), [as.halfmatrix.default\(\)](#), [as.halfmatrix.halfmatrix\(\)](#), [as.halfmatrix\(\)](#), [as.matrix.halfmatrix\(\)](#), [half.matrix\(\)](#), [half\(\)](#), [is.square.matrix\(\)](#), [is.square\(\)](#), [offdiag\(\)](#), [ord.halfmatrix\(\)](#), [ord.matrix\(\)](#), [ord\(\)](#), [print.halfmatrix\(\)](#)

parameters.character *Get Parameters for Character*

Description

Gets parameters, treating character as model names. If `x` is length one, slightly more details are returned such as datafile, reference model, and feature. Otherwise results are bound together, one model per column. See [estimates](#) and [errors](#) for a more formal interface to model estimates and asymptotic standard errors.

Usage

```
## S3 method for class 'character'
parameters(x, simplify = FALSE, ...)
```

Arguments

| | |
|-----------------------|------------------------------------------------------------------------------------------|
| <code>x</code> | object |
| <code>simplify</code> | if <code>x</code> is length one and <code>simplify</code> is TRUE, return a named vector |
| <code>...</code> | passed arguments |

Value

data.frame

See Also

Other parameters: [parameters.numeric\(\)](#), [parameters\(\)](#)

Examples

```
library(magrittr)
options(project = system.file('project/model', package='nonmemica'))
1001 %>% parameters
```

partab *Create Parameter Table*

Description

Creates a parameter table.

Creates a model parameter table from a partab object.

Usage

```
partab(x, ...)

## S3 method for class 'partab'
partab(x, ...)
```

Arguments

x object of dispatch
 ... arguments to methods

Details

x can be numeric or character model name, assuming project is identified by argument or option.
 Just returns the object unmodified.

Methods (by class)

- partab(partab): partab method

See Also

[partab.character](#)
 Other partab: [partab.character\(\)](#), [partab.numeric\(\)](#)
 Other partab: [partab.character\(\)](#), [partab.numeric\(\)](#)

| | |
|------------------|-------------------------------------------------|
| partab.character | <i>Create a Parameter Table from Model Name</i> |
|------------------|-------------------------------------------------|

Description

Creates a parameter table from a model name. Pass the project argument or set the project option.

Usage

```
## S3 method for class 'character'
partab(
  x,
  verbose = FALSE,
  lo = "5",
  hi = "95",
  metafile = modelpath(x, "def", ...),
  xmlfile = modelpath(x, "xml", ...),
  ctlfile = modelfile(x, ...),
  bootcsv,
  strip.namespace = TRUE,
```



```

    skip = 28,
    check.names = FALSE,
    digits = 3,
    ci = TRUE,
    open = "(",
    close = ")",
    sep = ", ",
    format = TRUE,
    fields = getOption("fields", default = c("symbol", "label", "unit")),
    relative = TRUE,
    percent = relative,
    nonzero = TRUE,
    shrinkage = FALSE,
    correlation = FALSE,
    ...
)

```

Arguments

| | |
|-----------------|----------------------------------------------------------------------------------|
| x | a model name (numeric or character) |
| verbose | set FALSE to suppress messages |
| lo | the PsN bootstrap lower confidence limit (%) |
| hi | the PsN bootstrap upper confidence limit (%) |
| metafile | optional metadata for parameter table (see also: fields) |
| xmlfile | path to xml file |
| ctlfile | path to control stream |
| bootcsv | path to PsN bootstrap_results.csv |
| strip.namespace | whether to strip e.g. nm: from xml elements for easier xpath syntax |
| skip | number of lines to skip in bootstrap_results.csv |
| check.names | passed to bootstrap reader |
| digits | limits numerics to significant digits (use NULL to suppress) |
| ci | combine bootstrap lo and hi into an enclosed interval |
| open | first character for bootstrap interval |
| close | last character for bootstrap interval |
| sep | separator for bootstrap interval |
| format | format numerics as character |
| fields | metadata fields to read from control stream. See details. |
| relative | transform standard errors to relative standard errors: rse replaces se |
| percent | if relative is true, express as percent (else ignore): prse replaces se |
| nonzero | limit random effects to those with nonzero estimates |
| shrinkage | whether to include percent shrinkage on random effects |
| correlation | whether to include correlation of random effects (as percent if percent is true) |
| ... | passed to other functions |

Details

Normally you can just call the generic. Suitable defaults are supplied, but much customization is supported by means of arguments documented here and in called functions.

Metadata can be added to the parameter table two ways: as markup in the control stream, and as a *.def file in the model directory. See vignette('parameter-table') for details.

Value

object of class partab, data.frame

See Also

[as.xml_document.character](#)

[as.bootstrap.character](#)

[as.model.character](#)

[as.csv](#)

Other partab: [partab.numeric\(\)](#), [partab\(\)](#)

Examples

```
library(magrittr)
options(project = system.file('project/model', package='nonmemica'))
1001 %>% partab
1001 %>% partab(shrinkage = TRUE, correlation = TRUE)
```

problem.character

Identify the Model Problem Statement for Character

Description

Identifies the model problem statement for character (model name).

Usage

```
## S3 method for class 'character'
problem(x, ...)
```

Arguments

| | |
|-----|------------------|
| x | object |
| ... | passed arguments |

Value

character

See Also

Other problem: [as.problem\(\)](#), [problem.numeric\(\)](#), [problem_\(\)](#), [problem\(\)](#)

| | |
|------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| psn_nested | <i>PsN Model File is Nested Check whether a particular file extension corresponds to a file that is nested within a subdirectory using default PsN conventions.</i> |
|------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|

Description

PsN Model File is Nested Check whether a particular file extension corresponds to a file that is nested within a subdirectory using default PsN conventions.

Usage

```
psn_nested(x, ...)
```

Arguments

| | |
|-----|-------------------------------------------|
| x | character, a file extension, without dot. |
| ... | ignored |

Value

logical

Examples

```
psn_nested('mod')
```

| | |
|-------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| psn_options | <i>Set PsN Options Sets PsN-style directory and control stream options. Supports control streams with semicolon-delimited metadata including symbol, unit, transform, and label. Expects model files to be found in nested directory, except for *.mod and *.lst.</i> |
|-------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

Description

Set PsN Options Sets PsN-style directory and control stream options. Supports control streams with semicolon-delimited metadata including symbol, unit, transform, and label. Expects model files to be found in nested directory, except for *.mod and *.lst.

Usage

```
psn_options(
  project = "NONMEM",
  modex = "mod",
  fields = c("symbol", "unit", "transform", "label"),
  nested = psn_nested,
  ...
)
```

Arguments

| | |
|---------|----------------------------------------------------------|
| project | character, path to project directory |
| modex | character, extension for model control stream (no dot) |
| fields | character |
| nested | logical, or function of file extension returning logical |
| ... | ignored |

Value

used for side-effects (sets options 'fields' and 'nested')

See Also

Other path: [datafile.character\(\)](#), [datafile.numeric\(\)](#), [datafile\(\)](#), [modeldir\(\)](#), [modelfile\(\)](#), [modelpath.character\(\)](#), [modelpath.numeric\(\)](#), [modelpath\(\)](#), [specfile.character\(\)](#), [specfile.numeric\(\)](#), [specfile\(\)](#)

Examples

```
## Not run:
psn_options()

## End(Not run)
```

relativizePath

Relativize a Path

Description

Relativizes a path.

Usage

```
relativizePath(x, dir = getwd(), sep = "/", ...)
```

Arguments

| | |
|-----|-----------------------|
| x | a file path |
| dir | a reference directory |
| sep | path separator |
| ... | ignored arguments |

Details

x and dir are first normalized, then x is expressed relative to dir. If x and dir are on different drives (i.e. C:/ D:/) x is returned as an absolute path.

| | |
|---------|--------------------------|
| resolve | <i>Resolve File Path</i> |
|---------|--------------------------|

Description

Resolves a file path. Returns the path if absolute. If relative, concatenates the directory and file.

Usage

```
resolve(file, dir)
```

Arguments

| | |
|------|----------------------------------------------|
| file | path to a file |
| dir | reference directory for a relative file path |

Value

character

| | |
|------------------|--------------------------------------|
| runlog.character | <i>Create a Runlog for Character</i> |
|------------------|--------------------------------------|

Description

Creates a Runlog for character by treating x as modelname(s).

Usage

```
## S3 method for class 'character'
runlog(x, dependencies = FALSE, digits = 3, places = 0, ...)
```

Arguments

| | |
|--------------|-------------------------------------------|
| x | object |
| dependencies | whether to log runs in lineage(s) as well |
| digits | significance for parameters |
| places | rounding for objective function |
| ... | passed arguments |

Value

data.frame

See Also

[likebut](#)

Other runlog: [runlog.numeric\(\)](#), [runlog\(\)](#)

Examples

```
library(magrittr)
options(project = system.file('project/model',package='nonmemica'))
# likebut(2001,'2 cmt', 2002)           # edit manually, then ...
# likebut(2002,'add. err.', 2003)      # edit manually, then ...
# likebut(2003,'allo. WT on CL',2004)  # edit manually, then ...
# likebut(2004,'estimate allometry', 2005) # edit manually, then ...
# likebut(2005,'SEX on CL', 2006)      # edit manually, then ...
# likebut(2006,'full block omega', 2007) # edit manually, then run all
2007 %>% runlog(dependencies = TRUE)
```

safe_join

Join Data Safely

Description

Joins data safely. Generic, with method for data.frame.

Usage

```
safe_join(x, ...)
```

Arguments

| | |
|-----|----------------------|
| x | object of dispatch |
| ... | arguments to methods |

See Also

[safe_join.data.frame](#)

Other safe_join: [safe_join.data.frame\(\)](#)

safe_join.data.frame *Join Data Frames Safely*

Description

Joins data frames safely. I.e., a left join that cannot alter row order or number. Supports the case where you only intend to augment existing rows with additional columns and are expecting singular matches. Gives an error if row order or number would have been altered by a left join.

Usage

```
## S3 method for class 'data.frame'
safe_join(x, y, ...)
```

Arguments

| | |
|-----|----------------------------|
| x | data.frame |
| y | data.frame |
| ... | passed to dplyr::left_join |

See Also

Other safe_join: [safe_join\(\)](#)

Examples

```
library(magrittr)
x <- data.frame(code = c('a','b','c'), value = c(1:3))
y <- data.frame(code = c('a','b','c'), roman = c('I','II','III'))
x %>% safe_join(y)
try(
  x %>% safe_join(rbind(y,y))
)
```

shuffle *Move the Columns of a Data Frame Relative to Each Other*

Description

Move the columns of a data.frame relative to each other.

Usage

```
shuffle(x, who, after = NA, ...)
```

Arguments

| | |
|-------|------------------------------------------------------------------------------------------------------------|
| x | data.frame |
| who | a character vector of column names to move, or a logical vector of length names(x), or a vector of indices |
| after | column after which to put who: may be character, integer, NA, or NULL |
| ... | ignored |

Value

data.frame

See Also

Other superset: [generalize\(\)](#), [meta.character\(\)](#), [meta.numeric\(\)](#), [metaplot.character\(\)](#), [metaplot.numeric\(\)](#), [metaplot_character\(\)](#), [metasuperset\(\)](#), [meta\(\)](#), [ninput.character\(\)](#), [ninput.numeric\(\)](#), [ninput\(\)](#), [superset.character\(\)](#), [superset.numeric\(\)](#), [superset\(\)](#), [superspec.character\(\)](#), [superspec.numeric\(\)](#), [superspec\(\)](#)

specfile.character *Identify the Data Specification File for a Model*

Description

Identifies the data specification file associated with the datafile used by a model. Locates the datafile specified in the control stream, and substitutes a different extension.

Usage

```
## S3 method for class 'character'
specfile(x, find = "\\*.csv$", use = ".spec", ...)
```

Arguments

| | |
|------|---------------------------------------------------------|
| x | the model name |
| find | file extension to replace |
| use | file extension to use |
| ... | pass ext over-ride default file extension in datafile() |

Value

character

See Also

datafile

Other path: [datafile.character\(\)](#), [datafile.numeric\(\)](#), [datafile\(\)](#), [modeldir\(\)](#), [modelfile\(\)](#), [modelpath.character\(\)](#), [modelpath.numeric\(\)](#), [modelpath\(\)](#), [psn_options\(\)](#), [specfile.numeric\(\)](#), [specfile\(\)](#)

Examples

```
library(spec)
source <- system.file(package = 'nonmemica', 'project')
target <- tempdir()
target <- gsub('\\\\', '/', target) # for windows
file.copy(source, target, recursive = TRUE)
project <- file.path(target, 'project', 'model')
options(project = project)
library(magrittr)
1001 %>% datafile
datafile(1001) %matches% specfile(1001)
1001 %>% specfile
1001 %>% specfile %>% read.spec
```

superset.character *Coerce to Superset from Character*

Description

Coerces to superset from character, treating x as a model name.

Usage

```
## S3 method for class 'character'
superset(
  x,
  read.input = list(read.csv, header = TRUE, as.is = TRUE),
  read.output = list(read.table, header = TRUE, as.is = TRUE, skip = 1, comment.char =
    "", check.names = FALSE, na.strings = c("", "\\s", ".", "NA")),
  include = character(0),
  exclude = character(0),
  rename = NULL,
  digits = 5,
  visible = "VISIBLE",
  after = NULL,
  groups = character(0),
  imputation = generalize,
  ...
)
```

Arguments

| | |
|-------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x | object |
| read.input | a methodology for acquiring the input |
| read.output | a methodology for acquiring the output |
| include | column names in output to consider adding |
| exclude | column names in output to reject |
| rename | logical: whether to keep and rename columns with re-used names |
| digits | significant digits for assessing informativeness when exclusive=NULL |
| visible | a name for the flag column indicating visibility |
| after | place new columns after this column; at end by default (NULL); TRUE places them after last model-visible column (see input statement) |
| groups | character vector of groupings within which any imputations will be performed |
| imputation | a list of functions (or arguments to match.fun()) to perform imputations within cells defined by groups: e.g. generalize, forbak, etc (to be tried in succession for new columns only). |
| ... | passed arguments |

Details

Given a model name, (project passed or set as global option) `superset()` figures out the run directory and location of a NONMEM control stream. It reads the control stream to identify the run-time location of input and output files, as well as the "ignore" (and/or "accept") criteria that relate extent of input records to extent of output records. 'read.input' and 'read.output' are lists consisting of functions and arguments appropriate for reading input and output file formats, respectively. The ignore criteria will be reconstructed per row so that output can be mapped unambiguously to input. A column named `VISIBLE` is bound to the input data, showing 1 where a record was visible to NONMEM, and 0 otherwise. During integration, naming convention of the input is retained, and output column names are mapped by position, using the control stream input criteria. Output tables are restored to input dimensions using the "ignore" criteria, then checked for length: currently, `superset` ignores output tables having fewer rows than the input, as well as output tables whose row count is not a multiple of input row count. Output tables may contain versions of input columns. Disposition depends on the values of `include`, `exclude`, and `rename`. If `include` has length, other columns are excluded. Then, if `exclude` has length, these columns are excluded. Then, if `rename` is `FALSE` all remaining columns with re-used names will be dropped. If `TRUE`, such columns will be renamed (`*.n`, where `n` is table number). If `NULL`, only informative columns will be retained and renamed. A column is informative if any element is informative. An element is informative if it is newly generated (not NA and not zero, but original is NA) or if it is an alteration (non-NA, and different from non-NA original). If the column pair can be interpreted as numeric, "different" is determined using only the first `digits` digits. Only the first instance of any column among successive output tables is retained. In the control stream, avoid use of `FIRSTONLY`, as this alters the number of rows.

Value

`superset`: a data.frame where row count is a multiple of (typically equal to) input row count.

See Also

Other superset: [generalize\(\)](#), [meta.character\(\)](#), [meta.numeric\(\)](#), [metaplot.character\(\)](#), [metaplot.numeric\(\)](#), [metaplot_character\(\)](#), [metasuperset\(\)](#), [meta\(\)](#), [ninput.character\(\)](#), [ninput.numeric\(\)](#), [ninput\(\)](#), [shuffle\(\)](#), [superset.numeric\(\)](#), [superset\(\)](#), [superspec.character\(\)](#), [superspec.numeric\(\)](#), [superspec\(\)](#)

Examples

```
library(magrittr)
library(dplyr)
library(wrangle)
options(project = system.file('project/model', package='nonmemica'))
1001 %>% superset %>% head
1001 %>% superset %>% filter(VISIBLE == 1) %>% group_by(ID, TIME) %>% status
```

superspec

Create Specification for Model Inputs and Outputs

Description

Create a specification for the result of `superset()`.

Usage

```
superspec(x, ...)
```

Arguments

| | |
|-----|------------------|
| x | object |
| ... | passed arguments |

See Also

[superspec.character](#)

Other superset: [generalize\(\)](#), [meta.character\(\)](#), [meta.numeric\(\)](#), [metaplot.character\(\)](#), [metaplot.numeric\(\)](#), [metaplot_character\(\)](#), [metasuperset\(\)](#), [meta\(\)](#), [ninput.character\(\)](#), [ninput.numeric\(\)](#), [ninput\(\)](#), [shuffle\(\)](#), [superset.character\(\)](#), [superset.numeric\(\)](#), [superset\(\)](#), [superspec.character\(\)](#), [superspec.numeric\(\)](#)

superspec.character *Create Specification for Model Inputs and Outputs From Character*

Description

Create a specification for the result of `superset()` from `character` by treating as a model name. By default, gives a spec template for `superset(x)`. Tries to supplement with labels and units from parent specification, if it exists. Tries to supplement with any additional labels and units in `definitions(x)`. Defers to actual data if provided. Specify `exclusive`, `visible`, and `after` as for `superset`.

Usage

```
## S3 method for class 'character'
superspec(
  x,
  include = character(0),
  exclude = character(0),
  rename = NULL,
  visible = "VISIBLE",
  after = NULL,
  data = NULL,
  ...
)
```

Arguments

| | |
|----------------------|---------------------------------------------------------------------------------------|
| <code>x</code> | character |
| <code>include</code> | column names in output to consider adding |
| <code>exclude</code> | column names in output to reject |
| <code>rename</code> | logical: whether to keep and rename columns with re-used names |
| <code>visible</code> | a name for the flag column indicating visibility |
| <code>after</code> | place new columns after this column; at end by default (NULL); TRUE places them after |
| <code>data</code> | an alternative dataset on which to model the specification |
| <code>...</code> | passed arguments |

See Also

Other `superset`: [generalize\(\)](#), [meta.character\(\)](#), [meta.numeric\(\)](#), [metaplot.character\(\)](#), [metaplot.numeric\(\)](#), [metaplot_character\(\)](#), [metasuperset\(\)](#), [meta\(\)](#), [ninput.character\(\)](#), [ninput.numeric\(\)](#), [ninput\(\)](#), [shuffle\(\)](#), [superset.character\(\)](#), [superset.numeric\(\)](#), [superset\(\)](#), [superspec.numeric\(\)](#), [superspec\(\)](#)

| | |
|-------------------|-----------------------------------------------------------------------|
| superspec.numeric | <i>Create Specification for Model Inputs and Outputs From Numeric</i> |
|-------------------|-----------------------------------------------------------------------|

Description

Create a specification for the result of `superset()` from numeric by coercing to character.

Usage

```
## S3 method for class 'numeric'
superspec(x, ...)
```

Arguments

| | |
|-----|------------------|
| x | numeric |
| ... | passed arguments |

See Also

Other `superset`: [generalize\(\)](#), [meta.character\(\)](#), [meta.numeric\(\)](#), [metaplot.character\(\)](#), [metaplot.numeric\(\)](#), [metaplot.character\(\)](#), [metasuperset\(\)](#), [meta\(\)](#), [ninput.character\(\)](#), [ninput.numeric\(\)](#), [ninput\(\)](#), [shuffle\(\)](#), [superset.character\(\)](#), [superset.numeric\(\)](#), [superset\(\)](#), [superspec.character\(\)](#), [superspec\(\)](#)

| | |
|-----|----------------------------------------------|
| tad | <i>Calculate Time Since Most Recent Dose</i> |
|-----|----------------------------------------------|

Description

Calculate time since most recent dose. Considers ADDL, but may not work with simultaneous dose records.

Usage

```
tad(
  x,
  dose = rep(FALSE, length(x)),
  addl = rep(0, length(x)),
  ii = rep(0, length(x)),
  index = rep(1, length(x)),
  pre = TRUE,
  ...
)
```

Arguments

| | |
|-------|-------------------------------------------------------------|
| x | a numeric vector of event times |
| dose | length x logical indicating which of x are dose times |
| addl | length x integer: number of additional doses |
| ii | length x numeric: interdose interval for addl |
| index | length x factor (optional) indicating subgroups to evaluate |
| pre | assume that simultaneous sample precedes implied dose |
| ... | passed to tod() |

Value

numeric

See Also

[tod](#)

Other tad: [tod\(\)](#)

Examples

```
data(tad1)
x <- tad1
head(x)
x$tad <- tad(
  x = x$TIME,
  dose = x$EVID %in% c(1,4) & is.na(x$C),
  addl = x$ADDL,
  ii = x$II,
  index = x$ID
)
head(x)
```

tad1

A NONMEM-like Dataset

Description

A dataset showing dose and observation records for several subjects. Doses are duplicated across compartments 1 and 2 as for mixed absorption modeling.

Usage

```
data(tad1)
```

Details

- C. An exclusion flag, NA by default, or 'C'.
- ID. Integer subject identifier.
- TIME. Numeric event time (h).
- EVID. Event type identifier: observation (0) or dose (1).
- CMT. Event compartment: dose (1), central (2) or peripheral (4).
- AMT. Amount of dose (mg).
- RATE. NONMEM RATE item.
- ADDL. Number of additional doses, or NA for observations.
- II. Interdose interval for additional doses, or NA for observations.
- DV. Observation placeholder.

 tod

Calculate Time of Most Recent Dose

Description

Calculates time of most recent dose.

Usage

```
tod(x, ref, addl, ii, pre = T, ...)
```

Arguments

| | |
|------|-------------------------------------------------------|
| x | a numeric vector of event times |
| ref | length x vector of reference dose times |
| addl | length x integer: number of additional doses |
| ii | length x numeric: interdose interval for addl |
| pre | assume that simultaneous sample precedes implied dose |
| ... | ignored |

Value

numeric

See Also

[tad](#)

Other tad: [tad\(\)](#)

`tweak.default`*Tweak a Model by Default*

Description

Tweaks a model by jittering initial estimates. Creates a new model directory in project context and places the model there. Copies helper files as well. Expects that `x` is a number. Assumes nested directory structure (run-specific directories).

Usage

```
## Default S3 method:
tweak(
  x,
  project = getOption("project", getwd()),
  ext = getOption("modex", "ctl"),
  start = NULL,
  n = 10,
  include = ".def$",
  ...
)
```

Arguments

| | |
|----------------------|--------------------------------------------------------|
| <code>x</code> | object |
| <code>project</code> | project directory |
| <code>ext</code> | file extension for control streams |
| <code>start</code> | a number to use as the first modelname |
| <code>n</code> | the number of variants to generate (named start:n) |
| <code>include</code> | regular expressions for files to copy to new directory |
| <code>...</code> | pass ext to over-ride default model file extension |

Value

character: vector of names for models created

See Also

Other tweak: [tweak.inits\(\)](#), [tweak.init\(\)](#), [tweak.model\(\)](#), [tweak\(\)](#)

`tweak.model`*Tweak Model*

Description

Tweaks model.

Usage

```
## S3 method for class 'model'  
tweak(x, sd = 0.13, digits = 3, ...)
```

Arguments

| | |
|---------------------|---------|
| <code>x</code> | object |
| <code>sd</code> | numeric |
| <code>digits</code> | integer |
| <code>...</code> | dots |

Value

model

See Also

Other tweak: [tweak.default\(\)](#), [tweak.inits\(\)](#), [tweak.init\(\)](#), [tweak\(\)](#)

Examples

```
# Create a working project.  
source <- system.file(package = 'nonmemica', 'project')  
target <- tempdir()  
target <- gsub('\\\\\\\\', '/', target) # for windows  
source  
target  
file.copy(source, target, recursive = TRUE)  
project <- file.path(target, 'project', 'model')  
  
# Point project option at working project  
options(project = project)  
library(magrittr)  
  
# Make ten new models with slightly different initial estimates.  
1001 %>% tweak
```

updated.character *Create the Updated Version of Character*

Description

Creates the updated version of character by treating as a modelname. Parses the associated control stream and ammends the initial estimates to reflect model results (as per xml file).

Usage

```
## S3 method for class 'character'  
updated(x, initial = estimates(x, ...), parse = TRUE, verbose = FALSE, ...)
```

Arguments

| | |
|---------|-----------------------------------------------|
| x | character |
| initial | values to use for initial estimates (numeric) |
| parse | whether to parse the initial estimates, etc. |
| verbose | extended messaging |
| ... | dots |

Value

model

See Also

Other updated: [updated.numeric\(\)](#), [updated\(\)](#)

upper.model *Get Upper Bounds for Model Initial Estimates*

Description

Gets upper bounds for model initial estimates.

Usage

```
## S3 method for class 'model'  
upper(x, ...)
```

Arguments

| | |
|-----|-------|
| x | model |
| ... | dots |

See Also

Other upper: [upper<- .model\(\)](#), [upper<-\(\)](#), [upper\(\)](#)

Examples

```
library(magrittr)
options(project = system.file('project/model', package='nonmemica'))
1001 %>% as.model %>% upper
```

| | |
|----------------|-----------------------------------------------------|
| upper<- .model | <i>Set Upper Bounds for Model Initial Estimates</i> |
|----------------|-----------------------------------------------------|

Description

Sets upper bounds for model initial estimates.

Usage

```
## S3 replacement method for class 'model'
upper(x) <- value
```

Arguments

| | |
|-------|---------|
| x | model |
| value | numeric |

See Also

Other upper: [upper.model\(\)](#), [upper<-\(\)](#), [upper\(\)](#)

| | |
|-------|----------------------------------|
| xpath | <i>Evaluate Xpath Expression</i> |
|-------|----------------------------------|

Description

Evaluates an xpath expression.

Coerces x to xml_document and evaluates.

Evaluates an xpath expression for a given document.

Usage

```
xpath(x, ...)  
  
## Default S3 method:  
xpath(x, ...)  
  
## S3 method for class 'xml_document'  
xpath(x, xpath, ...)
```

Arguments

| | |
|-------|------------------------------|
| x | xml_document |
| ... | passed arguments |
| xpath | xpath expression to evaluate |

Details

The resulting nodeset is scavenged for text, and coerced to best of numeric or character.

The resulting nodeset is scavenged for text, and coerced to best of numeric or character.

Value

vector
vector

Methods (by class)

- `xpath(default)`: default method
- `xpath(xml_document)`: `xml_document` method

See Also

Other xpath: [as.xml_document.numeric\(\)](#), [as.xml_document\(\)](#)

Other xpath: [as.xml_document.numeric\(\)](#), [as.xml_document\(\)](#)

Other xpath: [as.xml_document.numeric\(\)](#), [as.xml_document\(\)](#)

Examples

```
library(magrittr)  
options(project = system.file('project/model', package='nonmemica'))  
1001 %>% xpath('//etashrink/row/col')
```

Index

- * **definitions**
 - definitions, 7
 - * **depends**
 - depends.default, 8
 - * **errors**
 - errors.character, 9
 - * **estimates**
 - estimates.character, 10
 - * **fixed**
 - fixed.model, 11
 - * **halfmatrix**
 - as.halfmatrix.default, 3
 - as.matrix.halfmatrix, 4
 - offdiag.halfmatrix, 30
 - * **initial**
 - initial.model, 12
 - initial<-.model, 12
 - * **likebut**
 - likebut, 13
 - * **lower**
 - lower.model, 14
 - lower<-.model, 15
 - * **nms_nonmem**
 - nms_nonmem.character, 25
 - nms_nonmem.model, 25
 - * **parameters**
 - parameters.character, 31
 - * **partab**
 - partab, 31
 - partab.character, 32
 - * **path**
 - datafile.character, 6
 - modeldir, 19
 - modelfile, 19
 - modelpath, 20
 - modelpath.character, 21
 - psn_options, 35
 - specfile.character, 40
 - * **problem**
 - problem.character, 34
 - * **runlog**
 - runlog.character, 37
 - * **safe_join**
 - safe_join, 38
 - safe_join.data.frame, 39
 - * **superset**
 - generalize, 11
 - meta.character, 15
 - metaplot.character, 16
 - metaplot_character, 17
 - metasuperset, 18
 - ninput, 22
 - ninput.character, 22
 - ninput.numeric, 23
 - shuffle, 39
 - superset.character, 41
 - superspec, 43
 - superspec.character, 44
 - superspec.numeric, 45
 - * **tad**
 - tad, 45
 - tod, 47
 - * **tweak**
 - tweak.default, 48
 - tweak.model, 49
 - * **updated**
 - updated.character, 50
 - * **upper**
 - upper.model, 50
 - upper<-.model, 51
 - * **xpath**
 - as.xml_document, 4
 - xpath, 51
 - %contains%, 6
- absolute, 3
as.bootstrap.character, 8, 34
as.csv, 34
as.data.frame.halfmatrix, 4, 30

- as.halfmatrix, [4, 30](#)
- as.halfmatrix.default, [3, 4, 30](#)
- as.halfmatrix.halfmatrix, [4, 30](#)
- as.matrix.halfmatrix, [4, 4, 30](#)
- as.model.character, [8, 34](#)
- as.problem, [35](#)
- as.xml_document, [4, 52](#)
- as.xml_document.character, [8, 34](#)
- as.xml_document.numeric, [5, 52](#)
- contains, [5](#)
- datafile, [6, 19–21, 36, 41](#)
- datafile.character, [6, 19–21, 36, 41](#)
- datafile.numeric, [6, 19–21, 36, 41](#)
- definitions, [7](#)
- definitions.character, [8](#)
- definitions.numeric, [8](#)
- depends, [9](#)
- depends.default, [8](#)
- errors, [9, 31](#)
- errors.character, [9](#)
- errors.numeric, [9](#)
- estimates, [10, 31](#)
- estimates.character, [10](#)
- estimates.numeric, [10](#)
- fixed, [11](#)
- fixed.model, [11](#)
- generalize, [11, 16–18, 22, 23, 40, 43–45](#)
- half, [4, 30](#)
- half.matrix, [4, 30](#)
- initial, [12, 13](#)
- initial.model, [12, 13](#)
- initial<- .model, [12](#)
- is.square, [4, 30](#)
- is.square.matrix, [4, 30](#)
- likebut, [13, 38](#)
- lower, [14, 15](#)
- lower.model, [14, 15](#)
- lower<- .model, [15](#)
- meta, [12, 16–18, 22, 23, 40, 43–45](#)
- meta.character, [12, 15, 16–18, 22, 23, 40, 43–45](#)
- meta.numeric, [12, 16–18, 22, 23, 40, 43–45](#)
- metaplot.character, [12, 16, 16, 17, 18, 22, 23, 40, 43–45](#)
- metaplot.numeric, [12, 16–18, 22, 23, 40, 43–45](#)
- metaplot_character, [12, 16, 17, 18, 22, 23, 40, 43–45](#)
- metasuperset, [12, 16, 17, 18, 22, 23, 40, 43–45](#)
- modeldir, [6, 19, 20, 21, 36, 41](#)
- modelfile, [6, 19, 19, 20, 21, 36, 41](#)
- modelpath, [6, 19, 20, 20, 21, 36, 41](#)
- modelpath.character, [6, 19, 20, 21, 36, 41](#)
- modelpath.numeric, [6, 19–21, 36, 41](#)
- ninput, [12, 16–18, 22, 23, 40, 43–45](#)
- ninput.character, [12, 16–18, 22, 22, 23, 40, 43–45](#)
- ninput.numeric, [12, 16–18, 22, 23, 23, 40, 43–45](#)
- nms_canonical.character, [23](#)
- nms_canonical.model, [24](#)
- nms_nonmem, [25, 26](#)
- nms_nonmem.character, [25, 26](#)
- nms_nonmem.model, [25, 25](#)
- nms_nonmem.numeric, [25, 26](#)
- nms_psn.character, [26](#)
- nms_psn.model, [26](#)
- nonmemica, [27](#)
- offdiag, [4, 30](#)
- offdiag.halfmatrix, [4, 30](#)
- ord, [4, 30](#)
- ord.halfmatrix, [4, 30](#)
- ord.matrix, [4, 30](#)
- parameters, [9, 10, 31](#)
- parameters.character, [31](#)
- parameters.numeric, [31](#)
- partab, [31, 34](#)
- partab.character, [32, 32](#)
- partab.numeric, [32, 34](#)
- print.halfmatrix, [4, 30](#)
- problem, [35](#)
- problem.character, [34](#)
- problem.numeric, [35](#)
- problem_, [35](#)
- psn_nested, [35](#)
- psn_options, [6, 19–21, 35, 41](#)

relativizePath, 36
resolve, 37
runlog, 38
runlog.character, 14, 37
runlog.numeric, 38

safe_join, 38, 39
safe_join.data.frame, 38, 39
shuffle, 12, 16–18, 22, 23, 39, 43–45
specfile, 6, 19–21, 36, 41
specfile.character, 6, 19–21, 36, 40
specfile.numeric, 6, 19–21, 36, 41
superset, 12, 16–18, 22, 23, 40, 43–45
superset.character, 12, 16–18, 22, 23, 40,
41, 43–45
superset.numeric, 12, 16–18, 22, 23, 40,
43–45
superspec, 12, 16–18, 22, 23, 40, 43, 43, 44,
45
superspec.character, 12, 16–18, 22, 23, 40,
43, 44, 45
superspec.numeric, 12, 16–18, 22, 23, 40,
43, 44, 45

tad, 45, 47
tad1, 46
tod, 46, 47
tweak, 48, 49
tweak.default, 48, 49
tweak.init, 48, 49
tweak.inits, 48, 49
tweak.model, 48, 49

updated, 50
updated.character, 50
updated.numeric, 50
upper, 51
upper.model, 50, 51
upper<- .model, 51

xpath, 5, 51