

Package ‘posterior’

September 9, 2021

Title Tools for Working with Posterior Distributions

Version 1.1.0

Date 2021-09-09

Description Provides useful tools for both users and developers of packages for fitting Bayesian models or working with output from Bayesian models.

The primary goals of the package are to:

- (a) Efficiently convert between many different useful formats of draws (samples) from posterior or prior distributions.
- (b) Provide consistent methods for operations commonly performed on draws, for example, subsetting, binding, or mutating draws.
- (c) Provide various summaries of draws in convenient formats.
- (d) Provide lightweight implementations of state of the art posterior inference diagnostics. References: Vehtari et al. (2021) [doi:10.1214/20-BA1221](https://doi.org/10.1214/20-BA1221).

Depends R (>= 3.2.0)

Imports abind, checkmate, rlang (>= 0.4.7), stats, tibble (>= 3.0.0), vctrs, tensorA, pillar, distributional, parallel, matrixStats

Suggests testthat (>= 2.1.0), caret (>= 6.0.84), gbm (>= 2.1.8), randomForest (>= 4.6.14), e1071 (>= 1.7.3), dplyr, tidyr, knitr, rmarkdown

License BSD_3_clause + file LICENSE

Encoding UTF-8

LazyData false

URL <https://mc-stan.org/posterior/>, <https://discourse.mc-stan.org/>

BugReports <https://github.com/stan-dev/posterior/issues>

RoxygenNote 7.1.1

VignetteBuilder knitr

NeedsCompilation no

Author Paul-Christian Bürkner [aut, cre],
Jonah Gabry [aut],
Matthew Kay [aut],

Aki Vehtari [aut],
 Måns Magnusson [ctb],
 Rok Češnovar [ctb],
 Ben Lambert [ctb],
 Ozan Adıgüzel [ctb],
 Jacob Socolar [ctb]

Maintainer Paul-Christian Bürkner <paul.buerkner@gmail.com>

Repository CRAN

Date/Publication 2021-09-09 11:30:02 UTC

R topics documented:

posterior-package	3
as_rvar	4
bind_draws	5
chol.rvar	6
diagnostics	7
draws	7
draws-index	8
draws_array	10
draws_df	11
draws_list	13
draws_matrix	15
draws_of	16
draws_rvars	18
draws_summary	19
ess_basic	22
ess_bulk	23
ess_mean	24
ess_quantile	25
ess_sd	27
ess_tail	28
example_draws	29
extract_variable	31
extract_variable_matrix	31
is_rvar	32
mcse_mean	33
mcse_quantile	34
mcse_sd	35
merge_chains	37
mutate_variables	38
order_draws	39
print.draws_array	40
print.draws_df	41
print.draws_list	42
print.draws_matrix	43
print.draws_rvars	44

print.rvar	45
quantile2	46
rdo	47
rename_variables	48
repair_draws	49
resample_draws	50
reserved_variables	52
rfun	53
rhat	55
rhat_basic	56
rstar	57
rvar	59
rvar-dist	61
rvar-matmult	62
rvar-summaries-over-draws	64
rvar-summaries-within-draws	67
rvar_apply	68
rvar_is_finite	70
rvar_rng	71
split_chains	72
subset_draws	73
thin_draws	75
vctrs-compat	76
weights.draws	77
weight_draws	78
[.draws_array	80
[.draws_matrix	80
Index	82

posterior-package *Tools for working with posterior (and prior) distributions*

Description

The **posterior** package is intended to provide useful tools for both users and developers of packages for fitting Bayesian models or working with output from Bayesian models. The primary goals of the package are to:

- Efficiently convert between many different useful formats of draws (samples) from posterior or prior distributions.
- Provide consistent methods for operations commonly performed on draws, for example, subsetting, binding, or mutating draws.
- Provide various summaries of draws in convenient formats.
- Provide lightweight implementations of state of the art posterior inference diagnostics.

Package options

The following options are used to format and print `draws` objects, as in `print.draws_array()`, `print.draws_df()`, `print.draws_list()`, `print.draws_matrix()`, and `print.draws_rvars()`:

- `posterior.max_draws`: Maximum number of draws to print.
- `posterior.max_iterations`: Maximum number of iterations to print.
- `posterior.max_chains`: Maximum number of chains to print.
- `posterior.max_variables`: Maximum number of variables to print.

The following option is used to format and print `rvar` objects, as in `print.rvar()` and `print.draws_rvars()`:

- `posterior.rvar_summary`: What style of summary to display: "mean_sd" displays mean±sd, "median_mad" displays median±mad.

The following option is used to construct new `rvar` objects, as in `rfun()` and `rdo()`:

- `posterior.rvar_ndraws`: The number of draws used to construct new random variables when this number cannot be determined from existing arguments (e.g., other `rvars` passed to a function).

The following options are used to control warning messages:

- `posterior.warn_on_merge_chains`: (logical) Some operations will trigger an automatic merging of chains, for example, because chains do not match between two objects involved in a binary operation. Whether this causes a warning can be controlled by this option.

as_rvar

Coerce to a random variable

Description

Convert `x` to an `rvar` object.

Usage

```
as_rvar(x, dim = NULL, dimnames = NULL, nchains = NULL)
```

Arguments

<code>x</code>	(multiple options) An object that can be converted to an <code>rvar</code> , such as a vector, array, or an <code>rvar</code> itself.
<code>dim</code>	(integer vector) One or more integers giving the maximal indices in each dimension to override the dimensions of the <code>rvar</code> to be created (see <code>dim()</code>). If <code>NULL</code> (the default), <code>dim</code> is determined by the input. NOTE: This argument controls the dimensions of the <code>rvar</code> , not the underlying array, so you cannot change the number of draws using this argument.
<code>dimnames</code>	(list) Character vectors giving the names in each dimension to override the names of the dimensions of the <code>rvar</code> to be created (see <code>dimnames()</code>). If <code>NULL</code> (the default), this is determined by the input. NOTE: This argument controls the names of the dimensions of the <code>rvar</code> , not the underlying array.
<code>nchains</code>	(positive integer) The number of chains. The default is 1.

Details

For objects that are already [rvars](#), returns them (with modified dimensions if `dim` is not `NULL`).

For numeric or logical vectors or arrays, returns an [rvar](#) with a single draw and the same dimensions as `x`. This is in contrast to the [rvar\(\)](#) constructor, which treats the first dimension of `x` as the draws dimension. As a result, [as_rvar\(\)](#) is useful for creating constants.

Value

An object of class "rvar" representing a random variable.

See Also

[rvar\(\)](#) to construct [rvars](#) directly. See [rdo\(\)](#), [rfun\(\)](#), and [rvar_rng\(\)](#) for higher-level interfaces for creating [rvars](#).

Examples

```
# You can use as_rvar() to create "constant" rvars (having only one draw):
x <- as_rvar(1)
x

# Such constants can be of arbitrary shape:
as_rvar(1:4)
as_rvar(matrix(1:10, nrow = 5))
as_rvar(array(1:12, dim = c(2, 3, 2)))
```

bind_draws

Bind draws objects together

Description

Bind multiple [draws](#) objects together to form a single draws object.

Usage

```
bind_draws(x, ...)
```

```
## S3 method for class 'draws_matrix'
bind_draws(x, ..., along = "variable")
```

```
## S3 method for class 'draws_array'
bind_draws(x, ..., along = "variable")
```

```
## S3 method for class 'draws_df'
bind_draws(x, ..., along = "variable")
```

```
## S3 method for class 'draws_list'
bind_draws(x, ..., along = "variable")

## S3 method for class 'draws_rvars'
bind_draws(x, ..., along = "variable")
```

Arguments

`x` (draws) A [draws](#) object. The draws format of `x` will define the format of the returned draws object.

`...` (draws) Additional [draws](#) objects to bind to `x`.

`along` (string) The dimension along which draws objects should be bound together. Possible values are "variable" (the default), "chain", "iteration", and "draw". Not all options are supported for all input formats.

Value

A draws object of the same class as `x`.

Examples

```
x1 <- draws_matrix(alpha = rnorm(5), beta = rnorm(5))
x2 <- draws_matrix(alpha = rnorm(5), beta = rnorm(5))
ndraws(x1)
ndraws(x2)
x3 <- bind_draws(x1, x2, along = "draw")
ndraws(x3)

x4 <- draws_matrix(theta = rexp(5))
x5 <- bind_draws(x1, x4, along = "variable")
variables(x5)
```

chol.rvar

Cholesky decomposition of random matrix

Description

Cholesky decomposition of an [rvar](#) containing a matrix.

Usage

```
## S3 method for class 'rvar'
chol(x, ...)
```

Arguments

`x` (rvar) A 2-dimensional [rvar](#).
`...` Additional parameters passed on to `chol.tensor()`

Value

An [rvar](#) containing the upper triangular factor of the Cholesky decomposition, i.e., the matrix R such that $R'R = x$.

diagnostics *List of available convergence diagnostics*

Description

A list of available diagnostics and links to their individual help pages.

Details

Function	Description
ess_basic()	Basic version of effective sample size
ess_bulk()	Bulk effective sample size
ess_tail()	Tail effective sample size
ess_quantile()	Effective sample sizes for quantiles
ess_sd()	Effective sample sizes for standard deviations
mcse_mean()	Monte Carlo standard error for the mean
mcse_quantile()	Monte Carlo standard error for quantiles
mcse_sd()	Monte Carlo standard error for standard deviations
rhat_basic()	Basic version of Rhat
rhat()	Improved, rank-based version of Rhat
rstar()	R* diagnostic

Value

See individual functions for a description of return types.

draws *Transform to draws objects*

Description

Try to transform an R object to a format supported by the **posterior** package.

Usage

```
as_draws(x, ...)
```

```
is_draws(x)
```

Arguments

`x` (draws) A draws object or another R object for which the method is defined.
`...` Arguments passed to individual methods (if applicable).

Details

The class "draws" is the parent class of all supported formats, which also have their own subclasses of the form "draws_{format}" (e.g. "draws_array").

Value

If possible, a draws object in the closest supported format to `x`. The formats are linked to in the **See Also** section below.

See Also

Other formats: [draws_array\(\)](#), [draws_df\(\)](#), [draws_list\(\)](#), [draws_matrix\(\)](#), [draws_rvars\(\)](#)

Examples

```
# create some random draws
x <- matrix(rnorm(30), nrow = 10)
colnames(x) <- c("a", "b", "c")
str(x)

# transform to a draws object
y <- as_draws(x)
str(y)

# remove the draws classes from the object
class(y) <- class(y)[-1:2]
str(y)
```

draws-index

Index draws objects

Description

Index variables, iterations, chains, and draws.

Usage

```
variables(x, ...)  
  
variables(x) <- value  
  
iteration_ids(x)  
  
chain_ids(x)  
  
draw_ids(x)  
  
nvariables(x, ...)  
  
niterations(x)  
  
nchains(x)  
  
ndraws(x)
```

Arguments

x	(draws) A draws object or another R object for which the method is defined.
...	Arguments passed to individual methods (if applicable).
value	(character vector) For <code>variables(x) <-value</code> , the new variable names to use.

Details

The methods `variables()`, `iteration_ids()`, `chain_ids()`, and `draw_ids()` return vectors of all variables, iterations, chains, and draws, respectively. In contrast, the methods `nvariables()`, `niterations()`, `nchains()`, and `ndraws()` return the number of variables, iterations, chains, and draws, respectively.

`variables(x) <-value` allows you to modify the vector of variable names, similar to how `names(x) <-value` works for vectors and lists. For renaming specific variables, `rename_variables()` may offer a more convenient approach.

Value

For `variables()`, a character vector.

For `iteration_ids()`, `chain_ids()`, and `draw_ids()`, an integer vector.

For `niterations()`, `nchains()`, and `ndraws()`, a scalar integer.

Examples

```
x <- example_draws()  
  
variables(x)  
nvariables(x)  
variables(x) <- letters[1:nvariables(x)]
```

```
iteration_ids(x)
niterations(x)
```

```
chain_ids(x)
nchains(x)
```

```
draw_ids(x)
ndraws(x)
```

```
draws_array
```

```
The draws_array format
```

Description

The `as_draws_array()` methods convert objects to the `draws_array` format. The `draws_array()` function creates an object of the `draws_array` format based on a set of numeric vectors. See **Details**.

Usage

```
as_draws_array(x, ...)

## Default S3 method:
as_draws_array(x, ...)

## S3 method for class 'draws_array'
as_draws_array(x, ...)

## S3 method for class 'draws_matrix'
as_draws_array(x, ...)

## S3 method for class 'draws_df'
as_draws_array(x, ...)

## S3 method for class 'draws_list'
as_draws_array(x, ...)

## S3 method for class 'draws_rvars'
as_draws_array(x, ...)

## S3 method for class 'mcmc'
as_draws_array(x, ...)

## S3 method for class 'mcmc.list'
as_draws_array(x, ...)
```

```
draws_array(..., .nchains = 1)
```

```
is_draws_array(x)
```

Arguments

x An object to convert to a `draws_array` object.

... For `as_draws_array()`: Arguments passed to individual methods (if applicable). For `draws_array()`: Named arguments containing numeric vectors each defining a separate variable.

.nchains (positive integer) The number of chains. The default is 1.

Details

Objects of class "draws_array" are 3-D arrays with dimensions "iteration", "chain", and "variable". See **Examples**.

Value

A `draws_array` object, which has classes `c("draws_array", "draws", "array")`.

See Also

Other formats: [draws_df\(\)](#), [draws_list\(\)](#), [draws_matrix\(\)](#), [draws_rvars\(\)](#), [draws](#)

Examples

```
x1 <- as_draws_array(example_draws())
class(x1)
print(x1)
str(x1)

x2 <- draws_array(a = rnorm(10), b = rnorm(10), c = 1)
class(x2)
print(x2)
str(x2)
```

draws_df

The draws_df format

Description

The `as_draws_df()` methods convert objects to the `draws_df` format. The `draws_df()` function creates an object of the `draws_df` format based on a set of numeric vectors. See **Details**.

Usage

```

as_draws_df(x, ...)

## Default S3 method:
as_draws_df(x, ...)

## S3 method for class 'data.frame'
as_draws_df(x, ...)

## S3 method for class 'draws_df'
as_draws_df(x, ...)

## S3 method for class 'draws_matrix'
as_draws_df(x, ...)

## S3 method for class 'draws_array'
as_draws_df(x, ...)

## S3 method for class 'draws_list'
as_draws_df(x, ...)

## S3 method for class 'draws_rvars'
as_draws_df(x, ...)

## S3 method for class 'mcmc'
as_draws_df(x, ...)

## S3 method for class 'mcmc.list'
as_draws_df(x, ...)

draws_df(..., .nchains = 1)

is_draws_df(x)

```

Arguments

x	An object to convert to a draws_df object.
...	For as_draws_df(): Arguments passed to individual methods (if applicable). For draws_df(): Named arguments containing numeric vectors each defining a separate variable.
.nchains	(positive integer) The number of chains. The default is 1.

Details

Objects of class "draws_df" are [tibble](#) data frames. They have one column per variable as well as additional metadata columns ".iteration", ".chain", and ".draw". The difference between the ".iteration" and ".draw" columns is that the former is relative to the MCMC chain while the latter ignores the chain information and has all unique values. See **Examples**.

If a data.frame-like object is supplied to `as_draws_df` that contains columns named `".iteration"` or `".chain"`, they will be treated as iteration and chain indices, respectively. See **Examples**.

Value

A `draws_df` object, which has classes `c("draws_df", "draws", class(tibble::tibble()))`.

See Also

Other formats: [draws_array\(\)](#), [draws_list\(\)](#), [draws_matrix\(\)](#), [draws_rvars\(\)](#), [draws](#)

Examples

```
x1 <- as_draws_df(example_draws())
class(x1)
print(x1)
str(x1)

x2 <- draws_df(a = rnorm(10), b = rnorm(10), c = 1)
class(x2)
print(x2)
str(x2)

# the difference between iteration and draw is clearer when contrasting
# the head and tail of the data frame
print(head(x1, reserved = TRUE, max_variables = 2))
print(tail(x1, reserved = TRUE, max_variables = 2))

# manually supply chain information
xnew <- data.frame(mu = rnorm(10), .chain = rep(1:2, each = 5))
xnew <- as_draws_df(xnew)
print(xnew)
```

draws_list

The draws_list format

Description

The `as_draws_list()` methods convert objects to the `draws_list` format. The `draws_list()` function creates an object of the `draws_list` format based on a set of numeric vectors. See **Details**.

Usage

```
as_draws_list(x, ...)

## Default S3 method:
as_draws_list(x, ...)
```

```

## S3 method for class 'draws_list'
as_draws_list(x, ...)

## S3 method for class 'draws_matrix'
as_draws_list(x, ...)

## S3 method for class 'draws_array'
as_draws_list(x, ...)

## S3 method for class 'draws_df'
as_draws_list(x, ...)

## S3 method for class 'draws_rvars'
as_draws_list(x, ...)

## S3 method for class 'mcmc'
as_draws_list(x, ...)

## S3 method for class 'mcmc.list'
as_draws_list(x, ...)

draws_list(..., .nchains = 1)

is_draws_list(x)

```

Arguments

<code>x</code>	An object to convert to a <code>draws_list</code> object.
<code>...</code>	For <code>as_draws_list()</code> : Arguments passed to individual methods (if applicable). For <code>draws_list()</code> : Named arguments containing numeric vectors each defining a separate variable.
<code>.nchains</code>	(positive integer) The number of chains. The default is 1.

Details

Objects of class "draws_list" are lists with one element per MCMC chain. Each of these elements is itself a named list of numeric vectors with one vector per variable. The length of each vector is equal to the number of saved iterations per chain. See **Examples**.

Value

A `draws_list` object, which has classes `c("draws_list", "draws", "list")`.

See Also

Other formats: [draws_array\(\)](#), [draws_df\(\)](#), [draws_matrix\(\)](#), [draws_rvars\(\)](#), [draws](#)

Examples

```
x1 <- as_draws_list(example_draws())
class(x1)
print(x1)
str(x1)

x2 <- draws_list(a = rnorm(10), b = rnorm(10), c = 1)
class(x2)
print(x2)
str(x2)
```

draws_matrix	<i>The draws_matrix format</i>
--------------	--------------------------------

Description

The `as_draws_matrix()` methods convert objects to the `draws_matrix` format. The `draws_matrix()` function creates an object of the `draws_matrix` format based on a set of numeric vectors. See **Details**.

Usage

```
as_draws_matrix(x, ...)

## Default S3 method:
as_draws_matrix(x, ...)

## S3 method for class 'draws_matrix'
as_draws_matrix(x, ...)

## S3 method for class 'draws_array'
as_draws_matrix(x, ...)

## S3 method for class 'draws_df'
as_draws_matrix(x, ...)

## S3 method for class 'draws_list'
as_draws_matrix(x, ...)

## S3 method for class 'draws_rvars'
as_draws_matrix(x, ...)

## S3 method for class 'mcmc'
as_draws_matrix(x, ...)

## S3 method for class 'mcmc.list'
as_draws_matrix(x, ...)
```

```
draws_matrix(..., .nchains = 1)
```

```
is_draws_matrix(x)
```

Arguments

x An object to convert to a `draws_matrix` object.

... For `as_draws_matrix()`: Arguments passed to individual methods (if applicable). For `draws_matrix()`: Named arguments containing numeric vectors each defining a separate variable.

.nchains (positive integer) The number of chains. The default is 1.

Details

Objects of class "draws_matrix" are matrices (2-D arrays) with dimensions "draw" and "variable". See **Examples**.

Value

A `draws_matrix` object, which has classes `c("draws_matrix", "draws", "matrix")`.

See Also

Other formats: [draws_array\(\)](#), [draws_df\(\)](#), [draws_list\(\)](#), [draws_rvars\(\)](#), [draws](#)

Examples

```
x1 <- as_draws_matrix(example_draws())
class(x1)
print(x1)
str(x1)
```

```
x2 <- draws_matrix(a = rnorm(10), b = rnorm(10), c = 1)
class(x2)
print(x2)
str(x2)
```

draws_of

Get/set array of draws underlying a random variable

Description

Gets/sets the array-representation that backs an [rvar](#). Should be used rarely.

Usage

```
draws_of(x, with_chains = FALSE)

draws_of(x, with_chains = FALSE) <- value
```

Arguments

x (rvar) An [rvar](#) object.

with_chains (logical) Should the array of draws include a dimension for chains? If FALSE (the default), chains are not included and the array has dimension `c(ndraws(x), dim(x))`. If TRUE, chains are included and the array has dimension `c(niterations(x), nchains(x), dim(x))`.

value (array) An array of values to use as the backing array of `x`.

Details

While [rvars](#) implement fast versions of basic math operations (including [matrix multiplication](#)), sometimes you may need to bypass the [rvar](#) abstraction to do what you need to do more efficiently. `draws_of()` allows you to get / set the underlying array of draws in order to do that.

[rvars](#) represent draws internally using arrays of arbitrary dimension, which is returned by `draws_of(x)` and can be set using `draws_of(x) <- value`. The **first** dimension of these arrays is the index of the draws. If `with_chains = TRUE`, then the dimensions of the returned array are modified so that the first dimension is the index of the iterations and the second dimension is the index of the chains.

Value

If `with_chains = FALSE`, an array with dimensions `c(ndraws(x), dim(x))`.

If `with_chains = TRUE`, an array with dimensions `c(niterations(x), nchains(x), dim(x))`.

Examples

```
x <- rvar(1:10, nchains = 2)
x

# draws_of() without arguments will return the array of draws without
# chain information (first dimension is draw)
draws_of(x)

# draws_of() with with_chains = TRUE will reshape the returned array to
# include chain information in the second dimension
draws_of(x, with_chains = TRUE)

# you can also set draws using draws_of(). When with_chains = FALSE the
# existing chain information will be retained ...
draws_of(x) <- 2:11
x

# when with_chains = TRUE the chain information will be set by the
# second dimension of the assigned array
```

```
draws_of(x, with_chains = TRUE) <- array(2:11, dim = c(2,5))
x
```

draws_rvars

The draws_rvars format

Description

The `as_draws_rvars()` methods convert objects to the `draws_rvars` format. The `draws_rvars()` function creates an object of the `draws_rvars` format based on a set of numeric vectors. See **Details**.

Usage

```
as_draws_rvars(x, ...)

## Default S3 method:
as_draws_rvars(x, ...)

## S3 method for class 'draws_rvars'
as_draws_rvars(x, ...)

## S3 method for class 'list'
as_draws_rvars(x, ...)

## S3 method for class 'draws_matrix'
as_draws_rvars(x, ...)

## S3 method for class 'draws_array'
as_draws_rvars(x, ...)

## S3 method for class 'draws_df'
as_draws_rvars(x, ...)

## S3 method for class 'draws_list'
as_draws_rvars(x, ...)

## S3 method for class 'mcmc'
as_draws_rvars(x, ...)

## S3 method for class 'mcmc.list'
as_draws_rvars(x, ...)

draws_rvars(..., .nchains = 1)

is_draws_rvars(x)
```

Arguments

<code>x</code>	An object to convert to a <code>draws_rvars</code> object.
<code>...</code>	For <code>as_draws_rvars()</code> : Arguments passed to individual methods (if applicable). For <code>draws_rvars()</code> : Named arguments containing numeric vectors each defining a separate variable.
<code>.nchains</code>	(positive integer) The number of chains. The default is 1.

Details

Objects of class "draws_rvars" are lists of `rvar` objects. See **Examples**.

Value

A `draws_rvars` object, which has classes `c("draws_rvars", "draws", "list")`.

See Also

Other formats: [draws_array\(\)](#), [draws_df\(\)](#), [draws_list\(\)](#), [draws_matrix\(\)](#), [draws](#)

Examples

```
x1 <- as_draws_rvars(example_draws())
class(x1)
print(x1)
str(x1)

x2 <- draws_rvars(a = rnorm(10), b = rnorm(10), c = 1)
class(x2)
print(x2)
str(x2)
```

draws_summary

Summaries of draws objects

Description

The `summarise_draws()` (and `summarize_draws()`) methods provide a quick way to get a table of summary statistics and diagnostics. These methods will convert an object to a `draws` object if it isn't already. For convenience, a `summary()` method for `draws` and `rvar` objects are also provided as an alias for `summarise_draws()` if the input object is a `draws` or `rvar` object.

Usage

```

summarise_draws(.x, ...)

summarize_draws(.x, ...)

## S3 method for class 'draws'
summarise_draws(.x, ..., .args = list(), .cores = 1)

## S3 method for class 'draws'
summary(object, ...)

## S3 method for class 'rvar'
summarise_draws(.x, ...)

## S3 method for class 'rvar'
summary(object, ...)

default_summary_measures()

default_convergence_measures()

default_mcse_measures()

```

Arguments

<code>.x, object</code>	(draws) A draws object or one coercible to a draws object.
<code>...</code>	Name-value pairs of summary or diagnostic functions. The provided names will be used as the names of the columns in the result <i>unless</i> the function returns a named vector, in which case the latter names are used. The functions can be specified in any format supported by as_function() . See Examples .
<code>.args</code>	(named list) Optional arguments passed to the summary functions.
<code>.cores</code>	(positive integer) The number of cores to use for computing summaries for different variables in parallel. Coerced to integer if possible, otherwise errors. The default is <code>.cores = 1</code> , in which case no parallelization is implemented. By default, a socket cluster is used on Windows and forks otherwise.

Details

The default summary functions used are the ones specified by `default_summary_measures()` and `default_convergence_measures()`:

```
default_summary_measures()
```

- [mean\(\)](#)
- [median\(\)](#)
- [sd\(\)](#)
- [mad\(\)](#)

- [quantile2\(\)](#)

`default_convergence_measures()`

- [rhat\(\)](#)
- [ess_bulk\(\)](#)
- [ess_tail\(\)](#)

The `var()` function should not be used to compute variances due to its inconsistent behavior with matrices. Instead, please use `distributional::variance()`.

Value

The `summarise_draws()` methods return a [tibble](#) data frame. The first column ("variable") contains the variable names and the remaining columns contain summary statistics and diagnostics.

The functions `default_summary_measures()`, `default_convergence_measures()`, and `default_mcse_measures()` return character vectors of names of the default measures.

See Also

[diagnostics](#) for a list of available diagnostics and links to their individual help pages.

Examples

```
x <- example_draws("eight_schools")
class(x)
str(x)

summarise_draws(x)
summarise_draws(x, "mean", "median")
summarise_draws(x, mean, mcse = mcse_mean)
summarise_draws(x, ~quantile(.x, probs = c(0.4, 0.6)))

# using default_*_measures()
summarise_draws(x, default_summary_measures())
summarise_draws(x, default_convergence_measures())
summarise_draws(x, default_mcse_measures())

# compute variance of variables
summarise_draws(x, var = distributional::variance)

# illustrate use of '.args'
ws <- rexp(ndraws(x))
summarise_draws(x, weighted.mean, .args = list(w = ws))
```

 ess_basic

Basic version of the effective sample size

Description

Compute the basic effective sample size (ESS) estimate for a single variable as described in Gelman et al. (2013). For practical applications, we strongly recommend the improved ESS convergence diagnostics implemented in [ess_bulk\(\)](#) and [ess_tail\(\)](#).

Usage

```
ess_basic(x, ...)

## Default S3 method:
ess_basic(x, split = TRUE, ...)

## S3 method for class 'rvar'
ess_basic(x, split = TRUE, ...)
```

Arguments

x	(multiple options) One of: <ul style="list-style-type: none"> • A matrix of draws for a single variable (iterations x chains). See extract_variable_matrix(). • An rvar.
...	Arguments passed to individual methods (if applicable).
split	(logical) Should the estimate be computed on split chains? The default is TRUE.

Value

If the input is an array, returns a single numeric value. If any of the draws is non-finite, that is, NA, NaN, Inf, or -Inf, the returned output will be (numeric) NA. Also, if all draws within any of the chains of a variable are the same (constant), the returned output will be (numeric) NA as well. The reason for the latter is that, for constant draws, we cannot distinguish between variables that are supposed to be constant (e.g., a diagonal element of a correlation matrix is always 1) or variables that just happened to be constant because of a failure of convergence or other problems in the sampling process.

If the input is an [rvar](#), returns an array of the same dimensions as the [rvar](#), where each element is equal to the value that would be returned by passing the draws array for that element of the [rvar](#) to this function.

References

Andrew Gelman, John B. Carlin, Hal S. Stern, David B. Dunson, Aki Vehtari and Donald B. Rubin (2013). Bayesian Data Analysis, Third Edition. Chapman and Hall/CRC.

See Also

Other diagnostics: [ess_bulk\(\)](#), [ess_quantile\(\)](#), [ess_sd\(\)](#), [ess_tail\(\)](#), [mcse_mean\(\)](#), [mcse_quantile\(\)](#), [mcse_sd\(\)](#), [rhat_basic\(\)](#), [rhat\(\)](#), [rstar\(\)](#)

Examples

```
mu <- extract_variable_matrix(example_draws(), "mu")
ess_basic(mu)
```

```
d <- as_draws_rvars(example_draws("multi_normal"))
ess_basic(d$Sigma)
```

 ess_bulk

Bulk effective sample size (bulk-ESS)

Description

Compute a bulk effective sample size estimate (bulk-ESS) for a single variable. Bulk-ESS is useful as a diagnostic for the sampling efficiency in the bulk of the posterior. It is defined as the effective sample size for rank normalized values using split chains. For the tail effective sample size see [ess_tail\(\)](#).

Usage

```
ess_bulk(x, ...)

## Default S3 method:
ess_bulk(x, ...)

## S3 method for class 'rvar'
ess_bulk(x, ...)
```

Arguments

`x` (multiple options) One of:

- A matrix of draws for a single variable (iterations x chains). See [extract_variable_matrix\(\)](#).
- An [rvar](#).

`...` Arguments passed to individual methods (if applicable).

Value

If the input is an array, returns a single numeric value. If any of the draws is non-finite, that is, NA, NaN, Inf, or -Inf, the returned output will be (numeric) NA. Also, if all draws within any of the chains of a variable are the same (constant), the returned output will be (numeric) NA as well. The reason for the latter is that, for constant draws, we cannot distinguish between variables that are supposed to be constant (e.g., a diagonal element of a correlation matrix is always 1) or variables

that just happened to be constant because of a failure of convergence or other problems in the sampling process.

If the input is an `rvar`, returns an array of the same dimensions as the `rvar`, where each element is equal to the value that would be returned by passing the draws array for that element of the `rvar` to this function.

References

Aki Vehtari, Andrew Gelman, Daniel Simpson, Bob Carpenter, and Paul-Christian Bürkner (2019). Rank-normalization, folding, and localization: An improved R-hat for assessing convergence of MCMC. *arXiv preprint arXiv:1903.08008*.

See Also

Other diagnostics: `ess_basic()`, `ess_quantile()`, `ess_sd()`, `ess_tail()`, `mcse_mean()`, `mcse_quantile()`, `mcse_sd()`, `rhat_basic()`, `rhat()`, `rstar()`

Examples

```
mu <- extract_variable_matrix(example_draws(), "mu")
ess_bulk(mu)

d <- as_draws_rvars(example_draws("multi_normal"))
ess_bulk(d$Sigma)
```

ess_mean

Effective sample size for the mean

Description

Compute an effective sample size estimate for a mean (expectation) estimate of a single variable.

Usage

```
ess_mean(x, ...)

## S3 method for class 'rvar'
ess_mean(x, ...)
```

Arguments

`x` (multiple options) One of:

- A matrix of draws for a single variable (iterations x chains). See `extract_variable_matrix()`.
- An `rvar`.

`...` Arguments passed to individual methods (if applicable).

Value

If the input is an array, returns a single numeric value. If any of the draws is non-finite, that is, NA, NaN, Inf, or -Inf, the returned output will be (numeric) NA. Also, if all draws within any of the chains of a variable are the same (constant), the returned output will be (numeric) NA as well. The reason for the latter is that, for constant draws, we cannot distinguish between variables that are supposed to be constant (e.g., a diagonal element of a correlation matrix is always 1) or variables that just happened to be constant because of a failure of convergence or other problems in the sampling process.

If the input is an `rvar`, returns an array of the same dimensions as the `rvar`, where each element is equal to the value that would be returned by passing the draws array for that element of the `rvar` to this function.

References

Andrew Gelman, John B. Carlin, Hal S. Stern, David B. Dunson, Aki Vehtari and Donald B. Rubin (2013). Bayesian Data Analysis, Third Edition. Chapman and Hall/CRC.

Examples

```
mu <- extract_variable_matrix(example_draws(), "mu")
ess_mean(mu)

d <- as_draws_rvars(example_draws("multi_normal"))
ess_mean(d$Sigma)
```

ess_quantile

Effective sample sizes for quantiles

Description

Compute effective sample size estimates for quantile estimates of a single variable.

Usage

```
ess_quantile(x, probs = c(0.05, 0.95), ...)
```

Default S3 method:

```
ess_quantile(x, probs = c(0.05, 0.95), names = TRUE, ...)
```

S3 method for class 'rvar'

```
ess_quantile(x, probs = c(0.05, 0.95), names = TRUE, ...)
```

```
ess_median(x, ...)
```

Default S3 method:

```
ess_mean(x, ...)
```

Arguments

<code>x</code>	(multiple options) One of: <ul style="list-style-type: none"> • A matrix of draws for a single variable (iterations x chains). See <code>extract_variable_matrix()</code>. • An <code>rvar</code>.
<code>probs</code>	(numeric vector) Probabilities in [0, 1].
<code>...</code>	Arguments passed to individual methods (if applicable).
<code>names</code>	(logical) Should the result have a <code>names</code> attribute? The default is <code>TRUE</code> , but use <code>FALSE</code> for improved speed if there are many values in <code>probs</code> .

Value

If the input is an array, returns a numeric vector with one element per quantile. If any of the draws is non-finite, that is, `NA`, `NaN`, `Inf`, or `-Inf`, the returned output will be a vector of (numeric) `NA` values. Also, if all draws of a variable are the same (constant), the returned output will be a vector of (numeric) `NA` values as well. The reason for the latter is that, for constant draws, we cannot distinguish between variables that are supposed to be constant (e.g., a diagonal element of a correlation matrix is always 1) or variables that just happened to be constant because of a failure of convergence or other problems in the sampling process.

If the input is an `rvar` and `length(probs) == 1`, returns an array of the same dimensions as the `rvar`, where each element is equal to the value that would be returned by passing the draws array for that element of the `rvar` to this function. If `length(probs) > 1`, the first dimension of the result indexes the input probabilities; i.e. the result has dimension `c(length(probs), dim(x))`.

References

Aki Vehtari, Andrew Gelman, Daniel Simpson, Bob Carpenter, and Paul-Christian Bürkner (2019). Rank-normalization, folding, and localization: An improved R-hat for assessing convergence of MCMC. *arXiv preprint arXiv:1903.08008*.

See Also

Other diagnostics: `ess_basic()`, `ess_bulk()`, `ess_sd()`, `ess_tail()`, `mcse_mean()`, `mcse_quantile()`, `mcse_sd()`, `rhat_basic()`, `rhat()`, `rstar()`

Examples

```
mu <- extract_variable_matrix(example_draws(), "mu")
ess_quantile(mu, probs = c(0.1, 0.9))

d <- as_draws_rvars(example_draws("multi_normal"))
ess_quantile(d$mu, probs = c(0.1, 0.9))
```

`ess_sd`*Effective sample size for the standard deviation*

Description

Compute an effective sample size estimate for the standard deviation (SD) estimate of a single variable. This is defined as minimum of the effective sample size estimate for the mean and the the effective sample size estimate for the mean of the squared value.

Usage

```
ess_sd(x, ...)  
  
## Default S3 method:  
ess_sd(x, ...)  
  
## S3 method for class 'rvar'  
ess_sd(x, ...)
```

Arguments

`x` (multiple options) One of:

- A matrix of draws for a single variable (iterations x chains). See [extract_variable_matrix\(\)](#).
- An [rvar](#).

`...` Arguments passed to individual methods (if applicable).

Value

If the input is an array, returns a single numeric value. If any of the draws is non-finite, that is, NA, NaN, Inf, or -Inf, the returned output will be (numeric) NA. Also, if all draws within any of the chains of a variable are the same (constant), the returned output will be (numeric) NA as well. The reason for the latter is that, for constant draws, we cannot distinguish between variables that are supposed to be constant (e.g., a diagonal element of a correlation matrix is always 1) or variables that just happened to be constant because of a failure of convergence or other problems in the sampling process.

If the input is an [rvar](#), returns an array of the same dimensions as the [rvar](#), where each element is equal to the value that would be returned by passing the draws array for that element of the [rvar](#) to this function.

References

Aki Vehtari, Andrew Gelman, Daniel Simpson, Bob Carpenter, and Paul-Christian Bürkner (2019). Rank-normalization, folding, and localization: An improved R-hat for assessing convergence of MCMC. *arXiv preprint arXiv:1903.08008*.

See Also

Other diagnostics: [ess_basic\(\)](#), [ess_bulk\(\)](#), [ess_quantile\(\)](#), [ess_tail\(\)](#), [mcse_mean\(\)](#), [mcse_quantile\(\)](#), [mcse_sd\(\)](#), [rhat_basic\(\)](#), [rhat\(\)](#), [rstar\(\)](#)

Examples

```
mu <- extract_variable_matrix(example_draws(), "mu")
ess_sd(mu)
```

```
d <- as_draws_rvars(example_draws("multi_normal"))
ess_sd(d$Sigma)
```

 ess_tail

Tail effective sample size (tail-ESS)

Description

Compute a tail effective sample size estimate (tail-ESS) for a single variable. Tail-ESS is useful as a diagnostic for the sampling efficiency in the tails of the posterior. It is defined as the minimum of the effective sample sizes for 5% and 95% quantiles. For the bulk effective sample size see [ess_bulk\(\)](#).

Usage

```
ess_tail(x, ...)

## Default S3 method:
ess_tail(x, ...)

## S3 method for class 'rvar'
ess_tail(x, ...)
```

Arguments

`x` (multiple options) One of:

- A matrix of draws for a single variable (iterations x chains). See [extract_variable_matrix\(\)](#).
- An [rvar](#).

`...` Arguments passed to individual methods (if applicable).

Value

If the input is an array, returns a single numeric value. If any of the draws is non-finite, that is, NA, NaN, Inf, or -Inf, the returned output will be (numeric) NA. Also, if all draws within any of the chains of a variable are the same (constant), the returned output will be (numeric) NA as well. The reason for the latter is that, for constant draws, we cannot distinguish between variables that are supposed to be constant (e.g., a diagonal element of a correlation matrix is always 1) or variables

that just happened to be constant because of a failure of convergence or other problems in the sampling process.

If the input is an `rvar`, returns an array of the same dimensions as the `rvar`, where each element is equal to the value that would be returned by passing the draws array for that element of the `rvar` to this function.

References

Aki Vehtari, Andrew Gelman, Daniel Simpson, Bob Carpenter, and Paul-Christian Bürkner (2019). Rank-normalization, folding, and localization: An improved R-hat for assessing convergence of MCMC. *arXiv preprint arXiv:1903.08008*.

See Also

Other diagnostics: `ess_basic()`, `ess_bulk()`, `ess_quantile()`, `ess_sd()`, `mcse_mean()`, `mcse_quantile()`, `mcse_sd()`, `rhat_basic()`, `rhat()`, `rstar()`

Examples

```
mu <- extract_variable_matrix(example_draws(), "mu")
ess_tail(mu)

d <- as_draws_rvars(example_draws("multi_normal"))
ess_tail(d$Sigma)
```

example_draws

Example draws objects

Description

Objects for use in examples, vignettes, and tests.

Usage

```
example_draws(example = "eight_schools")
```

Arguments

`example` (string) The name of the example draws object. See **Details** for available options.

Details

The following example draws objects are available.

eight_schools: A `draws_array` object with 100 iterations from each of 4 Markov chains obtained by fitting the eight schools model described in Gelman et al. (2013) with `Stan`. The variables are:

- `mu`: Overall mean of the eight schools
- `tau`: Standard deviation between schools
- `theta`: Individual means of each of the eight schools

multi_normal: A `draws_array` object with 100 iterations from each of the 4 Markov chains obtained by fitting a 3-dimensional multivariate normal model to 100 simulated observations. The variables are:

- `mu`: Mean parameter vector of length 3
- `Sigma`: Covariance matrix of dimension 3 x 3

Value

A draws object.

Note

These objects are only intended to be used in demonstrations and tests. They contain fewer iterations and chains than recommended for performing actual inference.

References

Andrew Gelman, John B. Carlin, Hal S. Stern, David B. Dunson, Aki Vehtari and Donald B. Rubin (2013). Bayesian Data Analysis, Third Edition. Chapman and Hall/CRC.

Examples

```
draws_eight_schools <- example_draws("eight_schools")
summarise_draws(draws_eight_schools)
```

```
draws_multi_normal <- example_draws("multi_normal")
summarise_draws(draws_multi_normal)
```

extract_variable	<i>Extract draws of a single variable</i>
------------------	---

Description

Extract a vector of draws of a single variable.

Usage

```
extract_variable(x, variable, ...)  
  
## Default S3 method:  
extract_variable(x, variable, ...)  
  
## S3 method for class 'draws'  
extract_variable(x, variable, ...)  
  
## S3 method for class 'draws_rvars'  
extract_variable(x, variable, ...)
```

Arguments

x	(draws) A draws object or another R object for which the method is defined.
variable	(string) The name of the variable to extract.
...	Arguments passed to individual methods (if applicable).

Value

A numeric vector of length equal to the number of draws.

Examples

```
x <- example_draws()  
mu <- extract_variable(x, variable = "mu")  
str(mu)
```

extract_variable_matrix	<i>Extract matrix of a single variable</i>
-------------------------	--

Description

Extract an iterations x chains matrix of draws of a single variable. This is primarily used for convergence diagnostic functions such as `rhat()`.

Usage

```
extract_variable_matrix(x, variable, ...)

## Default S3 method:
extract_variable_matrix(x, variable, ...)

## S3 method for class 'draws'
extract_variable_matrix(x, variable, ...)

## S3 method for class 'draws_rvars'
extract_variable_matrix(x, variable, ...)
```

Arguments

`x` (draws) A draws object or another R object for which the method is defined.
`variable` (string) The name of the variable to extract.
`...` Arguments passed to individual methods (if applicable).

Value

A matrix with dimension iterations x chains.

Examples

```
x <- example_draws()
mu <- extract_variable_matrix(x, variable = "mu")
dim(mu)
rhat(mu)
```

is_rvar

Is x a random variable?

Description

Test if `x` is an [rvar](#).

Usage

```
is_rvar(x)
```

Arguments

`x` (any object) An object to test.

Value

TRUE if `x` is an [rvar](#), FALSE otherwise.

See Also

[as_rvar\(\)](#) to convert objects to rvars.

mcse_mean

Monte Carlo standard error for the mean

Description

Compute the Monte Carlo standard error for the mean (expectation) of a single variable.

Usage

```
mcse_mean(x, ...)

## Default S3 method:
mcse_mean(x, ...)

## S3 method for class 'rvar'
mcse_mean(x, ...)
```

Arguments

`x` (multiple options) One of:

- A matrix of draws for a single variable (iterations x chains). See [extract_variable_matrix\(\)](#).
- An [rvar](#).

`...` Arguments passed to individual methods (if applicable).

Value

If the input is an array, returns a single numeric value. If any of the draws is non-finite, that is, NA, NaN, Inf, or -Inf, the returned output will be (numeric) NA. Also, if all draws within any of the chains of a variable are the same (constant), the returned output will be (numeric) NA as well. The reason for the latter is that, for constant draws, we cannot distinguish between variables that are supposed to be constant (e.g., a diagonal element of a correlation matrix is always 1) or variables that just happened to be constant because of a failure of convergence or other problems in the sampling process.

If the input is an [rvar](#), returns an array of the same dimensions as the [rvar](#), where each element is equal to the value that would be returned by passing the draws array for that element of the [rvar](#) to this function.

References

Andrew Gelman, John B. Carlin, Hal S. Stern, David B. Dunson, Aki Vehtari and Donald B. Rubin (2013). Bayesian Data Analysis, Third Edition. Chapman and Hall/CRC.

See Also

Other diagnostics: [ess_basic\(\)](#), [ess_bulk\(\)](#), [ess_quantile\(\)](#), [ess_sd\(\)](#), [ess_tail\(\)](#), [mcse_quantile\(\)](#), [mcse_sd\(\)](#), [rhat_basic\(\)](#), [rhat\(\)](#), [rstar\(\)](#)

Examples

```
mu <- extract_variable_matrix(example_draws(), "mu")
mcse_mean(mu)
```

```
d <- as_draws_rvars(example_draws("multi_normal"))
mcse_mean(d$Sigma)
```

 mcse_quantile

Monte Carlo standard error for quantiles

Description

Compute Monte Carlo standard errors for quantile estimates of a single variable.

Usage

```
mcse_quantile(x, probs = c(0.05, 0.95), ...)

## Default S3 method:
mcse_quantile(x, probs = c(0.05, 0.95), names = TRUE, ...)

## S3 method for class 'rvar'
mcse_quantile(x, probs = c(0.05, 0.95), names = TRUE, ...)

mcse_median(x, ...)
```

Arguments

<code>x</code>	(multiple options) One of: <ul style="list-style-type: none"> • A matrix of draws for a single variable (iterations x chains). See extract_variable_matrix(). • An rvar.
<code>probs</code>	(numeric vector) Probabilities in [0, 1].
<code>...</code>	Arguments passed to individual methods (if applicable).
<code>names</code>	(logical) Should the result have a names attribute? The default is TRUE, but use FALSE for improved speed if there are many values in probs.

Value

If the input is an array, returns a numeric vector with one element per quantile. If any of the draws is non-finite, that is, NA, NaN, Inf, or -Inf, the returned output will be a vector of (numeric) NA values. Also, if all draws of a variable are the same (constant), the returned output will be a vector of (numeric) NA values as well. The reason for the latter is that, for constant draws, we cannot distinguish between variables that are supposed to be constant (e.g., a diagonal element of a correlation matrix is always 1) or variables that just happened to be constant because of a failure of convergence or other problems in the sampling process.

If the input is an `rvar` and `length(probs) == 1`, returns an array of the same dimensions as the `rvar`, where each element is equal to the value that would be returned by passing the draws array for that element of the `rvar` to this function. If `length(probs) > 1`, the first dimension of the result indexes the input probabilities; i.e. the result has dimension `c(length(probs), dim(x))`.

References

Aki Vehtari, Andrew Gelman, Daniel Simpson, Bob Carpenter, and Paul-Christian Bürkner (2019). Rank-normalization, folding, and localization: An improved R-hat for assessing convergence of MCMC. *arXiv preprint arXiv:1903.08008*.

See Also

Other diagnostics: `ess_basic()`, `ess_bulk()`, `ess_quantile()`, `ess_sd()`, `ess_tail()`, `mcse_mean()`, `mcse_sd()`, `rhat_basic()`, `rhat()`, `rstar()`

Examples

```
mu <- extract_variable_matrix(example_draws(), "mu")
mcse_quantile(mu, probs = c(0.1, 0.9))

d <- as_draws_rvars(example_draws("multi_normal"))
mcse_quantile(d$mu)
```

mcse_sd

Monte Carlo standard error for the standard deviation

Description

Compute the Monte Carlo standard error for the standard deviation (SD) of a single variable using Stirling's approximation and assuming approximate normality.

Usage

```
mcse_sd(x, ...)

## Default S3 method:
mcse_sd(x, ...)
```

```
## S3 method for class 'rvar'
mcse_sd(x, ...)
```

Arguments

x (multiple options) One of:

- A matrix of draws for a single variable (iterations x chains). See [extract_variable_matrix\(\)](#).
- An [rvar](#).

... Arguments passed to individual methods (if applicable).

Value

If the input is an array, returns a single numeric value. If any of the draws is non-finite, that is, NA, NaN, Inf, or -Inf, the returned output will be (numeric) NA. Also, if all draws within any of the chains of a variable are the same (constant), the returned output will be (numeric) NA as well. The reason for the latter is that, for constant draws, we cannot distinguish between variables that are supposed to be constant (e.g., a diagonal element of a correlation matrix is always 1) or variables that just happened to be constant because of a failure of convergence or other problems in the sampling process.

If the input is an [rvar](#), returns an array of the same dimensions as the [rvar](#), where each element is equal to the value that would be returned by passing the draws array for that element of the [rvar](#) to this function.

References

Aki Vehtari, Andrew Gelman, Daniel Simpson, Bob Carpenter, and Paul-Christian Bürkner (2019). Rank-normalization, folding, and localization: An improved R-hat for assessing convergence of MCMC. *arXiv preprint* arXiv:1903.08008.

See Also

Other diagnostics: [ess_basic\(\)](#), [ess_bulk\(\)](#), [ess_quantile\(\)](#), [ess_sd\(\)](#), [ess_tail\(\)](#), [mcse_mean\(\)](#), [mcse_quantile\(\)](#), [rhat_basic\(\)](#), [rhat\(\)](#), [rstar\(\)](#)

Examples

```
mu <- extract_variable_matrix(example_draws(), "mu")
mcse_sd(mu)

d <- as_draws_rvars(example_draws("multi_normal"))
mcse_sd(d$Sigma)
```

merge_chains	<i>Merge chains of draws objects</i>
--------------	--------------------------------------

Description

Merge chains of `draws` objects into a single chain. Some operations will trigger an automatic merging of chains, for example, because chains do not match between two objects involved in a binary operation. By default, no warning will be issued when this happens but you can activate one via `options(posterior.warn_on_merge_chains = TRUE)`.

Usage

```
merge_chains(x, ...)  
  
## S3 method for class 'draws_matrix'  
merge_chains(x, ...)  
  
## S3 method for class 'draws_array'  
merge_chains(x, ...)  
  
## S3 method for class 'draws_df'  
merge_chains(x, ...)  
  
## S3 method for class 'draws_list'  
merge_chains(x, ...)  
  
## S3 method for class 'rvar'  
merge_chains(x, ...)  
  
## S3 method for class 'draws_rvars'  
merge_chains(x, ...)
```

Arguments

`x` (draws) A draws object or another R object for which the method is defined.
`...` Arguments passed to individual methods (if applicable).

Value

A draws object of the same class as `x`.

Examples

```
x <- example_draws()  
  
# draws_array with 4 chains, 100 iters each  
str(x)
```

```
# draws_array with 1 chain of 400 iterations
str(merge_chains(x))
```

mutate_variables	<i>Mutate variables in draws objects</i>
------------------	--

Description

Mutate variables in a [draws](#) object.

Usage

```
mutate_variables(.x, ...)

## S3 method for class 'draws_matrix'
mutate_variables(.x, ...)

## S3 method for class 'draws_array'
mutate_variables(.x, ...)

## S3 method for class 'draws_df'
mutate_variables(.x, ...)

## S3 method for class 'draws_list'
mutate_variables(.x, ...)

## S3 method for class 'draws_rvars'
mutate_variables(.x, ...)
```

Arguments

<code>.x</code>	(draws) A draws object.
<code>...</code>	Name-value pairs of expressions, each with either length 1 or the same length as in the entire input (i.e., number of iterations or draws). The name of each argument will be the name of a new variable, and the value will be its corresponding value. Use a NULL value in <code>mutate_variables</code> to drop a variable. New variables overwrite existing variables of the same name.

Details

In order to mutate variables in [draws_matrix](#) and [draws_array](#) objects, they are transformed to [draws_df](#) objects first and then transformed back after mutation. As those transformations are quite expensive for larger number of draws, we recommend using `mutate_variables` on [draws_df](#) and [draws_list](#) objects if speed is an issue.

In [draws_rvars](#) objects, the output of each expression in `...` is coerced to an [rvar](#) object if it is not already one using `as_rvar()`.

Value

Returns a [draws](#) object of the same format as `.x`, with variables mutated according to the expressions provided in `...`

See Also

[variables](#), [rename_variables](#)

Examples

```
x <- as_draws_df(example_draws())
x <- subset(x, variable = c("mu", "tau"))

mutate_variables(x, tau2 = tau^2)
mutate_variables(x, scale = 1.96 * tau, lower = mu - scale)
```

order_draws

Order draws objects

Description

Order [draws](#) objects according to iteration and chain number. By default, draws objects are ordered but subsetting or extracting parts of them may leave them in an unordered state.

Usage

```
order_draws(x, ...)
```

S3 method for class 'draws_matrix'

```
order_draws(x, ...)
```

S3 method for class 'draws_array'

```
order_draws(x, ...)
```

S3 method for class 'draws_df'

```
order_draws(x, ...)
```

S3 method for class 'draws_list'

```
order_draws(x, ...)
```

S3 method for class 'draws_rvars'

```
order_draws(x, ...)
```

S3 method for class 'rvar'

```
order_draws(x, ...)
```

Arguments

`x` (draws) A draws object or another R object for which the method is defined.
`...` Arguments passed to individual methods (if applicable).

Value

A draws object of the same class as `x`.

See Also

[repair_draws\(\)](#)

Examples

```
x <- as_draws_array(example_draws())
dimnames(x[10:5, 4:3, ])
dimnames(order_draws(x[10:5, 4:3, ]))
```

print.draws_array *Print draws_array objects*

Description

Pretty printing for [draws_array](#) objects.

Usage

```
## S3 method for class 'draws_array'
print(
  x,
  digits = 2,
  max_iterations = getOption("posterior.max_iterations", 5),
  max_chains = getOption("posterior.max_chains", 8),
  max_variables = getOption("posterior.max_variables", 4),
  reserved = FALSE,
  ...
)
```

Arguments

`x` (draws) A draws object or another R object for which the method is defined.
`digits` (nonnegative integer) The minimum number of significant digits to print.
`max_iterations` (positive integer) The maximum number of iterations to print. Can be controlled globally via the "posterior.max_iterations" [option](#).
`max_chains` (positive integer) The maximum number of chains to print. Can be controlled globally via the "posterior.max_chains" [option](#).

max_variables	(positive integer) The maximum number of variables to print. Can be controlled globally via the "posterior.max_variables" option .
reserved	(logical) Should reserved variables be included in the output? Defaults to FALSE. See reserved_variables for an overview of currently reserved variable names.
...	Further arguments passed to the underlying <code>print()</code> methods.

Value

A draws object of the same class as x.

Examples

```
x <- as_draws_array(example_draws())
print(x)
```

print.draws_df	<i>Print draws_df objects</i>
----------------	-------------------------------

Description

Pretty printing for [draws_df](#) objects.

Usage

```
## S3 method for class 'draws_df'
print(
  x,
  digits = 2,
  max_draws = getOption("posterior.max_draws", 10),
  max_variables = getOption("posterior.max_variables", 8),
  reserved = FALSE,
  ...
)
```

Arguments

x	(draws) A draws object or another R object for which the method is defined.
digits	(nonnegative integer) The minimum number of significant digits to print.
max_draws	(positive integer) The maximum number of draws to print. Can be controlled globally via the "posterior.max_draws" option .
max_variables	(positive integer) The maximum number of variables to print. Can be controlled globally via the "posterior.max_variables" option .
reserved	(logical) Should reserved variables be included in the output? Defaults to FALSE. See reserved_variables for an overview of currently reserved variable names.
...	Further arguments passed to the underlying <code>print()</code> methods.

Value

A draws object of the same class as `x`.

Examples

```
x <- as_draws_df(example_draws())
print(x)
```

```
print.draws_list      Print draws_list objects
```

Description

Pretty printing for `draws_list` objects.

Usage

```
## S3 method for class 'draws_list'
print(
  x,
  digits = 2,
  max_iterations = getOption("posterior.max_iterations", 10),
  max_chains = getOption("posterior.max_chains", 2),
  max_variables = getOption("posterior.max_variables", 4),
  reserved = FALSE,
  ...
)
```

Arguments

<code>x</code>	(draws) A draws object or another R object for which the method is defined.
<code>digits</code>	(nonnegative integer) The minimum number of significant digits to print.
<code>max_iterations</code>	(positive integer) The maximum number of iterations to print. Can be controlled globally via the "posterior.max_iterations" option .
<code>max_chains</code>	(positive integer) The maximum number of chains to print. Can be controlled globally via the "posterior.max_chains" option .
<code>max_variables</code>	(positive integer) The maximum number of variables to print. Can be controlled globally via the "posterior.max_variables" option .
<code>reserved</code>	(logical) Should reserved variables be included in the output? Defaults to FALSE. See reserved_variables for an overview of currently reserved variable names.
<code>...</code>	Further arguments passed to the underlying <code>print()</code> methods.

Value

A draws object of the same class as `x`.

Examples

```
x <- as_draws_list(example_draws())
print(x)
```

```
print.draws_matrix      Print draws_matrix objects
```

Description

Pretty printing for `draws_matrix` objects.

Usage

```
## S3 method for class 'draws_matrix'
print(
  x,
  digits = 2,
  max_draws = getOption("posterior.max_draws", 10),
  max_variables = getOption("posterior.max_variables", 8),
  reserved = FALSE,
  ...
)
```

Arguments

<code>x</code>	(draws) A draws object or another R object for which the method is defined.
<code>digits</code>	(nonnegative integer) The minimum number of significant digits to print.
<code>max_draws</code>	(positive integer) The maximum number of draws to print. Can be controlled globally via the "posterior.max_draws" option .
<code>max_variables</code>	(positive integer) The maximum number of variables to print. Can be controlled globally via the "posterior.max_variables" option .
<code>reserved</code>	(logical) Should reserved variables be included in the output? Defaults to FALSE. See reserved_variables for an overview of currently reserved variable names.
<code>...</code>	Further arguments passed to the underlying <code>print()</code> methods.

Value

A draws object of the same class as `x`.

Examples

```
x <- as_draws_matrix(example_draws())
print(x)
```

```
print.draws_rvars      Print draws_rvars objects
```

Description

Pretty printing for `draws_rvars` objects.

Usage

```
## S3 method for class 'draws_rvars'
print(
  x,
  digits = 2,
  max_variables = getOption("posterior.max_variables", 8),
  summary = getOption("posterior.rvar_summary", "mean_sd"),
  reserved = FALSE,
  ...
)
```

Arguments

<code>x</code>	(draws) A draws object or another R object for which the method is defined.
<code>digits</code>	(nonnegative integer) The minimum number of significant digits to print.
<code>max_variables</code>	(positive integer) The maximum number of variables to print. Can be controlled globally via the <code>"posterior.max_variables"</code> option .
<code>summary</code>	(string) The style of summary to display: <code>"mean_sd"</code> displays $\text{mean} \pm \text{sd}$, <code>"median_mad"</code> displays $\text{median} \pm \text{mad}$. If NULL, <code>getOption("posterior.rvar_summary")</code> is used (default <code>"mean_sd"</code>).
<code>reserved</code>	(logical) Should reserved variables be included in the output? Defaults to FALSE. See reserved_variables for an overview of currently reserved variable names.
<code>...</code>	Further arguments passed to the underlying <code>print()</code> methods.

Value

A draws object of the same class as `x`.

Examples

```
x <- as_draws_rvars(example_draws())
print(x)
```

print.rvar	<i>Print or format a random variable</i>
------------	--

Description

Printing and formatting methods for [rvars](#).

Usage

```
## S3 method for class 'rvar'
print(x, ..., summary = NULL, digits = 2, color = TRUE)

## S3 method for class 'rvar'
format(x, ..., summary = NULL, digits = 2, color = FALSE)

## S3 method for class 'rvar'
str(
  object,
  ...,
  summary = NULL,
  vec.len = NULL,
  indent.str = paste(rep.int(" ", max(0, nest.lev + 1)), collapse = ".."),
  nest.lev = 0,
  give.attr = TRUE
)
```

Arguments

x, object	(rvar) The rvar to print.
...	Further arguments passed to the underlying print() methods.
summary	(string) The style of summary to display: "mean_sd" displays mean±sd, "median_mad" displays median±mad. If NULL, <code>getOption("posterior.rvar.summary")</code> is used (default "mean_sd").
digits	(nonnegative integer) The minimum number of significant digits to print.
color	(logical) Whether or not to use color when formatting the output. If TRUE, the pillar::style_num() functions may be used to produce strings containing control sequences to produce colored output on the terminal.
vec.len	(nonnegative integer) How many 'first few' elements are displayed of each vector. If NULL, defaults to <code>getOption("str")\$vec.len</code> , which defaults to 4.
indent.str	(string) The indentation string to use.
nest.lev	(nonnegative integer) Current nesting level in the recursive calls to <code>str()</code> .
give.attr	(logical) If TRUE (default), show attributes as sub structures.

Details

`print()` and `str()` print out `rvar` objects by summarizing each element in the random variable with either its $\text{mean} \pm \text{sd}$ or $\text{median} \pm \text{mad}$, depending on the value of `summary`. Both functions use the `format()` implementation for `rvar` objects under the hood, which returns a character vector in the $\text{mean} \pm \text{sd}$ or $\text{median} \pm \text{mad}$ form.

Value

For `print()`, an invisible version of the input object.

For `str()`, nothing; i.e. `invisible(NULL)`.

For `format()`, a character vector of the same dimensions as `x` where each entry is of the form " $\text{mean} \pm \text{sd}$ " or " $\text{median} \pm \text{mad}$ ", depending on the value of `summary`.

Examples

```
set.seed(5678)
x = rbind(
  cbind(rvar(rnorm(1000, 1)), rvar(rnorm(1000, 2))),
  cbind(rvar(rnorm(1000, 3)), rvar(rnorm(1000, 4)))
)

print(x)
print(x, summary = "median_mad")

str(x)

format(x)
```

 quantile2

Compute Quantiles

Description

Compute quantiles of a sample and return them in a format consistent with other summary functions in the **posterior** package.

Usage

```
quantile2(x, probs = c(0.05, 0.95), na.rm = FALSE, ...)

## Default S3 method:
quantile2(x, probs = c(0.05, 0.95), na.rm = FALSE, names = TRUE, ...)

## S3 method for class 'rvar'
quantile2(x, probs = c(0.05, 0.95), na.rm = FALSE, names = TRUE, ...)
```

Arguments

x	(multiple options) One of: <ul style="list-style-type: none"> • A matrix of draws for a single variable (iterations x chains). See <code>extract_variable_matrix()</code>. • An <code>rvar</code>.
probs	(numeric vector) Probabilities in [0, 1].
na.rm	(logical) Should NA and NaN values be removed from x prior to computing quantiles? The default is FALSE.
...	Arguments passed to individual methods (if applicable) and then on to <code>stats::quantile()</code> .
names	(logical) Should the result have a names attribute? The default is TRUE, but use FALSE for improved speed if there are many values in probs.

Value

A numeric vector of length `length(probs)`. If `names = TRUE`, it has a `names` attribute with names like "q5", "q95", etc, based on the values of probs.

Examples

```
mu <- extract_variable_matrix(example_draws(), "mu")
quantile2(mu)
```

rdo

*Execute expressions of random variables***Description**

Execute (nearly) arbitrary R expressions that may include `rvars`, producing a new `rvar`.

Usage

```
rdo(expr, dim = NULL, ndraws = NULL)
```

Arguments

expr	(expression) A bare expression that can (optionally) contain <code>rvars</code> . The expression supports <code>quasiquote</code> .
dim	(integer vector) One or more integers giving the maximal indices in each dimension to override the dimensions of the <code>rvar</code> to be created (see <code>dim()</code>). If NULL (the default), <code>dim</code> is determined by the input. NOTE: This argument controls the dimensions of the <code>rvar</code> , not the underlying array, so you cannot change the number of draws using this argument.
ndraws	(positive integer) The number of draws used to construct new random variables if no <code>rvars</code> are supplied in <code>expr</code> . If NULL, <code>getOption("posterior.rvar.ndraws")</code> is used (default 4000). If <code>expr</code> contains <code>rvars</code> , the number of draws in the provided <code>rvars</code> is used instead of the value of this argument.

Details

This function evaluates `expr` possibly multiple times, once for each draw of the `rvars` it contains, then returns a new `rvar` representing the output of those expressions. To identify `rvars`, `rdo()` searches the calling environment for any variables named in `expr` for which `is_rvar()` evaluates to `TRUE`. If `expr` contains no `rvars`, then it will be executed `ndraws` times and an `rvar` with that many draws returned.

`rdo()` is not necessarily *fast* (in fact in some cases it may be very slow), but it has the advantage of allowing a nearly arbitrary R expression to be executed against `rvars` simply by wrapping it with `rdo(...)`. This makes it especially useful as a prototyping tool. If you create code with `rdo()` and it is unacceptably slow for your application, consider rewriting it using math operations directly on `rvars` (which should be fast), using `rvar_rng()`, and/or using operations directly on the arrays that back the `rvars` (via `draws_of()`).

Value

An `rvar`.

See Also

Other rfun: `rfun()`, `rvar_rng()`

Examples

```
mu <- rdo(rnorm(10, mean = 1:10, sd = 1))
sigma <- rdo(rgamma(1, shape = 1, rate = 1))
x <- rdo(rnorm(10, mu, sigma))
x
```

rename_variables

Rename variables in draws objects

Description

Rename variables in a `draws` object.

Usage

```
rename_variables(.x, ...)

## S3 method for class 'draws'
rename_variables(.x, ...)
```


Arguments

`.x` (draws) A [draws](#) object.

`...` One or more expressions, separated by commas, indicating the variables to rename. The variable names can be unquoted (`new_name = old_name`) or quoted (`"new_name" = "old_name"`). For non-scalar variables, all elements can be renamed together (`"new_name" = "old_name"`) or they can be renamed individually (`"new_name[1]" = "old_name[1]"`).

Value

Returns a [draws](#) object of the same format as `.x`, with variables renamed according to the expressions provided in `...`

See Also

[variables](#), [mutate_variables](#)

Examples

```
x <- as_draws_df(example_draws())
variables(x)

x <- rename_variables(x, mean = mu, sigma = tau)
variables(x)

x <- rename_variables(x, b = `theta[1]`) # or b = "theta[1]"
variables(x)

# rename all elements of 'theta' at once
x <- rename_variables(x, alpha = theta)
variables(x)
```

 repair_draws

Repair indices of draws objects

Description

Repair indices of draws objects so that iterations, chains, and draws are continuously and consistently numbered.

Usage

```
repair_draws(x, order = TRUE, ...)

## S3 method for class 'draws_matrix'
repair_draws(x, order = TRUE, ...)
```

```
## S3 method for class 'draws_array'
repair_draws(x, order = TRUE, ...)

## S3 method for class 'draws_df'
repair_draws(x, order = TRUE, ...)

## S3 method for class 'draws_list'
repair_draws(x, order = TRUE, ...)

## S3 method for class 'draws_rvars'
repair_draws(x, order = TRUE, ...)

## S3 method for class 'rvar'
repair_draws(x, order = TRUE, ...)
```

Arguments

x	(draws) A draws object or another R object for which the method is defined.
order	(logical) Should draws be ordered (via order_draws()) before repairing indices? Defaults to TRUE.
...	Arguments passed to individual methods (if applicable).

Value

A draws object of the same class as x.

See Also

[order_draws\(\)](#)

Examples

```
x <- as_draws_array(example_draws())
(x <- x[10:5, 3:4, ])
repair_draws(x)
```

resample_draws

Resample draws objects

Description

Resample [draws](#) objects according to provided weights, for example weights obtained through importance sampling.

Usage

```
resample_draws(x, ...)

## S3 method for class 'draws'
resample_draws(x, weights = NULL, method = "stratified", ndraws = NULL, ...)
```

Arguments

x	(draws) A draws object or another R object for which the method is defined.
...	Arguments passed to individual methods (if applicable).
weights	(numeric vector) A vector of positive weights of length <code>ndraws(x)</code> . The weights will be internally normalized. If <code>weights</code> is not specified, an attempt will be made to extract any weights already stored in the draws object (via weight_draws()). How exactly the weights influence the resampling depends on the method argument.
method	(string) The resampling method to use: <ul style="list-style-type: none"> • "simple": simple random resampling with replacement • "simple_no_replace": simple random resampling without replacement • "stratified": stratified resampling with replacement • "deterministic": deterministic resampling with replacement <p>Currently, "stratified" is the default as it has comparably low variance and bias with respect to ideal resampling. The latter would sample perfectly proportional to the weights, but this is not possible in practice due to the finite number of draws available. For more details about resampling methods, see Kitagawa (1996).</p>
ndraws	(positive integer) The number of draws to be returned. By default <code>ndraws</code> is set internally to the total number of draws in <code>x</code> if sensible.

Details

Upon usage of `resample_draws()`, chains will automatically be merged due to subsetting of individual draws (see [subset_draws](#) for details). Also, weights stored in the draws object will be removed in the process, as resampling invalidates existing weights.

Value

A draws object of the same class as `x`.

References

Kitagawa, G., Monte Carlo Filter and Smoother for Non-Gaussian Nonlinear ' State Space Models, *Journal of Computational and Graphical Statistics*, 5(1):1-25, 1996.

See Also

[resample_draws\(\)](#)

Examples

```
x <- as_draws_df(example_draws())

# random weights for justr for demonstration
w <- runif(ndraws(x), 0, 10)

# use default stratified sampling
x_rs <- resample_draws(x, weights = w)
summarise_draws(x_rs, default_summary_measures())

# use simple random sampling
x_rs <- resample_draws(x, weights = w, method = "simple")
summarise_draws(x_rs, default_summary_measures())
```

reserved_variables	<i>Reserved variables</i>
--------------------	---------------------------

Description

Get names of reserved variables from objects in the **posterior** package.

Usage

```
reserved_variables(x, ...)
```

Default S3 method:
reserved_variables(x, ...)

S3 method for class 'draws_matrix'
reserved_variables(x, ...)

S3 method for class 'draws_array'
reserved_variables(x, ...)

S3 method for class 'draws_df'
reserved_variables(x, ...)

S3 method for class 'draws_list'
reserved_variables(x, ...)

S3 method for class 'draws_rvars'
reserved_variables(x, ...)

Arguments

x (draws) A draws object or another R object for which the method is defined.

... Arguments passed to individual methods (if applicable).

Details

`reserved_variables()` returns the names of reserved variables in use by an object.

The following variables names are currently reserved for special use cases in all `draws` formats:

- `.log_weight`: Log weights per draw (see `weight_draws`).

Further, specific for the `draws_df` format, there are three additional reserved variables:

- `.chain`: Chain index per draw
- `.iteration`: Iteration index within each chain
- `.draw`: Draw index across chains

More reserved variables may be added in the future.

Value

A character vector of reserved variables used in `x`.

Examples

```
x <- example_draws()
reserved_variables(x)

# if we add weights, the `.log_weight` reserved variable is used
x <- weight_draws(x, rexp(ndraws(x)))
reserved_variables(x)
```

rfun

Create functions of random variables

Description

Function that create functions that can accept and/or produce `rvars`.

Usage

```
rfun(.f, rvar_args = NULL, ndraws = NULL)
```

Arguments

- `.f` (multiple options) A function to turn into a function that accepts and/or produces random variables:
- A function
 - A one-sided formula that can be parsed by `rlang::as_function()`

rvar_args	(character vector) The names of the arguments of <code>.f</code> that should be allowed to accept <code>rvars</code> as arguments. If <code>NULL</code> (the default), all arguments to <code>.f</code> are turned into arguments that accept <code>rvars</code> .
ndraws	(positive integer). The number of draws used to construct new random variables if no <code>rvars</code> are supplied as arguments to the returned function. If <code>NULL</code> , <code>getOption("posterior.rvar.ndraws")</code> is used (default 4000). If any arguments to the returned function contain <code>rvars</code> , the number of draws in the provided <code>rvars</code> is used instead of the value of this argument.

Details

This function wraps an existing function (`.f`) such that it returns `rvars` containing whatever type of data `.f` would normally return.

The returned function, when called, executes `.f` possibly multiple times, once for each draw of the `rvars` passed to it, then returns a new `rvar` representing the output of those function evaluations. If the arguments contain no `rvars`, then `.f` will be executed `ndraws` times and an `rvar` with that many draws returned.

Functions created by `rfun()` are not necessarily *fast* (in fact in some cases they may be very slow), but they have the advantage of allowing a nearly arbitrary R functions to be executed against `rvars` simply by wrapping them with `rfun()`. This makes it especially useful as a prototyping tool. If you create code with `rfun()` and it is unacceptably slow for your application, consider rewriting it using math operations directly on `rvars` (which should be fast), using `rvar_rng()`, and/or using operations directly on the arrays that back the `rvars` (via `draws_of()`).

Value

A function with the same argument specification as `.f`, but which can accept and return `rvars`.

See Also

Other `rfun`: `rdo()`, `rvar_rng()`

Examples

```
rvar_norm <- rfun(rnorm)
rvar_gamma <- rfun(rgamma)

mu <- rvar_norm(10, mean = 1:10, sd = 1)
sigma <- rvar_gamma(1, shape = 1, rate = 1)
x <- rvar_norm(10, mu, sigma)
x
```

rhat *Rhat convergence diagnostic*

Description

Compute the Rhat convergence diagnostic for a single variable as the maximum of rank normalized split-Rhat and rank normalized folded-split-Rhat as proposed in Vehtari et al. (2019).

Usage

```
rhat(x, ...)  
  
## Default S3 method:  
rhat(x, ...)  
  
## S3 method for class 'rvar'  
rhat(x, ...)
```

Arguments

`x` (multiple options) One of:

- A matrix of draws for a single variable (iterations x chains). See [extract_variable_matrix\(\)](#).
- An [rvar](#).

`...` Arguments passed to individual methods (if applicable).

Value

If the input is an array, returns a single numeric value. If any of the draws is non-finite, that is, NA, NaN, Inf, or -Inf, the returned output will be (numeric) NA. Also, if all draws within any of the chains of a variable are the same (constant), the returned output will be (numeric) NA as well. The reason for the latter is that, for constant draws, we cannot distinguish between variables that are supposed to be constant (e.g., a diagonal element of a correlation matrix is always 1) or variables that just happened to be constant because of a failure of convergence or other problems in the sampling process.

If the input is an [rvar](#), returns an array of the same dimensions as the [rvar](#), where each element is equal to the value that would be returned by passing the draws array for that element of the [rvar](#) to this function.

References

Aki Vehtari, Andrew Gelman, Daniel Simpson, Bob Carpenter, and Paul-Christian Bürkner (2019). Rank-normalization, folding, and localization: An improved R-hat for assessing convergence of MCMC. *arXiv preprint arXiv:1903.08008*.

See Also

Other diagnostics: [ess_basic\(\)](#), [ess_bulk\(\)](#), [ess_quantile\(\)](#), [ess_sd\(\)](#), [ess_tail\(\)](#), [mcse_mean\(\)](#), [mcse_quantile\(\)](#), [mcse_sd\(\)](#), [rhat_basic\(\)](#), [rstar\(\)](#)

Examples

```
mu <- extract_variable_matrix(example_draws(), "mu")
rhat(mu)
```

```
d <- as_draws_rvars(example_draws("multi_normal"))
rhat(d$Sigma)
```

rhat_basic

Basic version of the Rhat convergence diagnostic

Description

Compute the basic Rhat convergence diagnostic for a single variable as described in Gelman et al. (2013). For practical applications, we strongly recommend the improved Rhat convergence diagnostic implemented in [rhat\(\)](#).

Usage

```
rhat_basic(x, ...)

## Default S3 method:
rhat_basic(x, split = TRUE, ...)

## S3 method for class 'rvar'
rhat_basic(x, split = TRUE, ...)
```

Arguments

x	(multiple options) One of: <ul style="list-style-type: none"> • A matrix of draws for a single variable (iterations x chains). See extract_variable_matrix(). • An rvar.
...	Arguments passed to individual methods (if applicable).
split	(logical) Should the estimate be computed on split chains? The default is TRUE.

Value

If the input is an array, returns a single numeric value. If any of the draws is non-finite, that is, NA, NaN, Inf, or -Inf, the returned output will be (numeric) NA. Also, if all draws within any of the chains of a variable are the same (constant), the returned output will be (numeric) NA as well. The reason for the latter is that, for constant draws, we cannot distinguish between variables that are

supposed to be constant (e.g., a diagonal element of a correlation matrix is always 1) or variables that just happened to be constant because of a failure of convergence or other problems in the sampling process.

If the input is an `rvar`, returns an array of the same dimensions as the `rvar`, where each element is equal to the value that would be returned by passing the draws array for that element of the `rvar` to this function.

References

Andrew Gelman, John B. Carlin, Hal S. Stern, David B. Dunson, Aki Vehtari and Donald B. Rubin (2013). Bayesian Data Analysis, Third Edition. Chapman and Hall/CRC.

See Also

Other diagnostics: `ess_basic()`, `ess_bulk()`, `ess_quantile()`, `ess_sd()`, `ess_tail()`, `mcse_mean()`, `mcse_quantile()`, `mcse_sd()`, `rhat()`, `rstar()`

Examples

```
mu <- extract_variable_matrix(example_draws(), "mu")
rhat_basic(mu)

d <- as_draws_rvars(example_draws("multi_normal"))
rhat_basic(d$Sigma)
```

rstar

Calculate R convergence diagnostic*

Description

The `rstar()` function generates a measure of convergence for MCMC draws based on whether it is possible to determine the Markov chain that generated a draw with probability greater than chance. To do so, it fits a machine learning classifier to a training set of MCMC draws and evaluates its predictive accuracy on a testing set: giving the ratio of accuracy to predicting a chain uniformly at random.

Usage

```
rstar(
  x,
  split = TRUE,
  uncertainty = FALSE,
  method = "rf",
  hyperparameters = NULL,
  training_proportion = 0.7,
  nsimulations = 1000,
  ...
)
```

Arguments

x	(draws) A <code>draws_df</code> object or one coercible to a <code>draws_df</code> object.
split	(logical) Should the estimate be computed on split chains? The default is <code>TRUE</code> .
uncertainty	(logical). Indicates whether to provide a vector of R^* values representing uncertainty in the calculated value (if <code>TRUE</code>) or a single value (if <code>FALSE</code>). The default is <code>TRUE</code> .
method	(string) The machine learning classifier to use (must be available in the <code>caret</code> package). The default is <code>"rf"</code> , which calls the random forest classifier.
hyperparameters	(named list) Hyperparameter settings passed to the classifier. The default for the random forest classifier (<code>method = "rf"</code>) is <code>list(mtry = floor(sqrt(nvariables(x))))</code> . The default for the gradient-based model (<code>method = "gbm"</code>) is <code>list(interaction.depth = 3, n.trees = 50, shrinkage = 0.1, n.minobsinnode = 10)</code> .
training_proportion	(positive real) The proportion (in $(0,1)$) of iterations in used to train the classifier. The default is <code>0.7</code> .
nsimulations	(positive integer) The number of R^* values in the returned vector if uncertainty is <code>TRUE</code> . The default is <code>1000</code> .
...	Other arguments passed to <code>caret::train()</code> .

Details

The `rstar()` function provides a measure of MCMC convergence based on whether it is possible to determine the chain that generated a particular draw with a probability greater than chance. To do so, it fits a machine learning classifier to a subset of the original MCMC draws (the training set) and evaluates its predictive accuracy on the remaining draws (the testing set). If predictive accuracy exceeds chance (i.e. predicting the chain that generated a draw uniformly at random), the diagnostic measure R^* will be above 1, indicating that convergence has yet to occur. This statistic is recently developed, and it is currently unclear what is a reasonable threshold for diagnosing convergence.

The statistic, R^* , is stochastic, meaning that each time the test is run, unless the random seed is fixed, it will generally produce a different result. To minimize the implications of this stochasticity, it is recommended to repeatedly run this function to calculate a distribution of R^* ; alternatively, an approximation to this distribution can be obtained by setting `uncertainty = TRUE`, although this approximation of uncertainty will generally have a lower mean.

By default, a random forest classifier is used (`method = "rf"`), which tends to perform best for target distributions of around 4 dimensions and above. For lower dimensional targets, gradient boosted models (called via `method = "gbm"`) tend to have a higher classification accuracy. On a given MCMC sample, it is recommended to try both of these classifiers.

Value

A numeric vector of length 1 (by default) or length `nsimulations` (if `uncertainty = TRUE`).

References

Ben Lambert, Aki Vehtari (2020) R^* : A robust MCMC convergence diagnostic with uncertainty using gradient-boosted machines. *arXiv preprint arXiv:2003.07900*.

See Also

Other diagnostics: [ess_basic\(\)](#), [ess_bulk\(\)](#), [ess_quantile\(\)](#), [ess_sd\(\)](#), [ess_tail\(\)](#), [mcse_mean\(\)](#), [mcse_quantile\(\)](#), [mcse_sd\(\)](#), [rhat_basic\(\)](#), [rhat\(\)](#)

Examples

```
if (require("caret", quietly = TRUE)) {
  x <- example_draws("eight_schools")
  print(rstar(x))
  print(rstar(x, split = FALSE))
  print(rstar(x, method = "gbm"))
  # can pass additional arguments to methods
  print(rstar(x, method = "gbm", verbose = FALSE))

  # with uncertainty, returns a vector of R* values
  hist(rstar(x, uncertainty = TRUE))
  hist(rstar(x, uncertainty = TRUE, nsimulations = 100))

  # can use other classification methods in caret library
  print(rstar(x, method = "knn"))
}
```

rvar

Random variables of arbitrary dimension

Description

Random variables backed by arrays of arbitrary dimension

Usage

```
rvar(
  x = double(),
  dim = NULL,
  dimnames = NULL,
  nchains = 1L,
  with_chains = FALSE
)
```

Arguments

x (multiple options) The object to convert to an rvar:

- A vector of draws from a distribution.

- An array where the first dimension represents draws from a distribution. The resulting `rvar` will have dimension `dim(x)[-1]`; that is, everything except the first dimension is used for the shape of the variable, and the first dimension is used to index draws from the distribution (see **Examples**). Optionally, if `with_chains == TRUE`, the first dimension indexes the iteration and the second dimension indexes the chain (see `with_chains`).

<code>dim</code>	(integer vector) One or more integers giving the maximal indices in each dimension to override the dimensions of the <code>rvar</code> to be created (see <code>dim()</code>). If <code>NULL</code> (the default), <code>dim</code> is determined by the input. NOTE: This argument controls the dimensions of the <code>rvar</code> , not the underlying array, so you cannot change the number of draws using this argument.
<code>dimnames</code>	(list) Character vectors giving the names in each dimension to override the names of the dimensions of the <code>rvar</code> to be created (see <code>dimnames()</code>). If <code>NULL</code> (the default), this is determined by the input. NOTE: This argument controls the names of the dimensions of the <code>rvar</code> , not the underlying array.
<code>nchains</code>	(positive integer) The number of chains. The default is 1.
<code>with_chains</code>	(logical) Does <code>x</code> include a dimension for chains? If <code>FALSE</code> (the default), chains are not included, the first dimension of the input array should index draws, and the <code>nchains</code> argument can be used to determine the number of chains. If <code>TRUE</code> , the <code>nchains</code> argument is ignored and the second dimension of <code>x</code> is used to index chains. Internally, the array will be converted to a format without the chain index.

Details

The "rvar" class internally represents random variables as arrays of arbitrary dimension, where the first dimension is used to index draws from the distribution. Most mathematical operators and functions are supported, including efficient matrix multiplication and vector and array-style indexing. The intent is that an `rvar` works as closely as possible to how a base vector/matrix/array does, with a few differences:

- The default behavior when subsetting is not to drop extra dimensions (i.e. the default drop argument for `[]` is `FALSE`, not `TRUE`).
- Rather than base R-style recycling, `rvars` use a limited form of broadcasting: if an operation is being performed on two vectors with different size of the same dimension, the smaller vector will be recycled up to the size of the larger one along that dimension so long as it has size 1.

For functions that expect base numeric arrays and for which `rvars` cannot be used directly as arguments, you can use `rfun()` or `rdo()` to translate your code into code that executes across draws from one or more random variables and returns a random variable as output. Typically `rdo()` offers the most straightforward translation.

As `rfun()` and `rdo()` incur some performance cost, you can also operate directly on the underlying array using the `draws_of()` function. To re-use existing random number generator functions to efficiently create `rvars`, use `rvar_rng()`.

Value

An object of class "rvar" representing a random variable.

See Also

`as_rvar()` to convert objects to rvars. See `rdo()`, `rfunc()`, and `rvar_rng()` for higher-level interfaces for creating rvars.

Examples

```
set.seed(1234)

# To create a "scalar" `rvar`, pass a one-dimensional array or a vector
# whose length (here `4000`) is the desired number of draws:
x <- rvar(rnorm(4000, mean = 1, sd = 1))
x

# Create random vectors by adding an additional dimension:
n <- 4 # length of output vector
x <- rvar(array(rnorm(4000 * n, mean = rep(1:n, each = 4000), sd = 1), dim = c(4000, n)))
x

# Create a random matrix:
rows <- 4
cols <- 3
x <- rvar(array(rnorm(4000 * rows * cols, mean = 1, sd = 1), dim = c(4000, rows, cols)))
x

# If the input sample comes from multiple chains, we can indicate that using the
# nchains argument (here, 1000 draws each from 4 chains):
x <- rvar(rnorm(4000, mean = 1, sd = 1), nchains = 4)
x

# Or if the input sample has chain information as its second dimension, we can
# use with_chains to create the rvar
x <- rvar(array(rnorm(4000, mean = 1, sd = 1), dim = c(1000, 4)), with_chains = TRUE)
x
```

rvar-dist

Density, CDF, and quantile functions of random variables

Description

The probability density function (`density()`), cumulative distribution function (`cdf()`), and quantile function / inverse CDF (`quantile()`) of an `rvar`.

Usage

```
## S3 method for class 'rvar'
density(x, at, ...)
```

```
## S3 method for class 'rvar'
cdf(x, q, ...)
```

```
## S3 method for class 'rvar'
quantile(x, probs, ...)
```

Arguments

x	(rvar) An <code>rvar</code> object.
...	Additional arguments passed onto underlying methods: <ul style="list-style-type: none"> • For <code>density()</code>, these are passed to <code>stats::density()</code>. • For <code>cdf()</code>, these are ignored. • For <code>quantile()</code>, these are passed to <code>stats::quantile()</code>.
q, at	(numeric vector) One or more quantiles.
probs	(numeric vector) One or more probabilities in [0,1].

Value

If x is a scalar `rvar`, returns a vector of the same length as the input (q, at, or probs) containing values from the corresponding function of the given `rvar`.

If x has length greater than 1, returns an array with dimensions `c(length(y), dim(x))` where y is q, at, or probs, where each `result[i, ...]` is the value of the corresponding function, `f(y[i])`, for the corresponding cell in the input array, `x[...]`.

Examples

```
set.seed(1234)
x = rvar(rnorm(100))

density(x, seq(-2, 2, length.out = 10))
cdf(x, seq(-2, 2, length.out = 10))
quantile(x, ppoints(10))

x2 = c(rvar(rnorm(100, mean = -0.5)), rvar(rnorm(100, mean = 0.5)))
density(x2, seq(-2, 2, length.out = 10))
cdf(x2, seq(-2, 2, length.out = 10))
quantile(x2, ppoints(10))
```

Description

Matrix multiplication of random variables.

Usage

```
x %**% y
```

Arguments

x (multiple options) The object to be postmultiplied by *y*:

- An `rvar`
- A `numeric` vector or matrix
- A `logical` vector or matrix

If a vector is used, it is treated as a *row* vector.

y (multiple options) The object to be premultiplied by *x*:

- An `rvar`
- A `numeric` vector or matrix
- A `logical` vector or matrix

If a vector is used, it is treated as a *column* vector.

Details

If *x* or *y* are vectors, they are converted into matrices prior to multiplication, with *x* converted to a row vector and *y* to a column vector. Numerics and logicals can be multiplied by `rvars` and are broadcasted across all draws of the `rvar` argument. Tensor multiplication is used to efficiently multiply matrices across draws, so if either *x* or *y* is an `rvar`, `x %**% y` will be much faster than `rdo(x %**% y)`.

Because `rvar` is an S3 class and S3 classes cannot properly override `%**%`, `rvars` use `%**%o` for matrix multiplication.

Value

An `rvar` representing the matrix product of *x* and *y*.

Examples

```
# d has mu (mean vector of length 3) and Sigma (3x3 covariance matrix)
d <- as_draws_rvars(example_draws("multi_normal"))
d$Sigma

# trivial example: multiplication by a non-random matrix
d$Sigma %**% diag(1:3)

# Decompose Sigma into R s.t. R'R = Sigma ...
R <- chol(d$Sigma)
# ... and recreate Sigma using matrix multiplication
t(R) %**% R
```

rvar-summaries-over-draws

Summaries of random variables within array elements, over draws

Description

Compute summaries within elements of an `rvar` and over draws of each element, producing an array of the same shape as the input random variable (except in the case of `range()`, see **Details**).

Usage

```
E(x, ...)  
  
## S3 method for class 'rvar'  
mean(x, ...)  
  
Pr(x, ...)  
  
## Default S3 method:  
Pr(x, ...)  
  
## S3 method for class 'logical'  
Pr(x, ...)  
  
## S3 method for class 'rvar'  
Pr(x, ...)  
  
## S3 method for class 'rvar'  
median(x, ...)  
  
## S3 method for class 'rvar'  
min(x, ...)  
  
## S3 method for class 'rvar'  
max(x, ...)  
  
## S3 method for class 'rvar'  
sum(x, ...)  
  
## S3 method for class 'rvar'  
prod(x, ...)  
  
## S3 method for class 'rvar'  
all(x, ...)  
  
## S3 method for class 'rvar'  
any(x, ...)
```



```
## S3 method for class 'rvar'  
Summary(...)  
  
## S3 method for class 'rvar'  
variance(x, ...)  
  
var(x, ...)  
  
## Default S3 method:  
var(x, ...)  
  
## S3 method for class 'rvar'  
var(x, ...)  
  
sd(x, ...)  
  
## Default S3 method:  
sd(x, ...)  
  
## S3 method for class 'rvar'  
sd(x, ...)  
  
mad(x, ...)  
  
## Default S3 method:  
mad(x, ...)  
  
## S3 method for class 'rvar'  
mad(x, ...)  
  
## S3 method for class 'rvar'  
range(x, ...)  
  
## S3 method for class 'rvar'  
is.finite(x)  
  
## S3 method for class 'rvar'  
is.infinite(x)  
  
## S3 method for class 'rvar'  
is.nan(x)  
  
## S3 method for class 'rvar'  
is.na(x)
```

Arguments

x (rvar) An [rvar](#).

... Further arguments passed to underlying functions (e.g., `base::mean()` or `base::median()`), such as `na.rm`.

Details

Summaries include expectations (`E()` or `mean()`), probabilities (`Pr()`), medians (`median()`), spread (`var()`, `variance()`, `sd()`, `mad()`), sums and products (`sum()`, `prod()`), extrema and ranges (`min()`, `max()`, `range()`), logical summaries (`all()`, `any()`), and special value predicates (`is.finite()`, `is.infinite()`, `is.nan()`, `is.na()`).

Unless otherwise stated, these functions return a numeric array with the same shape (same dimensions) as the input `rvar`, `x`.

`range(x)` returns an array with dimensions `c(2, dim(x))`, where the last dimension contains the minimum and maximum values.

`is.infinite(x)`, `is.nan(x)`, and `is.na(x)` return logical arrays, where each element is TRUE if **any** draws in its corresponding element in `x` match the predicate. Each elements in the result of `is.finite(x)` is TRUE if **all** draws in the corresponding element in `x` are finite.

Both `E()`, `mean()`, and `Pr()` return the means of each element in the input. `Pr()` additionally checks that the provided `rvar` is a logical variable (hence, taking its expectation results in a probability).

For consistency, `E()` and `Pr()` are also defined for base arrays so that they can be used as summary functions in `summarise_draws()`.

Value

A numeric or logical vector with the same dimensions as the given random variable, where each entry in the vector is the mean, median, or variance of the corresponding entry in `x`.

See Also

[rvar-summaries-within-draws](#) for summary functions within draws. [rvar-dist](#) for density, CDF, and quantile functions of random variables.

Other `rvar-summaries`: [rvar-summaries-within-draws](#), [rvar_is_finite\(\)](#)

Examples

```
set.seed(5678)
x = rvar_rng(rnorm, 4, mean = 1:4, sd = 2)

# These should all be ~ c(1, 2, 3, 4)
E(x)
mean(x)
median(x)

# This ...
Pr(x < 1.5)
# ... should be about the same as this:
pnorm(1.5, mean = 1:4, sd = 2)
```

 rvar-summaries-within-draws

Summaries of random variables over array elements, within draws

Description

Compute summaries of random variables over array elements and within draws, producing a new random variable of length 1 (except in the case of `rvar_range()`, see **Details**).

Usage

```
rvar_mean(..., na.rm = FALSE)
rvar_median(..., na.rm = FALSE)
rvar_sum(..., na.rm = FALSE)
rvar_prod(..., na.rm = FALSE)
rvar_min(..., na.rm = FALSE)
rvar_max(..., na.rm = FALSE)
rvar_sd(..., na.rm = FALSE)
rvar_var(..., na.rm = FALSE)
rvar_mad(..., constant = 1.4826, na.rm = FALSE)
rvar_range(..., na.rm = FALSE)
rvar_quantile(..., probs, names = FALSE, na.rm = FALSE)
rvar_all(..., na.rm = FALSE)
rvar_any(..., na.rm = FALSE)
```

Arguments

<code>...</code>	(<code>rvar</code>) One or more <code>rvars</code> .
<code>na.rm</code>	(logical) Should NAs be removed from the input before summaries are computed? The default is FALSE.
<code>constant</code>	(scalar real) For <code>rvar_mad()</code> , a scale factor for computing the median absolute deviation. See the details of <code>stats::mad()</code> for the justification for the default value.
<code>probs</code>	(numeric vector) For <code>rvar_quantile()</code> , probabilities in [0, 1].
<code>names</code>	(logical) For <code>rvar_quantile()</code> , if TRUE, the result has a <code>names</code> attribute.

Details

These functions compute statistics within each draw of the random variable. For summaries over draws (such as expectations), see [rvar-summaries-over-draws](#).

Each function defined here corresponds to the base function of the same name without the `rvar_` prefix (e.g., `rvar_mean()` calls `mean()` under the hood, etc).

Value

An `rvar` of length 1 (for `range()`, length 2; for `quantile()`, length equal to `length(probs)`) with the same number of draws as the input `rvar(s)` containing the summary statistic computed within each draw of the input `rvar(s)`.

See Also

[rvar-summaries-over-draws](#) for summary functions across draws (e.g. expectations). [rvar-dist](#) for density, CDF, and quantile functions of random variables.

Other `rvar-summaries`: [rvar-summaries-over-draws](#), [rvar_is_finite\(\)](#)

Examples

```
set.seed(5678)
x = rvar_rng(rnorm, 4, mean = 1:4, sd = 2)

# These will give similar results to mean(1:4),
# median(1:4), sum(1:4), prod(1:4), etc
rvar_mean(x)
rvar_median(x)
rvar_sum(x)
rvar_prod(x)
rvar_range(x)
rvar_quantile(x, probs = c(0.25, 0.5, 0.75), names = TRUE)
```

rvar_apply

Random variable resulting from a function applied over margins of an array or random variable

Description

Returns an `rvar` obtained by applying a function to margins of an array or `rvar`. Acts like `apply()`, except that the function supplied (`.f`) should return an `rvar`, and the final result is always an `rvar`.

Usage

```
rvar_apply(.x, .margin, .f, ...)
```

Arguments

<code>.x</code>	An array or an <code>rvar</code> .
<code>.margin</code>	(multiple options) The subscripts which the function will be applied over: <ul style="list-style-type: none"> • An integer vector. E.g., for a matrix 1 indicates rows, 2 indicates columns, <code>c(1, 2)</code> indicates rows and columns. • A character vector of dimension names if <code>.x</code> has named dimensions.
<code>.f</code>	(function) The function to be applied. The function <code>.f</code> must return an <code>rvar</code> and the dimensions of the result of <code>.f</code> applied to each margin of <code>.x</code> must be able to be broadcasted to a common shape (otherwise the resulting <code>rvar</code> cannot be simplified). See Details .
<code>...</code>	Optional arguments passed to <code>.f</code> .

Details

This function acts much like `apply()`, except that the function passed to it (`.f`) must return `rvars`, and the result is simplified into an `rvar`. Unlike `apply()`, it also keeps the dimensions of the returned values along each margin, rather than simplifying each margin to a vector, and if the results of `.f` do not all have the same dimensions, it applies the `rvar` broadcasting rules to bind results together rather than using vector recycling.

If you wish to apply functions over `rvars` where the result is not intended to be simplified into an `rvar`, you can use the standard `apply()`, `lapply()`, `sapply()`, or `vapply()` functions.

Value

An `rvar`.

If the result of each call to `.f` returns an `rvar` of dimension `d` after being broadcast to a common shape, then `rvar_apply()` returns an `rvar` of dimension `c(d, dim(.x)[.margin])`. If the last dimension of the result would be 1, it is dropped (other dimensions equal to 1 are retained). If `d` is `0`, the result has length `0` but not necessarily the 'correct' dimension.

See Also

`as_rvar()` to convert objects to `rvars`. See `rdo()`, `rfunc()`, and `rvar_rng()` for higher-level interfaces for creating `rvars`.

Examples

```
set.seed(3456)
x <- rvar_rng(rnorm, 24, mean = 1:24)
dim(x) <- c(2,3,4)

# we can find the distributions of marginal means of the above array
# using rvar_mean along with rvar_apply
rvar_apply(x, 1, rvar_mean)
rvar_apply(x, 2:3, rvar_mean)
```

rvar_is_finite *Special value predicates for random variables*

Description

Compute special value predicates (checking for finite / infinite values, NaN, and NA) on all draws within a random variable, returning a random variable.

Usage

```
rvar_is_finite(x)
```

```
rvar_is_infinite(x)
```

```
rvar_is_nan(x)
```

```
rvar_is_na(x)
```

Arguments

x (rvar) An [rvar](#).

Details

These functions return a new [rvar](#) that is the result of applying `is.finite()`, `is.infinite()`, `is.nan()`, or `is.na()` to every draw in the input random variable.

Value

A logical [rvar](#) of the same length as the input.

See Also

[rvar-summaries-over-draws](#) for summary functions across draws, including implementations of `is.finite()`, `is.infinite()`, `is.nan()`, and `is.na()` for [rvars](#).

Other [rvar](#)-summaries: [rvar-summaries-over-draws](#), [rvar-summaries-within-draws](#)

Examples

```
x <- rvar(c(1, Inf, -Inf, NaN, NA))
x
```

```
rvar_is_finite(x)
rvar_is_infinite(x)
rvar_is_nan(x)
rvar_is_na(x)
```

rvar_rng

*Create random variables from existing random number generators***Description**

Specialized alternative to `rdo()` or `rfunc()` for creating `rvars` from existing random-number generator functions (such as `rnorm()`, `rbinom()`, etc).

Usage

```
rvar_rng(.f, n, ..., ndraws = NULL)
```

Arguments

<code>.f</code>	(function) A function (or string naming a function) representing a random-number generating function that follows the pattern of base random number generators (like <code>rnorm()</code> , <code>rbinom()</code> , etc). It must: <ul style="list-style-type: none"> • Have a first argument, <code>n</code>, giving the number of draws to take from the distribution • Have vectorized parameter arguments • Return a single vector of length <code>n</code>
<code>n</code>	(positive integer) The length of the output <code>rvar</code> vector (not the number of draws).
<code>...</code>	Arguments passed to <code>.f</code> . These arguments may include <code>rvars</code> , so long as they are vectors only (no multidimensional <code>rvars</code> are allowed).
<code>ndraws</code>	(positive integer) The number of draws used to construct the returned random variable if no <code>rvars</code> are supplied in <code>...</code> . If <code>NULL</code> , <code>getOption("posterior.rvar.ndraws")</code> is used (default 4000). If <code>...</code> contains <code>rvars</code> , the number of draws in the provided <code>rvars</code> is used instead of the value of this argument.

Details

This function unwraps the arrays underlying the input `rvars` in `...` and then passes them to `.f`, relying on the vectorization of `.f` to evaluate it across draws from the input `rvars`. This is why the arguments of `.f` **must** be vectorized. It asks for `n` times the number of draws in the input `rvars` (or `ndraws` if none are given) draws from the random number generator `.f`, then reshapes the output from `.f` into an `rvar` with length `n`.

`rvar_rng()` is a fast alternative to `rdo()` or `rfunc()`, but you **must** ensure that `.f` satisfies the preconditions described above for the result to be correct. Most base random number generators satisfy these conditions. It is advisable to test against `rdo()` or `rfunc()` (which should be correct, but slower) if you are uncertain.

Value

A single-dimensional `rvar` of length `n`.

See Also

Other rfun: [rdo\(\)](#), [rfun\(\)](#)

Examples

```
mu <- rvar_rng(rnorm, 10, mean = 1:10, sd = 1)
sigma <- rvar_rng(rgamma, 1, shape = 1, rate = 1)
x <- rvar_rng(rnorm, 10, mu, sigma)
x
```

split_chains

Split Chains

Description

Split chains by halving the number of iterations per chain and doubling the number of chains.

Usage

```
split_chains(x, ...)
```

Arguments

`x` (draws) A draws object or another R object for which the method is defined.
`...` Arguments passed to individual methods (if applicable).

Value

A draws object of the same class as `x`.

Examples

```
x <- example_draws()
niterations(x)
nchains(x)

x <- split_chains(x)
niterations(x)
nchains(x)
```

subset_draws	<i>Subset draws objects</i>
--------------	-----------------------------

Description

Subset [draws](#) objects by variables, iterations, chains, and draws indices.

Usage

```
subset_draws(x, ...)
```

```
## S3 method for class 'draws_matrix'
```

```
subset_draws(  
  x,  
  variable = NULL,  
  iteration = NULL,  
  chain = NULL,  
  draw = NULL,  
  regex = FALSE,  
  unique = TRUE,  
  ...  
)
```

```
## S3 method for class 'draws_array'
```

```
subset_draws(  
  x,  
  variable = NULL,  
  iteration = NULL,  
  chain = NULL,  
  draw = NULL,  
  regex = FALSE,  
  unique = TRUE,  
  ...  
)
```

```
## S3 method for class 'draws_df'
```

```
subset_draws(  
  x,  
  variable = NULL,  
  iteration = NULL,  
  chain = NULL,  
  draw = NULL,  
  regex = FALSE,  
  unique = TRUE,  
  ...  
)
```

```
## S3 method for class 'draws_list'
subset_draws(
  x,
  variable = NULL,
  iteration = NULL,
  chain = NULL,
  draw = NULL,
  regex = FALSE,
  unique = TRUE,
  ...
)

## S3 method for class 'draws_rvars'
subset_draws(
  x,
  variable = NULL,
  iteration = NULL,
  chain = NULL,
  draw = NULL,
  regex = FALSE,
  unique = TRUE,
  ...
)

## S3 method for class 'draws'
subset(x, ...)
```

Arguments

x	(draws) A draws object or another R object for which the method is defined.
...	Arguments passed to individual methods (if applicable).
variable	(character vector) The variables to select. All elements of non-scalar variables can be selected at once.
iteration	(integer vector) The iteration indices to select.
chain	(integer vector) The chain indices to select.
draw	(integer vector) The draw indices to be select. Subsetting draw indices will lead to an automatic merging of chains via merge_chains .
regex	(logical) Should variable should be treated as a (vector of) regular expressions? Any variable in x matching at least one of the regular expressions will be selected. Defaults to FALSE.
unique	(logical) Should duplicated selection of chains, iterations, or draws be allowed? If TRUE (the default) only unique chains, iterations, and draws are selected regardless of how often they appear in the respective selecting arguments.

Details

To ensure that multiple consecutive subsetting operations work correctly, `subset()` *repairs* the draws object before and after subsetting.

Value

A draws object of the same class as `x`.

Examples

```
x <- example_draws()
subset_draws(x, variable = c("mu", "tau"))
subset_draws(x, chain = 2)
subset_draws(x, iteration = 5:10, chain = 3:4)

# extract the first chain twice
subset_draws(x, chain = c(1, 1), unique = FALSE)

# extract all elements of 'theta'
subset_draws(x, variable = "theta")
```

`thin_draws`*Thin draws objects*

Description

Thin `draws` objects to reduce their size and autocorrelation in the chains.

Usage

```
thin_draws(x, thin, ...)

## S3 method for class 'draws'
thin_draws(x, thin, ...)
```

Arguments

`x` (draws) A draws object or another R object for which the method is defined.
`thin` (positive integer) The period for selecting draws.
`...` Arguments passed to individual methods (if applicable).

Value

A draws object of the same class as `x`.

Examples

```
x <- example_draws()
niterations(x)

x <- thin_draws(x, thin = 5)
niterations(x)
```

vctrs-compat *rvar vctrs compatibility*

Description

These functions implement compatibility with [vctrs-package](#) for *rvars*.

Usage

```
## S3 method for class 'rvar'  
vec_ptype2(x, y, ...)  
  
## Default S3 method:  
vec_ptype2.rvar(x, y, ..., x_arg = "x", y_arg = "y")  
  
## S3 method for class 'rvar'  
vec_cast(x, to, ...)  
  
## Default S3 method:  
vec_cast.rvar(x, to, ...)  
  
## S3 method for class 'rvar'  
vec_ptype2.rvar(x, y, ...)  
  
## S3 method for class 'rvar'  
vec_cast.rvar(x, to, ...)  
  
## S3 method for class 'rvar'  
vec_ptype2.double(x, y, ...)  
  
## S3 method for class 'double'  
vec_ptype2.rvar(x, y, ...)  
  
## S3 method for class 'double'  
vec_cast.rvar(x, to, ...)  
  
## S3 method for class 'rvar'  
vec_ptype2.integer(x, y, ...)  
  
## S3 method for class 'integer'  
vec_ptype2.rvar(x, y, ...)  
  
## S3 method for class 'integer'  
vec_cast.rvar(x, to, ...)  
  
## S3 method for class 'rvar'  
vec_ptype2.logical(x, y, ...)
```

```
## S3 method for class 'logical'
vec_ptype2.rvar(x, y, ...)

## S3 method for class 'logical'
vec_cast.rvar(x, to, ...)
```

Arguments

x, y	Vectors.
...	Further arguments passed to other functions.
x_arg, y_arg	Argument names for x and y.
to	Type to cast to.

Value

See the corresponding functions in [vctrs-package](#) for more information, or `vignette("s3-vector", package = "vctrs")` for examples.

See Also

[vctrs::vec_cast\(\)](#), [vctrs::vec_ptype2\(\)](#)

weights.draws	<i>Extract Weights from Draws Objects</i>
---------------	---

Description

Extract weights from [draws](#) objects, with one weight per draw. See [weight_draws](#) for details how to add weights to [draws](#) objects.

Usage

```
## S3 method for class 'draws'
weights(object, log = FALSE, normalize = TRUE, ...)
```

Arguments

object	(draws) A draws object.
log	(logical) Should the weights be returned on the log scale? Defaults to FALSE.
normalize	(logical) Should the weights be normalized to sum to 1 on the standard scale? Defaults to TRUE.
...	Arguments passed to individual methods (if applicable).

Value

A vector of weights, with one weight per draw.

See Also

[weight_draws](#), [resample_draws](#)

Examples

```
x <- example_draws()

# sample some random weights for illustration
wts <- rexp(ndraws(x))
head(wts)

# add weights
x <- weight_draws(x, weights = wts)

# extract weights
head(weights(x)) # defaults to normalized weights
head(weights(x, normalize=FALSE)) # recover original weights
head(weights(x, log=TRUE)) # get normalized log-weights

# add weights which are already on the log scale
log_wts <- log(wts)
head(log_wts)

x <- weight_draws(x, weights = log_wts, log = TRUE)
# extract weights
head(weights(x))
head(weights(x, log=TRUE, normalize = FALSE)) # recover original log_wts
```

weight_draws

Weight draws objects

Description

Add weights to [draws](#) objects, with one weight per draw, for use in subsequent weighting operations. For reasons of numerical accuracy, weights are stored in the form of unnormalized log-weights (in a variable called `.log_weight`). See [weights.draws\(\)](#) for details how to extract weights from draws objects.

Usage

```
weight_draws(x, weights, ...)

## S3 method for class 'draws_matrix'
weight_draws(x, weights, log = FALSE, ...)

## S3 method for class 'draws_array'
weight_draws(x, weights, log = FALSE, ...)
```

```
## S3 method for class 'draws_df'
weight_draws(x, weights, log = FALSE, ...)

## S3 method for class 'draws_list'
weight_draws(x, weights, log = FALSE, ...)

## S3 method for class 'draws_rvars'
weight_draws(x, weights, log = FALSE, ...)
```

Arguments

x	(draws) A draws object or another R object for which the method is defined.
weights	(numeric vector) A vector of weights of length <code>ndraws(x)</code> . Weights will be internally stored on the log scale (in a variable called <code>.log_weight</code>) and will not be normalized, but normalized (non-log) weights can be returned via the weights.draws() method later.
...	Arguments passed to individual methods (if applicable).
log	(logical) Are the weights passed already on the log scale? The default is FALSE, that is, expecting weights to be on the standard (non-log) scale.

Value

A draws object of the same class as x.

See Also

[weights.draws\(\)](#), [resample_draws\(\)](#)

Examples

```
x <- example_draws()

# sample some random weights for illustration
wts <- rexp(ndraws(x))
head(wts)

# add weights
x <- weight_draws(x, weights = wts)

# extract weights
head(weights(x)) # defaults to normalized weights
head(weights(x, normalize=FALSE)) # recover original weights
head(weights(x, log=TRUE)) # get normalized log-weights

# add weights which are already on the log scale
log_wts <- log(wts)
head(log_wts)

x <- weight_draws(x, weights = log_wts, log = TRUE)
# extract weights
```

```
head(weights(x))
head(weights(x, log=TRUE, normalize = FALSE)) # recover original log_wts
```

[.draws_array *Extract parts of a draws_array object*

Description

Extract parts of a draws_array object. They are strictly defined as arrays of 3 dimensions (iteration x chain x variable) so dropping any of the dimensions breaks the expected structure of the object. Accordingly, no dropping of dimensions is done by default even if the extracted slices are of length 1. If drop is manually set to TRUE and any of the dimensions is actually dropped, this will lead to dropping the "draws_array" class as well.

Usage

```
## S3 method for class 'draws_array'
x[i, j, ..., drop = FALSE]
```

Arguments

x, i, j, ..., drop
 Same as in the default extraction method but with drop being set to FALSE by default.

Value

An object of class "draws_array" unless any of the dimensions was dropped during the extraction.

[.draws_matrix *Extract parts of a draws_matrix object*

Description

Extract parts of a draws_matrix object. They are strictly defined as matrices (draws x variable) so dropping any of the dimensions breaks the expected structure of the object. Accordingly, no dropping of dimensions is done by default even if the extracted slices are of length 1. If drop is manually set to TRUE and any of the dimensions is actually dropped, this will lead to dropping the "draws_matrix" class as well.

Usage

```
## S3 method for class 'draws_matrix'
x[i, j, ..., drop = FALSE]
```


Arguments

x, *i*, *j*, ..., *drop*

Same as in the default extraction method but with *drop* being set to FALSE by default.

Value

An object of class "draws_matrix" unless any of the dimensions was dropped during the extraction.

Index

- * **diagnostics**
 - ess_basic, 22
 - ess_bulk, 23
 - ess_quantile, 25
 - ess_sd, 27
 - ess_tail, 28
 - mcse_mean, 33
 - mcse_quantile, 34
 - mcse_sd, 35
 - rhat, 55
 - rhat_basic, 56
 - rstar, 57
- * **formats**
 - draws, 7
 - draws_array, 10
 - draws_df, 11
 - draws_list, 13
 - draws_matrix, 15
 - draws_rvars, 18
- * **rfunc**
 - rdo, 47
 - rfunc, 53
 - rvar_rng, 71
- * **rvar-summaries**
 - rvar-summaries-over-draws, 64
 - rvar-summaries-within-draws, 67
 - rvar_is_finite, 70
- [.draws_array, 80
- [.draws_matrix, 80
- *** (rvar-matmult), 62
- all.rvar (rvar-summaries-over-draws), 64
- any.rvar (rvar-summaries-over-draws), 64
- as_draws (draws), 7
- as_draws_array (draws_array), 10
- as_draws_df (draws_df), 11
- as_draws_list (draws_list), 13
- as_draws_matrix (draws_matrix), 15
- as_draws_rvars (draws_rvars), 18
- as_function(), 20
- as_rvar, 4
- as_rvar(), 33, 61, 69
- bind_draws, 5
- cdf.rvar (rvar-dist), 61
- chain_ids (draws-index), 8
- chol.rvar, 6
- convergence (diagnostics), 7
- default_convergence_measures (draws_summary), 19
- default_mcse_measures (draws_summary), 19
- default_summary_measures (draws_summary), 19
- density.rvar (rvar-dist), 61
- diagnostic, 20
- diagnostics, 7, 21
- dim(), 4, 47, 60
- dimnames(), 4, 60
- draw_ids (draws-index), 8
- draws, 4–6, 7, 11, 13, 14, 16, 19, 37–39, 48–50, 53, 73, 75, 77, 78
- draws-index, 8
- draws_array, 8, 10, 13, 14, 16, 19, 30, 38, 40
- draws_df, 8, 11, 11, 14, 16, 19, 38, 41, 53, 58
- draws_list, 8, 11, 13, 13, 16, 19, 38, 42
- draws_matrix, 8, 11, 13, 14, 15, 19, 38, 43
- draws_of, 16
- draws_of(), 48, 54, 60
- draws_of<- (draws_of), 16
- draws_rvars, 8, 11, 13, 14, 16, 18, 38, 44
- draws_summary, 19
- E (rvar-summaries-over-draws), 64
- ess_basic, 22, 24, 26, 28, 29, 34–36, 56, 57, 59
- ess_basic(), 7
- ess_bulk, 23, 23, 26, 28, 29, 34–36, 56, 57, 59

- ess_bulk(), 7, 21, 22, 28
- ess_mean, 24
- ess_mean.default (ess_quantile), 25
- ess_median (ess_quantile), 25
- ess_quantile, 23, 24, 25, 28, 29, 34–36, 56, 57, 59
- ess_quantile(), 7
- ess_sd, 23, 24, 26, 27, 29, 34–36, 56, 57, 59
- ess_sd(), 7
- ess_tail, 23, 24, 26, 28, 28, 34–36, 56, 57, 59
- ess_tail(), 7, 21–23
- example_draws, 29
- extract_variable, 31
- extract_variable_matrix, 31
- extract_variable_matrix(), 22–24, 26–28, 33, 34, 36, 47, 55, 56

- format.rvar (print.rvar), 45

- is.finite.rvar
(rvar-summaries-over-draws), 64
- is.infinite.rvar
(rvar-summaries-over-draws), 64
- is.na.rvar (rvar-summaries-over-draws), 64
- is.nan.rvar
(rvar-summaries-over-draws), 64
- is_draws (draws), 7
- is_draws_array (draws_array), 10
- is_draws_df (draws_df), 11
- is_draws_list (draws_list), 13
- is_draws_matrix (draws_matrix), 15
- is_draws_rvars (draws_rvars), 18
- is_rvar, 32
- is_rvar(), 48
- iteration_ids (draws-index), 8

- logical, 63

- mad (rvar-summaries-over-draws), 64
- mad(), 20
- matrix multiplication, 17
- max.rvar (rvar-summaries-over-draws), 64
- mcse_mean, 23, 24, 26, 28, 29, 33, 35, 36, 56, 57, 59
- mcse_mean(), 7
- mcse_median (mcse_quantile), 34
- mcse_quantile, 23, 24, 26, 28, 29, 34, 34, 36, 56, 57, 59
- mcse_quantile(), 7
- mcse_sd, 23, 24, 26, 28, 29, 34, 35, 35, 56, 57, 59
- mcse_sd(), 7
- mean(), 20
- mean.rvar (rvar-summaries-over-draws), 64
- median(), 20
- median.rvar
(rvar-summaries-over-draws), 64
- merge_chains, 37, 74
- min.rvar (rvar-summaries-over-draws), 64
- mutate_variables, 38, 49

- names, 47
- nchains (draws-index), 8
- ndraws (draws-index), 8
- niterations (draws-index), 8
- numeric, 63
- nvariables (draws-index), 8

- option, 40–44
- order_draws, 39
- order_draws(), 50

- pillar::style_num(), 45
- posterior (posterior-package), 3
- posterior-package, 3
- Pr (rvar-summaries-over-draws), 64
- print(), 41–45
- print.draws_array, 40
- print.draws_df, 41
- print.draws_list, 42
- print.draws_matrix, 43
- print.draws_rvars, 44
- print.rvar, 45
- prod.rvar (rvar-summaries-over-draws), 64

- quantile.rvar (rvar-dist), 61
- quantile2, 46
- quantile2(), 21
- quasiquotation, 47

- range.rvar (rvar-summaries-over-draws), 64
- rdo, 47, 54, 72
- rdo(), 5, 60, 61, 69
- rename_variables, 39, 48

- rename_variables(), 9
- repair_draws, 49
- repair_draws(), 40
- repairs, 74
- resample_draws, 50, 78
- resample_draws(), 51, 79
- reserved_variables, 41–44, 52
- rfunc, 48, 53, 72
- rfunc(), 5, 60, 61, 69
- rhat, 23, 24, 26, 28, 29, 34–36, 55, 57, 59
- rhat(), 7, 21, 31, 56
- rhat_basic, 23, 24, 26, 28, 29, 34–36, 56, 56, 59
- rhat_basic(), 7
- rlang::as_function(), 53
- rstar, 23, 24, 26, 28, 29, 34–36, 56, 57, 57
- rstar(), 7
- rvar, 4–7, 16, 17, 19, 22–29, 32–36, 38, 45–48, 53–57, 59, 60–71, 76
- rvar(), 5
- rvar-dist, 61, 66, 68
- rvar-matmult, 62
- rvar-summaries-over-draws, 64, 68, 70
- rvar-summaries-within-draws, 66, 67
- rvar_all (rvar-summaries-within-draws), 67
- rvar_any (rvar-summaries-within-draws), 67
- rvar_apply, 68
- rvar_is_finite, 66, 68, 70
- rvar_is_infinite (rvar_is_finite), 70
- rvar_is_na (rvar_is_finite), 70
- rvar_is_nan (rvar_is_finite), 70
- rvar_mad (rvar-summaries-within-draws), 67
- rvar_max (rvar-summaries-within-draws), 67
- rvar_mean (rvar-summaries-within-draws), 67
- rvar_median (rvar-summaries-within-draws), 67
- rvar_min (rvar-summaries-within-draws), 67
- rvar_prod (rvar-summaries-within-draws), 67
- rvar_quantile (rvar-summaries-within-draws), 67
- rvar_range (rvar-summaries-within-draws), 67
- rvar_rng, 48, 54, 71
- rvar_rng(), 5, 48, 54, 60, 61, 69
- rvar_sd (rvar-summaries-within-draws), 67
- rvar_sum (rvar-summaries-within-draws), 67
- rvar_var (rvar-summaries-within-draws), 67
- sd (rvar-summaries-over-draws), 64
- sd(), 20
- split_chains, 72
- stats::density(), 62
- stats::quantile(), 47, 62
- str.rvar (print.rvar), 45
- subset.draws (subset_draws), 73
- subset_draws, 51, 73
- sum.rvar (rvar-summaries-over-draws), 64
- summarise_draws (draws_summary), 19
- summarize_draws (draws_summary), 19
- summary(), 19
- summary.draws (draws_summary), 19
- Summary.rvar (rvar-summaries-over-draws), 64
- summary.rvar (draws_summary), 19
- thin (thin_draws), 75
- thin_draws, 75
- tibble, 12, 21
- var (rvar-summaries-over-draws), 64
- variables, 39, 49
- variables (draws-index), 8
- variables<- (draws-index), 8
- variance.rvar (rvar-summaries-over-draws), 64
- vctrs-compat, 76
- vctrs-package, 76, 77
- vctrs::vec_cast(), 77
- vctrs::vec_ptype2(), 77
- vec_cast.rvar (vctrs-compat), 76
- vec_ptype2.double.rvar (vctrs-compat), 76

`vec_ptype2.integer.rvar` (`vctrs-compat`),
76
`vec_ptype2.logical.rvar` (`vctrs-compat`),
76
`vec_ptype2.rvar` (`vctrs-compat`), 76

`weight_draws`, 53, 77, 78, 78
`weight_draws()`, 51
`weights.draws`, 77
`weights.draws()`, 78, 79